

**Specification Sheet** 



# PowerEdge R6725

# **Versatility Meets Performance**

The new Dell PowerEdge R6725 is designed to be the foundation of your data center. This powerful server provides excellent performance, low-latency storage options and compute density in an air-cooled configuration.

### Breakthrough performance density

Delivering breakthrough performance density with multiple configuration options for traditional and emerging workloads including AI, high-performance compute (HPC), virtual desktop integration (VDI) and dense virtualization.

#### Striving for next-level compute

Our partnership with AMD allows us to provide customers with a powerful 2-socket 1U server that can handle a variety of workloads. The PowerEdge R6725 offers great flexibility with multiple configuration options to suit diverse customer needs.

- Maximize performance with two AMD 5<sup>th</sup> Generation EPYC<sup>™</sup> processors.
- · Memory density with DDR5 (up to 6 TB of RAM) memory capacity.
- Up to 3 x Gen 5 PCIe slots and dual OCP offering flexibility to meet workload requirements.

### Energy Efficiency through consolidation

Lower your total cost of ownership while reducing energy consumption and make the best use of existing data center space.

- Smart Cooling design allows most configurations to be air-cooled.
- Improved heat sinks for better thermal performance.

#### Cyber Resilient Architecture for Zero Trust IT environment & operations

Security is integrated into every phase of the PowerEdge lifecycle, including protected supply chain and factory-to-site integrity assurance. The Silicon-based root of trust anchors end-to-end boot resilience while Multi-Factor Authentication (MFA) and role-based access controls safeguard trusted operations.

#### Increase efficiency and accelerate operations with autonomous collaboration

The Dell OpenManage systems management portfolio tames the complexity of managing and securing IT infrastructure. Using Dell Technologies' intuitive end-to-end tools, IT can deliver a secure, integrated experience by reducing process and information silos to focus on growing the business. The Dell OpenManage portfolio is the key to your innovation engine, unlocking the tools and automation that help you scale, manage, and protect your technology environment.

## Sustainability

From recycled materials in our products and packaging, to thoughtful, innovative options for energy efficiency, the PowerEdge portfolio is designed to make, deliver, and recycle products to help reduce the carbon footprint and lower your operation costs. We even make it easy to retire legacy systems responsibly with Dell Technologies.

#### Rest easier with Dell Technologies Services

Maximize your PowerEdge Servers with comprehensive services designed to meet you wherever you are. Accelerate time to value in achieving high AI use cases with Professional Services for AI, choose from tailored deployment options with the ProDeploy Suite, receive proactive and predictive support with our ProSupport Suite, and so much more with our services available across 170 locations and backed by our 60K+ employees and partners

#### PowerEdge R6725

Dell PowerEdge R6725 is ideal for a variety of workloads:

- High-performance compute (HPC)
- Virtual desktop integration (VDI)
- Dense virtualization
- Artificial Intelligence (AI)

\* Feature not available at product launch in November,2025. Please refer to the product configurator page on Dell.com to confirm feature availability.

Feature	Technical Specifications		
Processor	Two 5th Generation AMD EPYC 9005 Series processors with up to 192 cores per processor		
Memory	24 DDR5 DIMM slots, supports RDIMM 6 TB max, speeds up to 6400 MT/s		
	Supports registered ECC DDR5 DIMMs only		
Storage controllers	Internal Controllers (RAID): PERC H365i, H965i, H975i		
	Internal Boot: Boot Optimized Storage Subsystem (BOSS-N1 DC-MHS)     External HBAs (non-RAID): HBA465e		
Drive Bays	Front bays:		
	4 x 3.5-inch SAS/SATA		
	8 x 2.5-inch Universal or U.2 / 10 x 2.5-inch SAS/SATA		
	10 x 2.5-inch with 4 x Universal		
	8 x EDSFF E3.S / 16 x EDSFF E3.S / 20 x EDSFF E3.S + Rear 2 x EDSFF E3.S		
Power Supplies	Platinum: 800W, 1100W		
	<ul> <li>Titanium: 800W, 1100W, 1500W, 1500W 277VAC &amp; HVDC, 1800W*</li> </ul>		
	• Telco: 1400 W -48VDC		
Cooling Options	Air cooling, Direct Liquid Cooling (DLC)		
Fans	Up to four sets (dual fan module) hot plug fans		
Dimensions	Height – 42.8 mm (1.68 inches)     Width – 482 mm (1.8 97 inches)		
	• Width – 482 mm (18.97 inches)		
	Depth – 816.921 mm (32.16 inches) with bezel		
Form Factor	1U rack server		
Embedded Management			
ű	iDRAC Direct		
	iDRAC RESTful API with Redfish		
	Racadm CLI		
	Quick Sync 2 wireless module		
Bezel	Optional Metal Bezel		
OpenManage Consoles	OpenManage Enterprise (OME)	OME Integration for VMware vCenter (with VMware	
	OME Power Manager	Aria Operations)	
	OME Services	<ul> <li>OME integration for Microsoft System Center</li> <li>OpenManage Integration for Windows Admin Center</li> </ul>	
	OME Update Manager     OME APEX AlOps Observability	Openivariage integration for windows Admin Center	
Mobility	N/A		
Tools	IPMI		
Integrations and Connections			
	RedHat Ansible Collections		
	Terraform Providers		
Change Management	Dell Repository Manager		
o o	Dell System Update		
	Enterprise Catalogs		
	Server Update Utility (SUU)		
Security	AMD Secure Encrypted Virtualization (SEV)	Secure Erase	
	AMD Secure Memory Encryption (SME)	Silicon Root of Trust	
	Cryptographically signed firmware	System Lockdown	
	Data at Rest Encryption (SEDs with local or external key mgmt)	TPM 2.0 FIPS, CC-TCG certified	
	Secure Boot	Chassis Intrusion Detection	
	Secured Component Verification (Hardware integrity check)		
GPU Options	Up to 3 x 75 W SW		
Ports	Front Ports	Rear Ports	
	1 x USB 2.0 Type-A (optional LCP KVM)     1 x USB 2.0 Type C (USST/DMC Direct)	1 x 1 Gb dedicated BMC Ethernet port	
	1 x USB 2.0 Type-C (HOST/BMC Direct)     1 x Mini DisplayPort (ontional LCP KVM)	<ul><li>2 x USB 3.1 Type-A</li><li>1 x VGA</li></ul>	
	1 x Mini DisplayPort (optional LCP KVM)	- I X VGA	
	Internal Port		
	• 1 x USB 3.1 Type-A		

Feature	Technical Specifications	
PCle	Up to three PCIe slots (x16 connector)	
	Slot 1: 1 x16 Gen5 Full Height or Low Profile	
	Slot 2: 1 x16 Gen5 Low Profile or 1 x16 OCP3.0	
	Slot 4: 1 x16 Gen5 Full Height or Low profile	
Gen5 PCIe slots	3	
OCP Network options	2 x OCP card 3.0 (optional) and 1GbE, 10GbE, 25GbE, 100GbE and 400GbE	
	Slot 2: 1 x16 Gen5 OCP 3.0	
	Slot 5: 1 x16 Gen5 OCP 3.0	
Embedded NIC	1 Gb dedicated BMC Ethernet port	
DPU Options	NVIDIA BlueField-3 2x200 GbE B3220	
	NVIDIA BlueField-3 1x400 GbE B3140H *	
PCIe Add-in Card (AIC) NIC	100 GbE and 400GbE; NDR VPI (400GbE); FC 32 / 64	
Operating System and Hypervisors	Canonical Ubuntu Server LTS	
	Microsoft Windows Server with Hyper-V	
	Red Hat Enterprise Linux	
	VMware ESXi	
	SUSE Linux Enterprise Server	
	For specifications and interoperability details, see Dell.com/OSsupport.	
OEM-ready version available	From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you. For more information, visit <b>Dell.com/OEM</b> .	

Note: From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you with our OEMR platforms, while XL platforms provide extended transitions and stability for OEM Solutions customers. For more information, visit Dell.com -> Solutions -> OEM Solutions.

#### **APEX on Demand**

APEX Flex on Demand Acquire the technology you need to support your changing business with payments that scale to match actual usage. For more information, visit www.delltechnologies.com/en-us/payment-solutions/flexible-consumption/flex-on-demand.htm.

#### Discover more about PowerEdge servers



Learn more about services for PowerEdge servers



Learn more about our systems management solutions



Search our Resource Library



Follow PowerEdge servers on X (formerly Twitter)



Contact a Dell Technologies Expert for Sales or Support

