



OEM PowerEdge XR7620

Short-depth accelerated data center-level compute, purpose-built for the edge

Dell Technology's short depth enterprise edge server

The new Dell OEM PowerEdge XR7620 is a short-depth 2U, 2-socket server with datacenter-level compute delivering high-performance, high-capacity and reduced latency. Purpose-built for the edge, the PowerEdge XR7620 is designed for the most demanding workloads including industrial automation, video analytics, point of sale analytics, AI inferencing and edge point device aggregation.

Purpose-built for the Edge

- Built rugged to operate in temperatures from -5°C to 55°C; MIL 810H* and NEBS Level 3* tested
- Offers easy serviceability with reversible I/O & power
- Short-depth (472 mm) chassis to fit in space constrained environments
- Withstand dusty and harsh environments with an optional lockable smart filtered bezel for extra physical security

Datacenter-level compute

- Two Intel® Xeon® Scalable Processors with up to 32 cores per processor for ultimate edge performance
- Integration with PCIe Gen5 doubles the data transfer rate from PCIe Gen4 for faster more efficient data transfer
- Includes latest memory DDR5, 50% memory capacity over DDR4, increasing bandwidth

Acceleration where it's needed

- Up to two double-wide GPU accelerators to support demanding workloads
- E3 NVME storage utilizes a limited-space design with more storage density, making it ideal for data-intensive workloads at the edge

Cyber Resilient Architecture for Zero Trust IT environment & operations

Security is integrated into every phase of the PowerEdge lifecycle, including protected supply chain and factory-to-site integrity assurance. Silicon-based root of trust anchors end-to-end boot resilience while Multi-Factor Authentication (MFA) and role-based access controls ensure trusted operations.

Increase efficiency and accelerate operations with an autonomous infrastructure

The Dell OpenManage™ systems management portfolio delivers a secure, efficient, and comprehensive solution for PowerEdge servers. Simplify, automate and centralize one-to-many management with the OpenManage Enterprise console and iDRAC.

Sustainability

From recycled materials in our products and packaging, to thoughtful, innovative options for energy efficiency, the PowerEdge portfolio is designed to make, deliver, and recycle products to help reduce the carbon footprint and lower your operation costs. We even make it easy to retire legacy systems responsibly with Dell Technologies Services.

Rest easier with Dell Technologies Services

Maximize your PowerEdge Servers with comprehensive services ranging from [Consulting](#), to [ProDeploy](#) and [ProSupport suites](#), [Data Migration](#) and more – available across 170 countries and backed by our 60K+ employees and partners.

NOTE: * indicates for limited configurations

OEM PowerEdge XR7620

The Dell OEM PowerEdge XR7620 is a high-performance server designed and optimized for edge use cases like

- Industrial automation
- Video analytics
- Point of sale analytics
- AI inferencing
- Edge point device aggregation

Feature	Technical Specifications	
Processor	Two 4th Generation Intel® Xeon® Scalable processors with up to 32 cores per processor	
Memory	<ul style="list-style-type: none"> 16 DDR5 DIMM slots, supports RDIMM 1 TB max, speeds up to 4800 MT/s. Supports registered ECC DDR5 DIMMs only 	
Storage controllers	<ul style="list-style-type: none"> Internal Controllers: PERC H965i, PERC H755, PERC H355, HBA355i Software RAID: S160 	<ul style="list-style-type: none"> Internal Boot: Boot Optimized Storage Subsystem (BOSS-N1): HWRAID 1, 2 x M.2 NVMe SSDs (cold swap) or internal USB module
Drive Bays	Front bays: Up to 4 x 2.5-inch SAS/SATA/NVMe SSD drives, 61.44 TB max, Up to 8 x E3.S NVMe direct drives, 51.2 TB max	
Hot swap redundant	<ul style="list-style-type: none"> 1800 W Titanium 200—240 VAC or 240 HVDC 	<ul style="list-style-type: none"> 1100 W Titanium 100—240 VAC or 240 HVDC, hot swap redundant
Power Supplies	<ul style="list-style-type: none"> 1400 W Platinum 100—240 VAC or 240 HVDC 	<ul style="list-style-type: none"> 1100 W -48 — (-60) VDC
Cooling Options	<ul style="list-style-type: none"> Air cooling 	
Fans	<ul style="list-style-type: none"> Six cold swap cooling fans 	
Dimensions	Rear Accessed configuration	Front Accessed configuration
	<ul style="list-style-type: none"> Height: 86.8 mm (3.41 inches) Width: 482.6 mm (19 inches) Depth: 448.8 mm (17.6 inches) Ear to rear wall 496.3 mm (19.53 inches) with bezel 471.8 mm (18.57 inches) without bezel 	<ul style="list-style-type: none"> Height: 86.8 mm (3.41 inches) Width: 482.6 mm (19 inches) Depth: 572 mm (22.51 inches) with bezel 471.8 mm (18.57 inches) without bezel
Weight	Max 21.16 kg (46.64 pounds)	
Form Factor	2U rack server	
Embedded Management	<ul style="list-style-type: none"> iDRAC9, iDRAC Direct, iDRAC RESTfulAPI with Redfish, iDRAC Service Module 	
Bezel	Optional security bezel with dust filter (dust sensor available only for Front Accessed configuration systems)	
OpenManage Software	<ul style="list-style-type: none"> CloudIQ for PowerEdge plug in OpenManage Enterprise OpenManage Power Manager plugin 	<ul style="list-style-type: none"> OpenManage Service plugin OpenManage Update Manager plugin
Mobility	OpenManage Mobile	
OpenManage Integrations	<ul style="list-style-type: none"> Microsoft System Center OpenManage Integration with Windows Admin Center OpenManage Integration with ServiceNow OpenManage Integration for Microsoft System Center 	<ul style="list-style-type: none"> OpenManage Enterprise Integration for VMware vCenter Red Hat Ansible Modules Terraform Providers VMware vCenter and vRealize Operations Manager
Security	<ul style="list-style-type: none"> Cryptographically signed firmware Data at Rest Encryption (SEDs with local or external key mgmt) Secure Boot Secure Erase 	<ul style="list-style-type: none"> Secured Component Verification (Hardware integrity check) Silicon Root of Trust System Lockdown (requires iDRAC9 Enterprise or Datacenter) TPM 2.0 FIPS, CC-TCG certified, TPM 2.0 China NationZ
GPU options	Up to 5 x 75 W (Single Width Full Height/Half Length, Low Profile) GPU or up to 2 x 300 W (Double Width Full Height/Full Length)	
Embedded NIC	2 x 1 GbE LOM	
Network options	1 x OCP card 3.0 (optional)	
Ports	For Rear Accessed configuration	For Front Accessed configuration
	<p>Front Ports:</p> <ul style="list-style-type: none"> 1 x iDRAC Direct (Micro-AB USB) port, 1 x USB 2.0 <p>Internal Ports:</p> <ul style="list-style-type: none"> 1 x USB 3.0 (optional) <p>Rear Ports:</p> <ul style="list-style-type: none"> 1 x USB 2.0, 1 x iDRAC dedicated port, 1 x USB 3.0, 1 x Serial port (optional on slot 5), 1 x VGA 	<p>Front Ports:</p> <ul style="list-style-type: none"> 1 x USB 2.0, 1 x iDRAC dedicated port, 1 x USB 3.0, 1 x Serial port (optional on slot 5), 1 x VGA, 1 x iDRAC Direct (Micro-AB USB) port <p>Internal Ports:</p> <ul style="list-style-type: none"> 1 x USB 3.0 (optional) <p>Rear Ports: NA</p>
PCIe	2 CPU configuration: Up to 5 PCIe slots (4 x16 Gen4/5, 1 x16 LP Gen4)	
Operating System and Hypervisors	<ul style="list-style-type: none"> Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server 	<ul style="list-style-type: none"> VMware ESXi Canonical Ubuntu Server LTS <p>For specifications and interoperability details, see Dell.com/OSsupport.</p>
OEM-ready version available	From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you. For more information, visit Dell.com -> Solutions -> OEM Solutions.	

APEX Flex on Demand

Acquire the technology you need to support your changing business with payments that scale to match actual usage. For more information, visit <https://www.delltechnologies.com/en-us/payment-solutions/flexible-consumption/flex-on-demand.htm>.

Discover more about PowerEdge servers



[Learn more](#) about our PowerEdge servers



[Learn more](#) about our systems management solutions



[Search](#) our Resource Library



[Follow](#) PowerEdge servers on Twitter



Contact a Dell Technologies Expert for [Sales](#) or [Support](#)