



PowerEdge R770

Drive efficiency in your datacenter through maximum performance with optimized power.

Boost Datacenter Efficiencies and Performance

The Dell PowerEdge R770 is a 2U, dual-socket rack server designed for high performance computing with optimal power efficiency and balanced performance to boost your data center productivity. It balances advanced computing power with virtualization, artificial intelligence inferencing, cloud-native applications, hyperscale workloads, and scale out databases.

Purpose-built for enterprise and scalable infrastructures, the PowerEdge R770 offers standardization that easily integrates into existing environments, equipped with two Intel® Xeon® 6 processors with E-cores and P-cores it offers up to 1.69x better performance per watt than previous models, improving power efficiency and increasing rack density. The addition of GPU support further amplifies computational power, ensuring high performance with lower energy use. These servers are available in rear I/O hot aisle and front I/O cold aisle configurations. The front I/O cold aisle improves serviceability, reduces maintenance time, and enhances efficiency, reliability, and uptime, supporting your sustainability goals by optimizing cooling and energy use. It also features Dell's Smart Power and Cooling Technology, optimized for air cooling to significantly reduce energy consumption, contributing to long-term operational savings.

Cyber Resilient Architecture for Zero Trust IT environment & operations

Security is integrated into every phase of the PowerEdge lifecycle, including protected supply chain and factory-to-site integrity assurance. The Silicon-based root of trust anchors end-to-end boot resilience while Multi-Factor Authentication (MFA) and role-based access controls safeguard trusted operations.

Increase efficiency and accelerate operations with autonomous collaboration

The Dell OpenManage systems management portfolio tames the complexity of managing and securing IT infrastructure. Using Dell Technologies' intuitive end-to-end tools, IT can deliver a secure, integrated experience by reducing process and information silos in order to focus on growing the business. The Dell OpenManage portfolio is the key to your innovation engine, unlocking the tools and automation that help you scale, manage, and protect your technology environment.

Sustainability

From recycled materials in our products and packaging, to thoughtful, innovative options for energy efficiency, the PowerEdge portfolio is designed to make, deliver, and recycle products to help reduce the carbon footprint and lower your operation costs. We even make it easy to retire legacy systems responsibly with Dell Technologies.

Rest easier with Dell Technologies Services

Maximize your PowerEdge Servers with comprehensive services designed to meet you wherever you are. Accelerate time to value in achieving high AI use cases with [Professional Services for AI](#), choose from tailored deployment options with the [ProDeploy Suite](#), receive proactive and predictive support with our [ProSupport Suite](#), and so much more with our services available across 170 locations and backed by our 60K+ employees and partners.

PowerEdge R770

The Dell PowerEdge R770 is powered by Intel Xeon 6 Processors, DDR5 Memory, NVMe BOSS, Energy Star compliant, advanced cooling for cloud environments. Ideal for:

- Virtualization
- Artificial Intelligence Inferencing
- Cloud-native applications
- Hyperscale workloads
- Scale out Databases

NOTE: This document provides a comprehensive list of product features. However, features marked with an asterisk (*) may not be available at launch but introduced in future updates. Please note that this document does not confirm the availability or release timeline of any feature. For the most accurate and up-to-date information on feature availability, please refer to the product configurator page on dell.com.

Feature	Technical Specifications		
Processor	Two Intel Xeon 6 Processors with up to 144 E-cores or 86 P-cores per processor		
Memory	<ul style="list-style-type: none">32 DDR5 DIMM slots, supports RDIMM 8 TB max, speeds up to 6400 MT/sSupports registered ECC DDR5 DIMMs only		
Storage controllers	<ul style="list-style-type: none">Internal Boot: Boot Optimized Storage Subsystem (BOSS-N1 DC-MHS): HWRAID 1, 2 x M.2 NVMe SSDs or M.2 Interposer board (DC-MHS): 2 x M.2 NVMe SSDs or USBInternal controllers: Front PERC H965i, Front PERC H975i, Front PERC H365i		
Front and Rear Bays	<ul style="list-style-type: none">No backplane configurationUp to 8 x EDSFF E3.S Gen5 NVMe max 491.52 TB also comes with FIO configurationUp to 16 x EDSFF E3.S Gen5 NVMe max 983.04 TB also comes with FIO configurationUp to 32 x EDSFF E3.S Gen5 NVMe max 1966.08 TBUp to 8 x 2.5 inch SATA/NVMe max 491.52 TBUp to 8 x 2.5-inch Universal max 491.52 TBUp to 16 x 2.5 inch SATA max 61.44TBUp to 24 x 2.5 inch SATA max 92.16 TBUp to 16 x 2.5 inch SATA + 8 x 2.5-inch NVME max 552.96 TBUp to 40 x EDSFF E3.S Gen5 NVMe max 2457.6 TBUp to 4 x EDSFF E3.S Gen5 NVMe max 245.76 TB on the rear		
Hot swap Power Supplies	<ul style="list-style-type: none">800 W Platinum 100—240 VAC or 240 VDC1100 W Platinum 100—240 VAC or 240 VDC1500 W Titanium 100—240 VAC or 240 VDC1100 W Titanium 100—240 VAC or 240 VDC3200 W Titanium 200—240 VAC or 240 VDC800 W Titanium 100—240 VAC or 240 VDC3200 W 277 VAC and 336 HVDC Titanium1400 W -48VDC 60mm1500 W 277 VAC and 336 HVDC Titanium*2400 W Titanium 100—240 VAC or 240 VDC*1800 W HLAC Titanium 200—240 VAC or 240 VDC*		
Cooling Options	<ul style="list-style-type: none">Air cooling and Direct Liquid Cooling <p>Note: DLC is a rack solution and requires rack manifolds and a cooling distribution unit (CDU) to operate.</p>		
Fans	<ul style="list-style-type: none">High performance Silver (HPR SLVR) fans/High performance Gold (HPR GOLD) fansUp to 6 hot swappable fans		
Dimensions and Weight	<ul style="list-style-type: none">Height – 86.8 mm (3.42 inches)Width – 482 mm (18.97 inches)Weight – 28.53 kg (62.89 pound)	<p>Depth (for rear I/O configuration)</p> <ul style="list-style-type: none">802.40 mm (31.59 inches) with bezel801.51 mm (31.56 inches) without bezel <p>Depth (for front I/O configuration)</p> <ul style="list-style-type: none">814.52 mm (32.07 inches) without bezel <p>Note: The front I/O configuration does not support the bezel.</p>	
Form Factor	2U rack server		
Embedded Management	<ul style="list-style-type: none">iDRACiDRAC DirectiDRAC RESTful API with RedfishRACADM CLIiDRAC Service Module (iSM)Quick Sync 2 wireless moduleNativeEdge Endpoint*NativeEdge Orchestrator*		
Bezel	<ul style="list-style-type: none">Optional security bezel		
Security	<ul style="list-style-type: none">Cryptographically signed firmwareData at Rest Encryption (SEDs with local or external key mgmt)Secure BootSecured Component Verification (Hardware integrity check)Silicon Root of TrustSystem LockdownSystem Lockdown (requires iDRAC10 Enterprise or Datacenter)Chassis Intrusion DetectionTPM 2.0 FIPS, CC-TCG certified		
Network options	OCP NIC card 3.0 : Two slots on the front or two slots on the rear		
BOSS	Slot 34: one BOSS slot Slot 6: one BOSS slot		
GPU options	Up to 6 x 75 W FHHL or up to 2 x 450 W DWFL		
Ports	Front Ports: <ul style="list-style-type: none">1 x USB 2.0 Type C port1 x USB 2.0 Type A port (optional)1 x Mini-DisplayPort (optional)1 x DB9 Serial (with front I/O configuration)1 x Dedicated ethernet port for iDRAC management	Rear Ports: <ul style="list-style-type: none">1 x Dedicated ethernet port for iDRAC management1 x VGA2 x USB 3.1 Type A ports	Internal Ports: <ul style="list-style-type: none">1 x USB 3.1 Type A port

Feature	Technical Specifications
PCIe	<ul style="list-style-type: none"> • Upto two PCIe slots (x16 connectors) • Slot 31 1 x 16 Gen5 Full Height - Half Length or Full Length on front Riser • Slot 36 1 x 16 Gen5 Full Height - Half Length on front Riser • Upto eight PCIe slots (x8 and x16 connectors) • Slot 1 1 x 8 Gen5 Full Height - Half Length • Slot 2 1 x 16 Gen5 Dual Width Full Length or 1 x 8 Gen5 Full Height - Half Length • Slot 3 1 x 16 Gen5 Full Height - Half Length or 1 x 16 Gen5 Low Profile • Slot 4 1 x 16 Gen5 Full Height - Half Length or 1 x 8 Gen5 Full Height - Half Length or 1 x 8 or 1 x 16 OCP 3.0 • Slot 5 2 x 16 Gen5 Full Height - Half Length or 1 x 8 Gen5 Full Height - Half Length • Slot 7 1 x 16 Gen5 Full Height - Half Length or 1 x 16 Gen5 Dual Width Full Length or 1 x 8 Gen5 Full Height - Half Length • Slot 8 1 x 16 Gen5 Full Height - Half Length or 1 x 8 Gen5 Full Height - Half Length • Slot 9 1 x 16 Gen5 Full Height - Half Length or 1 x 8 Gen5 Full Height - Half Length or 1 x 16 Low Profile- Half Length
Operating System and Hypervisors	<ul style="list-style-type: none"> • Canonical Ubuntu Server LTS • Microsoft Windows Server with Hyper-V (P-Core only) • Red Hat Enterprise Linux • SUSE Linux Enterprise Server • VMware ESXi • Dell NativeEdge OS* <p>For specifications and interoperability details, see Dell.com/OSsupport.</p>
OEM-ready version available	From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you. For more information, visit Dell.com -> Solutions -> OEM Solutions.

Features marked with an asterisk () may not be available at product launch. Please refer to the product configurator page on Dell.com to confirm feature availability.

NOTE: From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you with our OEMR platforms, while XL platforms provide extended transitions and stability for OEM Solutions customers. For more information, visit Dell.com -> Solutions -> OEM Solutions.

APEX Flex on Demand

Acquire the technology you need to support your changing business with payments that scale to match actual usage. For more information, visit <https://www.delltechnologies.com/en-us/payment-solutions/flexible-consumption/flex-on-demand.htm>.

Discover more about PowerEdge servers



Learn more about services for PowerEdge servers



Learn more about our systems management solutions



Search our Resource Library



Follow PowerEdge servers on X (formerly Twitter)



Contact a Dell Technologies Expert for Sales or Support