

Z-Series	100/400GbE Multi-rate		100GbE Multi-rate
Overview	High-performance, high-density 100/400GbE multi-rate aggregation switch		High-performance, high-density 100GbE multi-rate aggregation switch
Models	Z9432F-ON	Z9332F-ON	Z9264F-ON
NPU	Broadcom® Trident4-X11	Broadcom Tomahawk™3	Broadcom Tomahawk2
Form factor	1 U	1 U	2 U
Performance			
Switching capacity (Tbps, full duplex)	25.6	25.6	12.8
Forwarding capacity (Bpps)	5.2	5.1	2.5
Buffer size (MB)	132	64	42
Latency (ns)	<850	<700	300 L2/400 L3
Ports*			
10GbE (SFP+)	144 (breakout) + 2	144 (breakout) + 2	128 (breakout) + 2
25GbE (SFP28)	144 (breakout)	144 (breakout)	128 (breakout)
40GbE (QSFP+)	64 (breakout)	64 (breakout)	64
50GbE (QSFP28)	128 (breakout) + 16 (QSA) (PAM4)	128 (breakout) + 16 (QSA) (PAM4)	128 (breakout) + 2 (25G NRZ)
50GbE (SFP56)	128 (breakout)		N/A
100GbE (QSFP28)	128 (breakout)	128 (breakout)	64
200GbE (QSFP28-DD)	64 (breakout)	64 (breakout)	N/A
400GbE (QSFP56-DD)	32	32	N/A
Power and cooling			
Power consumption (W)	1404 (max)/900 (normal)	1500 (max)/900 (normal)	1404 (max)/340 (normal)
Power options	AC or DC	AC	AC or DC
Redundant power	2 hot swappable		
Airflow	Normal or Reverse, can be reversed in the field**		
Features			
Operating Systems	Dell EMC SmartFabric OS10 and select 3rd party OS; Enterprise SONiC Distribution by Dell Technologies		
Industry-standard CLI (Console, Telnet, SSHv1/v2)	Dell EMC SmartFabric OS10 and select 3rd party OS		
iSCSI optimization	iSCSI optimization and FSB		iSCSI aware (detect and prioritize iSCSI traffic into pre-defined QoS); iSCSI Auto-Configuration (switch configuration routine for automated setup and optimal performance with Dell EqualLogic or Compellent arrays)
Max VLANs (Configured)	4K per port		
Max MAC entries	156K	8K	160K
Link aggregation (Groups/Members)	16 links per group, 128 groups	16 links per group, 128 groups	64 links per group, 128 groups
Max routes (IPv4/IPv6)	340K/310K	400K/300K	128K/64K
Jumbo frames	9,216 bytes		
IPv4 routing	OSPF, BGP		
IPv6 routing	MP-BGP, OSPFv3		
Multicast routing	PIM-SM, PIM-SSM		
VXLAN	L2 & L3 16k	Not supported	8k Bridging only

*Port configuration capacities represent HW supportable modes. SW support varies by OS.

**Z9332 is orderable only as IO/PSU but can be reversed in the field

S-Series	10/25/40/50/100/200/400GbE					
Overview	High-performance, open networking 25GbE for compute and storage connectivity or 100/400GbE spine/leaf switches offer optimum flexibility and cost effectiveness					
Models	S5212F-ON	S5224F-ON	S5232F-ON	S5248F-ON	S5296F-ON	S5448F-ON
NPU	Broadcom Trident3-X5		Broadcom Trident3-X7	Broadcom Trident3-X5	Broadcom Trident3-X7	Broadcom Trident4-X9
Form factor	1 U compact	1 U	1 U	1 U	2 U	1 U
Performance						
Switching capacity (full duplex) (Tbps)	2.16	2.16	6.4	4.0	6.4	16
Forwarding capacity (Bpps)	880 Mpps	1.42	4.8	3.0	4.8	2.6
Buffer size (MB)	32			82		
Latency (ns)	906	881	877	847	850	1135
Ports						
10GbE (SFP+)	12 + 12 (breakout)	24 + 16 (breakout)	124 (breakout) + 2	48 + 32 (breakout)	96 + 32 (breakout)	48 + 24 (breakout) + 2
25GbE (SFP28)	12 + 12 (breakout)	24 + 16 (breakout)	124 (breakout)	48 + 32 (breakout)	96 + 32 (breakout)	48 + 24 (breakout)
40GbE (QSFP28)	3	4	32	4 + 4 (breakout)	8	16 (breakout)
50GbE (QSFP28)	6 (breakout)	8 (breakout)	64 (breakout)	16 (breakout)	16 (breakout)	16 (Breakout)
50GbE (SFP56)	N/A			48 + 24 (Breakout)		
100GbE (QSFP28)	3	4	32	4 + 4 (breakout)	8	32 (breakout)
100GbE (SFP56-DD)	N/A			48		
400GbE (QSFP56-DD)	N/A			8		
Power and cooling						
Max. power consumption (W)	304 (max)/140 (normal)	455 (max)/200 (normal)	635 (max)/360 (normal)	647 (max)/310 (normal)	893 (max)/457 (normal)	920 (max)/250 (normal)
Power options	AC or DC					
Redundant power	2 fixed	2 hot swappable				
Airflow	Normal or Reverse	Normal or Reverse, can be reversed in the field				
Features						
Operating Systems	Dell EMC SmartFabric OS10 and select 3rd party OS; Enterprise SONiC Distribution by Dell Technologies*					
Industry-standard CLI (Console, Telnet, SSHv1/v2)	Dell EMC SmartFabric OS10 and select 3rd party OS					
iSCSI optimization	iSCSI optimization and FSB					
Max VLANs (Configured)**	4K per port					
Max MAC entries**	160K				256K	
Link aggregation (Groups/Members)**	16 links per group, 128 groups					
Max routes (IPv4/IPv6)**	128K/64K				875K/310K (IPv6/64 ALPM), 240K (IPv6/128 ALPM)	
Jumbo frames	9,216 bytes					
IPv4 routing	OSPF, BGP					
IPv6 routing	MP-BGP, OSPFv3					
Multicast routing	PIM-SM, PIM-SSM					
VXLAN	Routing and Bridging					

*In roadmap for S5448F-ON

**Hardware maximum. Refer to Network Operating System (NOS) scalability for actual supported numbers with the NOS.

S-Series		1/10/25/40/50/100GbE					
Overview		High-performance open networking 10GbE top-of-rack switches with 100GbE uplinks for compute and storage connectivity					
Models		S4112F-ON	S4112T-ON	S4128F-ON	S4128T-ON	S4148F-ON	S4148T-ON
NPU		Broadcom Maverick					
Form factor		1 U compact		1 U		1 U	
Performance							
Switching capacity (full duplex) (Gbps)		840		960		1,760	
Forwarding capacity (Mpps)		625		720		1,320	
Buffer size (MB)		12					
Latency (ns)		<800		<800		<2.3	
						<800	
						<2.3 μs	
Ports							
1/10GBase-T		N/A		12		N/A	
1GbE (SFP)		12 + 12 (breakout)		N/A		28	
10GbE (SFP+)		12 + 12 (breakout)		12 (breakout)		N/A	
25GbE (SFP28)		12 (breakout)		8 (breakout)		16 (breakout)	
40GbE (QSFP28)		3		2		4 + 2 (QSFP+)	
50GbE (QSFP28)		6 (breakout)		4 (breakout)		8 (breakout)	
100GbE (QSFP28)		3		2		4	
Power and cooling							
Power consumption (W)		180 (max)/90 (normal)		200 (max)/120 (normal)		260 (max)/160 (normal)	
Power options		AC		AC or DC		300 (max)/250 (normal)	
Redundant power supplies		Fixed, redundant power supply and fan		2		370 (max)/200 (normal)	
Airflow		Normal or Reverse		Normal or Reverse, can be reversed in the field		440 (max)/320 (normal)	
Features							
Operating Systems		Dell EMC SmartFabric OS10 and select 3rd party OS					
Industry-standard CLI (Console, Telnet, SSHv1/v2)		Dell EMC SmartFabric OS10 and select 3rd party OS					
iSCSI optimization		iSCSI optimization and FSB					
Max VLANs (Configured)		4K/500		500 L3 VLANs		500 L3 VLANs	
Max MAC entries		272K					
Link aggregation (Groups/Members)		32 links per group, 128 groups					
Max routes (IPv4/IPv6)		200K/130K					
Jumbo frames		9,216 bytes					
IPv4 routing		OSPF, BGP					
IPv6 routing		OSPFv3, MP-BGP					
Multicast routing		PIM-SM, PIM-SSM					
VXLAN		Routing and Bridging					

1GbE open networking switches for data center management

Overview		1GbE top-of-rack open networking switch	
Models	S3048-ON	N3248TE-ON	
NPU	Broadcom Helix4	Broadcom Trident3-X3	
Form factor	1 U		
Performance			
Switching capacity (full duplex) (Gbps)	260	576	
Forwarding Capacity (Mpps)	131	800	
Buffer size (MB)	4	8	
Latency (µs)	3.7	2.38	
Ports			
1GBase-T	48	48	
10GbE (SFP+)	4	4	
100GbE (QSFP28)	N/A	12	
Power and cooling			
Power consumption (W)	87 (max)/65 (normal)	212 (max)	
Power options	AC	AC or DC	
Redundant power supplies	2 hot swappable redundant power supplies. 1 PSU included, 2nd PSU optional.		
Airflow	Normal or Reverse	Normal or Reverse	
Features			
Stacking	Up to 6 units		
Operating system	Dell EMC OS9, Dell EMC SmartFabric OS10	Dell EMC SmartFabric OS10 and select 3rd party OS; Enterprise SONiC Distribution by Dell Technologies	
Industry-standard CLI	Dell EMC Networking OS9, Dell EMC SmartFabric OS10 and select 3rd party OS	Dell EMC SmartFabric OS10 and select 3rd party OS	
iSCSI optimization storage features	N/A		
Max VLANs (Configured)	4096/1000		
Max MAC entries	64K	55K	
Link aggregation (groups/Members)	16 links per group, 128 groups		
Max routes (IPv4/IPv6)	16K/8K	8K/4K	
Jumbo frames (Bytes)	9,216		
IPv4 routing	OSPF, BGP	IPv4 and IPv6 functionality including BGP, VRF, BFD, PIM-SM/SSM, OSPFv2/v3	
IPv6 routing	OSPFv3, BGPv6, IS-IS		
Multicast routing	PIM-SM, PIM-SSM		
VXLAN	Routing & Bridging		

[Learn more at DellTechnologies.com/Networking](https://www.dell.com/technologies.com/Networking)