PowerEdge R450

D¢LLTechnologies

Spec Sheet

1U, value and density-focused, built for general purpose IT

The Dell EMC PowerEdge R450, with 3rd generation Intel® Xeon® Scalable processors, offers exceptional value and density with excellent performance.



Innovate at scale with challenging and emerging workloads

The Dell EMC PowerEdge R450 is a 1U, two-socket entry-level server that offers the best value for organizations seeking updated processing, I/O, and storage capabilities in a dense form factor. It lets you:

- Add additional power: Adds additional power with up to two 3rd generation Intel Xeon Scalable processors with up to 24 cores per socket
- Built with faster memory: Supports up to 16 DDR4 RDIMMS at 2933 MT/sec
- Improve throughput, reduce latency with up to 2 PCIe Gen4 slots
- Include flexible local storage: Offers up to 8x 2.5-inches HDDs or SSDs; or up to 4x 3.5-inches HDDs or SSDs
- · Support distinctive needs: Perfect for smaller infrastructures and light virtualization demands

Increase efficiency and accelerate operations with autonomous compute infrastructure

The Dell EMC OpenManage systems management portfolio tames the complexity of managing and securing IT infrastructure. Using Dell Technologies' intuitive end-to-end tools, IT can deliver a secure, integrated experience by reducing process and information silos in order to focus on growing the business. The Dell EMC OpenManage portfolio is the key to your innovation engine, unlocking the tools and automation that help you scale, manage, and protect your technology environment.

- · Built-in telemetry streaming, thermal management, and RESTful API with Redfish offer streamlined visibility and control for better server management
- · Intelligent automation lets you enable cooperation between human actions and system capabilities for added productivity
- · Integrated change management capabilities for update planning and seamless, zero-touch configuration and implementation
- Full-stack management integration with Microsoft, VMware, ServiceNow, Ansible and many other tools

Built-in proactive resilience through a complete portfolio of solutions

From the silicon and supply chain all the way to asset retirement, know that your servers are safe and secure with innovative Dell EMC and Intel technologies. We give you the confidence of cyber resilience with enterprise class security that minimizes risk for

• Start strong with platform security features, even before the server is built, including Secured Component Verification and Silicon Root of

any organization, from small business to hyperscale.

- Stay strong with continuous innovations that bolster cyber resilience, like OpenManage Secure Enterprise Key Manager and Automatic Certificate Enrollment
- · Outmaneuver threats with intelligence, automation, and recovery tools that include iDRAC9 Telemetry, BIOS live scanning, and Rapid OS recovery

PowerEdge R450

Power your innovation with the Dell EMC PowerEdge R450, the 1U 2-socket server that's built for high density and added value.

- · Small IT Infrastructure
- Light VM (virtual machine density)
- Small Business Specific

Features	Technical Specifications	
Processor	Up to two 3rd Generation Intel Xeon Scalable processors, with up to 24 cores per processor	
Memory	Memory 16 DDR4 DIMM slots, supports RDIMM max 1 TB, speeds up to 2933 MT/s	
Storage controllers	 Internal controllers (RAID): PERC H345, PERC H355, HBA355i, PERC H745, PERC H755, S150 Internal Boot: Internal Dual SD Module or Boot Optimized Storage Subsystem (BOSS-S1): HWRAID 2x M.2 SSDs or USB External PERC (RAID): PERC H840 External HBA (non-RAID) HBA355e 	
Drive Bays	Front bays: • Up to 4 x 3.5-inch SAS/SATA (HDD/SSD) max 64 TB • Up to 8 x 2.5-inch SAS/SATA (HDD/SSD) max 61.4 TB	
Power Supplies	 600W Platinum Mixed Mode (100-240Vac or 240Vdc) hot swap redundant 700W Titanium Mixed Mode (200-240Vac or 240Vdc) hot swap redundant 800W Platinum Mixed Mode (100-240Vac or 240Vdc) hot swap redundant 1100W Titanium Mixed Mode (100-240Vac or 240Vdc) hot swap redundant 1100W -48Vdc hot swap redundant (CAUTION: only works with -48Vdc to -60Vdc power input) 	
Cooling options	Air cooling	
Fans	Standard (STD) fans or High performance SLVR fans Up to seven cold swap fans	
Dimensions	 Height – 42.8 mm (1.7 inches) Width – 482 mm (18.97 inches) Depth – 734.95 mm (28.92 inches) – without bezel 748.79 mm (29.47 inches) – with bezel 	
Form Factor	1U rack server	
Embedded Management	iDRAC9 iDRAC Direct iDRAC RESTful API with Redfish iDRAC Service Module Quick Sync 2 wireless module	
Bezel	Optional LCD bezel or security bezel	
OpenManage Software	OpenManage Enterprise OpenManage Power Manager plugin OpenManage SupportAssist plugin OpenManage Update Manager plugin	
Mobility	OpenManage Mobile	
Integrations and Connections	OpenManage Integrations BMC Truesight Microsoft System Center Red Hat Ansible Modules VMware vCenter and vRealize Operations Manager	OpenManage Connections IBM Tivoli Netcool/OMNIbus IBM Tivoli Network Manager IP Edition Micro Focus Operations Manager Nagios Core Nagios XI
Security	 Cryptographically signed firmware Secure Boot Secure Erase Silicon Root of Trust System Lockdown (requires iDRAC9 Enterprise or Datacenter) TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China NationZ 	
Embedded NIC	2 x 1 GbE LOM	
Network Options	1 x OCP 3.0	
GPU Options	NA	
Ports	Front Ports 1 x Dedicated iDRAC Direct micro-USB 1 x USB 2.0 1 x VGA Internal Ports	Rear Ports 1 x USB 2.0 1 x Serial (optional) 1 x iDRAC ethernet port 1 x USB 3.0 2 x Ethernet 1 x VGA
200	• 1 x USB 3.0 (optional)	
PCle	 2 x PCle Gen4 slots + PCle Gen 2 x16 Gen4 (x16 connector) low profile, half length 1 x4 Gen3 (x8 connector) low profile, half length 	

Features	Technical Specifications
Operating System and Hypervisors	Canonical Ubuntu Server LTS
	Citrix Hypervisor
	Microsoft Windows Server with Hyper-V
	Red Hat Enterprise Linux
	SUSE Linux Enterprise Server
	VMware ESXi
	For specifications and interoperability details, see Dell.com/OSsupport.
OEM-ready version available	From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you. For more information, visit Dell.com/OEM.

Recommended support and services

Dell ProSupport Plus for critical systems or Dell ProSupport for premium hardware and software support for your PowerEdge solution. Consulting and deployment offerings are also available. Contact your Dell representative today for more information. Availability and terms of Dell Services vary by region. For more information, visit Dell.com/ServiceDescriptions.

Dell Technologies on demand

Consume technology, infrastructure and services any way you want with Dell Technologies on Demand, the industry's broadest end-to-end portfolio of flexible consumption and as-a-Service solutions. For more information, visit: www. delltechnologies.com/ondemand.

Discover more about PowerEdge servers



Learn more about our PowerEdge servers



Learn more about our systems management solutions



Search our Resource Library



Follow PowerEdge servers on Twitter



Contact a Dell Technologies Expert for Sales or Support

