

PowerEdge R770



Drive efficiency in your datacenter through maximum performance with optimized power.

Boost Datacenter Efficiencies and Performance

The Dell PowerEdge R770 is a 2U, dual-socket rack server designed for high performance computing with optimal power efficiency and balanced performance to boost your data center productivity. It balances advanced computing power with virtualization, artificial intelligence inferencing, cloud-native applications, hyperscale workloads, and scale out databases.

Purpose-built for enterprise and scalable infrastructures, the PowerEdge R770 offers standardization that easily integrates into existing environments, equipped with two Intel® Xeon® 6 processors with E-cores and P-cores it offers up to 1.69x better performance per watt than previous models, improving power efficiency and increasing rack density. The addition of GPU support further amplifies computational power, ensuring high performance with lower energy use. These servers are available in rear I/O hot aisle and front I/O cold aisle configurations. The front I/O cold aisle improves serviceability, reduces maintenance time, and enhances efficiency, reliability, and uptime, supporting your sustainability goals by optimizing cooling and energy use. It also features Dell's Smart Power and Cooling Technology, optimized for air cooling to significantly reduce energy consumption, contributing to long-term operational savings.

Cyber Resilient Architecture for Zero Trust IT environment & operations

Security is integrated into every phase of the PowerEdge lifecycle, including protected supply chain and factory-to-site integrity assurance. The Silicon-based root of trust anchors end-to-end boot resilience while Multi-Factor Authentication (MFA) and role-based access controls safeguard trusted operations.

Increase efficiency and accelerate operations with autonomous collaboration

The Dell OpenManage systems management portfolio tames the complexity of managing and securing IT infrastructure. Using Dell Technologies' intuitive end-to-end tools, IT can deliver a secure, integrated experience by reducing process and information silos in order to focus on growing the business. The Dell OpenManage portfolio is the key to your innovation engine, unlocking the tools and automation that help you scale, manage, and protect your technology environment.

Sustainability

From recycled materials in our products and packaging, to thoughtful, innovative options for energy efficiency, the PowerEdge portfolio is designed to make, deliver, and recycle products to help reduce the carbon footprint and lower your operation costs. We even make it easy to retire legacy systems responsibly with Dell Technologies.

Rest easier with Dell Technologies Services

Maximize your PowerEdge Servers with comprehensive services designed to meet you wherever you are. Accelerate time to value in achieving high AI use cases with [Professional Services for AI](#), choose from tailored deployment options with the [ProDeploy Suite](#), receive proactive and predictive support with our [ProSupport Suite](#), and so much more with our services available across 170 locations and backed by our 60K+ employees and partners.

PowerEdge R770

The Dell PowerEdge R770 is powered by Intel Xeon 6 Processors, DDR5 Memory, NVMe BOSS, Energy Star compliant, advanced cooling for cloud environments. Ideal for:

- Virtualization
- Artificial Intelligence Inferencing
- Cloud-native applications
- Hyperscale workloads
- Scale out Databases

*Expected to be available during the future releases. Planned Offerings are subject to change and may not be released as originally designed.

Feature	Technical Specifications		
Processor	Two Intel Xeon 6 Processors with up to 144 E-cores or 86 P-cores per processor		
Memory	<ul style="list-style-type: none"> 32 DDR5 DIMM slots, supports RDIMM 8 TB max, speeds up to 6400 MT/s Supports registered ECC DDR5 DIMMs only 		
Storage controllers	<ul style="list-style-type: none"> Internal Boot: Boot Optimized Storage Subsystem (BOSS-N1 DC-MHS): HWRAID 1, 2 x M.2 NVMe SSDs or M.2 Interposer board (DC-MHS): 2 x M.2 NVMe SSDs or USB Internal controllers: Front PERC H965i, Front PERC H975i*, Front PERC H365i 		
Front and Rear Bays	<ul style="list-style-type: none"> No backplane configuration Up to 8 x EDSFF E3.S Gen5 NVMe (SSD) max 122.88 TB also comes with FIO configuration Up to 16 x EDSFF E3.S Gen5 NVMe (SSD) max 245.76 TB also comes with FIO configuration Up to 32 x EDSFF E3.S Gen5 NVMe (SSD) max 489.6 TB Up to 8 x 2.5 inch SAS/SATA/NVMe (SSD) max 122.88 TB Up to 8 x 2.5-inch Universal max 245.6 TB Up to 16 x 2.5 inch SAS/SATA (SSD) max 61.44 TB Up to 24 x 2.5 inch SAS/SATA (SSD) max 92.16 TB Up to 16 x 2.5 inch SAS/SATA (SSD) + 8 x 2.5-inch NVMe max 92.16 TB Up to 40 x EDSFF E3.S Gen5 NVMe (SSD) max 614.4 TB* Up to 4 x EDSFF E3.S Gen5 NVMe (SSD) max 61.2 TB on the rear* 		
Hot swap Power Supplies	<ul style="list-style-type: none"> 800 W Platinum 100—240 VAC or 240 VDC 1100 W Platinum 100—240 VAC or 240 VDC 1500 W Titanium 100—240 VAC or 240 VDC 1100 W Titanium 100—240 VAC or 240 VDC* 3200 W Titanium 200—240 VAC or 240 VDC 800 W Titanium 100—240 VAC or 240 VDC* 3200 W 277 VAC and 336 HVDC Titanium* 1400 W -48VDC 60mm* 1500 W 277 VAC and 336 HVDC Titanium* 2400 W Titanium 100—240 VAC or 240 VDC* 1800 W HLAC Titanium 200—240 VAC or 240 VDC* 		
Cooling Options	<ul style="list-style-type: none"> Air cooling and Direct Liquid Cooling <p>Note: DLC is a rack solution and requires rack manifolds and a cooling distribution unit (CDU) to operate.</p>		
Fans	<ul style="list-style-type: none"> High performance Silver (HPR SLVR) fans/High performance Gold (HPR GOLD) fans Up to 6 hot swappable fans 		
Dimensions and Weight	<ul style="list-style-type: none"> Height – 86.8 mm (3.42 inches) Width – 482 mm (18.97 inches) Weight – 28.53 kg (62.89 pound) 	Depth (for rear I/O configuration) <ul style="list-style-type: none"> 802.40 mm (31.59 inches) with bezel 801.51 mm (31.56 inches) without bezel Depth (for front I/O configuration) <ul style="list-style-type: none"> 814.52 mm (32.07 inches) without bezel <p>Note: The front I/O configuration does not support the bezel.</p>	
Form Factor	2U rack server		
Embedded Management	<ul style="list-style-type: none"> iDRAC iDRAC Direct iDRAC RESTful API with Redfish RACADM CLI iDRAC Service Module (iSM) NativeEdge Endpoint NativeEdge Orchestrator 		
Bezel	<ul style="list-style-type: none"> Optional security bezel 		
Security	<ul style="list-style-type: none"> Cryptographically signed firmware Data at Rest Encryption (SEDs with local or external key mgmt) Secure Boot Secured Component Verification (Hardware integrity check) Silicon Root of Trust System Lockdown System Lockdown (requires iDRAC10 Enterprise or Datacenter) Chassis Intrusion Detection TPM 2.0 FIPS, CC-TCG certified 		
Network options	4 x OCP NIC 3.0 cards (optional) and 1GbE*, 10GbE*, 25GbE, 100GbE and 400GbE* Slot 4 1 x 8 or 1 x 16 Gen5 OCP 3.0 Slot 10 1 x 8 or 1 x 16 OCP 3.0 Slot 34 1 x 16 Gen5 OCP 3.0 on front riser Slot 38 1 x 16 Gen 5 OCP 3.0 on front riser		
BOSS	Slot 34 1 x 4 BOSS Slot 6 1 x 4 BOSS		
GPU options	Up to 6 x 75 W FHHL* or up to 2 x 350 W DWFL		
Ports	Front Ports: <ul style="list-style-type: none"> 1 x USB 2.0 Type C port 1 x USB 2.0 Type A port (optional) 1 x Mini-DisplayPort (optional) 1 x DB9 Serial (with front I/O configuration) 1 x Dedicated ethernet port for iDRAC management 	Rear Ports: <ul style="list-style-type: none"> 1 x Dedicated ethernet port for iDRAC management 1 x VGA 2 x USB 3.1 Type A ports 	Internal Ports: <ul style="list-style-type: none"> 1 x USB 3.1 Type A port

Feature	Technical Specifications
PCIe	<ul style="list-style-type: none"> • Upto two PCIe slots (x16 connectors) • Slot 3 1 x 16 Gen5 Full Height - Half Length or Full Length on front Riser • Slot 3 6 1 x 16 Gen5 Full Height - Half Length on front Riser • Upto eight PCIe slots (x8 and x16 connectors) • Slot 1 1 x 8 Gen5 Full Height - Half Length • Slot 2 1 x 16 Gen5 Dual Width Full Length or 1 x 8 Gen5 Full Height - Half Length • Slot 3 1 x 16 Gen5 Full Height - Half Length or 1 x 16 Gen5 Low Profile • Slot 4 1 x 16 Gen5 Full Height - Half Length or 1 x 8 Gen5 Full Height - Half Length or 1 x 8 or 1 x 16 OCP 3.0 • Slot 5 2 x 16 Gen5 Full Height - Half Length or 1 x 8 Gen5 Full Height - Half Length • Slot 7 1 x 16 Gen5 Full Height - Half Length or 1 x 16 Gen5 Dual Width Full Length or 1 x 8 Gen5 Full Height - Half Length • Slot 8 1 x 16 Gen5 Full Height - Half Length or 1 x 8 Gen5 Full Height - Half Length • Slot 9 1 x 16 Gen5 Full Height - Half Length or 1 x 8 Gen5 Full Height - Half Length or 1 x 16 Low Profile- Half Length
Operating System and Hypervisors	<ul style="list-style-type: none"> • Canonical Ubuntu Server LTS • Microsoft Windows Server with Hyper-V (P-Core only) • Red Hat Enterprise Linux • SUSE Linux Enterprise Server • VMware ESXi <p>For specifications and interoperability details, see Dell.com/OSsupport.</p>
OEM-ready version available	From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you. For more information, visit Dell.com -> Solutions -> OEM Solutions.

Note: From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you with our OEMR platforms, while XL platforms provide extended transitions and stability for OEM Solutions customers. For more information, visit Dell.com -> Solutions -> OEM Solutions.

APEX Flex on Demand

Acquire the technology you need to support your changing business with payments that scale to match actual usage. For more information, visit <https://www.delltechnologies.com/en-us/payment-solutions/flexible-consumption/flex-on-demand.htm>.

Discover more about PowerEdge servers



Learn more about services for PowerEdge servers



Learn more about our systems management solutions



Search our Resource Library



Follow PowerEdge servers on X (formerly Twitter)



Contact a Dell Technologies Expert for Sales or Support