



## Dell EMC Integrated System for Microsoft Azure Stack HCI

### Dell EMC - Microsoft certified and validated HCI Solution with end to end support

Dell EMC Integrated System for Microsoft Azure Stack HCI delivers a fully productized, validated and supported hyperconverged (HCI) solution that enables organizations to modernize their infrastructure for improved application uptime and performance, simplified management and operations, and lower total cost of ownership. Azure Stack HCI combines the software-defined compute, storage and networking features of Microsoft Azure Stack HCI OS with AX nodes from Dell Technologies to offer the high performance, scalable and secure foundation needed for a software-defined infrastructure. Comprehensive management with Dell EMC OpenManage Integration with Windows Admin Center, rapid time to value with Dell EMC ProDeploy options, and solution-level Dell EMC ProSupport complete this modern portfolio.

### Azure Stack HCI OS subscription available through Dell Cloud Solution Provider (CSP) program

New and existing customers can purchase their Azure subscription from Dell (or transfer to Dell) to activate their Azure Stack HCI OS. Additional Azure services will be supported in the future.

### Key Features of Azure Stack HCI:

- AX nodes from Dell Technologies offer:
  - Flexible and scalable infrastructure configurations across four different models for varying application performance, capacity or location needs
  - Pre-configured and optimized features such as caching and storage tiering
  - Hardware innovations such as RDMA networking and high-performance SSD drives
- Azure Stack HCI OS delivers new improved feature set including data deduplication, increased scalability, mirror accelerated parity and cluster sets.
- Dell EMC OpenManage Integration with Microsoft Windows Admin Center (WAC) simplifies management, configuration and monitoring.
- Dell EMC Networking 10/25/100GbE switches are fully qualified to enable a complete hyperconverged infrastructure solution.
- Dell EMC ProDeploy and Dell EMC ProSupport service deliver professional onsite deployment and one contact technical support.

“Dell EMC did the work to build their nodes to have the maximum amount of power and storage in a 2U device that conforms and is on catalog for Storage Spaces Direct. It was really an easy design to put forward and to consolidate our existing Hyper-V virtual machines on to.”

Lee Harrison  
Microsoft Solutions Architect, Fasthosts

Detailed specifications for the distinct platforms are shown in the tables below:

AX-750	
Storage Configuration	All Flash (All-SSD)
Chassis Configurations	24 x 2.5" front bay drives
Processors	Dual socket Intel Xeon Scalable, Ice Lake EP Processors (Silver/Gold/Platinum options)
Memory	128 GB to 4 TB DDR4
Storage controller	Internal HBA 355i 12Gbps SAS HBA Controller (NON-RAID)
Internal Boot Storage	BOSS S2 with Dual M.2 240 GB or 480 GB (RAID 1)
Storage for Cache Min/Max	-
RI = read intensive	
WI = write intensive	
MU = mixed use	
Storage for Capacity Min/Max	Minimum: 4 x 800GB = 3.2 TB Maximum: 24 x 7.68TB = 184.3 TB
RI = read intensive	- Options for SAS/vSAS devices
WI = write intensive	- Both MU and RI devices (RI at >1.92 TB capacities)
MU = mixed use	- WI capacity at 800 GB
Min/Max Raw Storage	3.2 to 184.3 TB
	Integrated LOM: 2 x 1 GbE Base-T Broadcom
	Add-in-Card (required) Mellanox Connect-X5 (Dual Port 25 GbE) or Mellanox Connect-X6 DX (Dual Port 100 GbE)
Network cards	OCP 3.0 Card (optional) Intel X710 Dual Port 10GbE SFP+, OCP NIC 3.0 or Intel X710 Quad Port 10GbE SFP+, OCP NIC 3.0 or Intel X710-T4L Quad Port 10GbE BASE-T, OCP NIC 3.0 or Intel X710-T2L Dual Port 10GbE BASE-T, OCP NIC 3.0 or Broadcom 57414 Dual Port 10/25GbE SFP28, OCP NIC 3.0 or Broadcom 57504 Quad Port 10/25GbE SFP28, OCP NIC 3.0 or Broadcom 57416 Dual Port 10GbE BASE-T Adapter, OCP NIC 3.0 or Broadcom 57412 Dual Port 10GbE SFP+, OCP NIC 3.0
HCI Software	Microsoft Azure Stack HCI OS (factory preinstalled) Windows Admin Center (WAC)
Out of Band Management	Integrated Dell Remote Access Controller (iDRAC) 9 Enterprise or Datacenter IPMI 2.0 compliant Quick Sync2 (Optional)
Integrations	Dell EMC OpenManage Integration with Windows Admin Center
Services	ProSupport and ProSupport Plus, ProDeploy, ProDeploy Plus with add-on for Azure Stack HCI Call-routing, phone home, and automated case creation supported with Secure Connect Gateway 5.0 Consulting Services for Azure Stack HCI iDRAC Service Module (iSM) 4.1.0.0
Security	Trusted Platform Module 2.0 v3
Power Supplies	Dual, Hot-plug, Redundant Power Supply (1+1), 1100/1400/2400 W
Form Factor	2U Rack

# AX-650

Storage Configuration	All Flash (All-SSD)	All Flash (All-NVMe)	Hybrid (SSD + HDD)
Chassis Configurations	10 x 2.5" SAS Chassis Up to 10 SSD front drives (SAS/vSAS)	10 x 2.5" NVMe Chassis Up to 10 NVMe front drives	10 x 2.5" SAS Chassis Up to 10 HDD front drives
Processors	Dual socket Intel Xeon Scalable, Ice Lake EP Processors (Silver/Gold/Platinum options)		
Memory	128 GB to 4 TB DDR4		
Storage controller	Internal HBA 355i 12Gbps SAS HBA Controller (NON-RAID)		
Internal Boot Storage	BOSS S2 with Dual M.2 240 GB or 480 GB (RAID 1)		
Storage for Cache Min/Max RI = read intensive WI = write intensive MU = mixed use	-		Minimum: 1.6 TB 2 x 800 GB MU SAS Maximum: 7.68 TB 2 x 3.84TB MU SAS/vSAS
Storage for Capacity Min/max RI = read intensive WI = write intensive MU = mixed use	Minimum: 4 x 800GB = 3.2 TB Maximum: 10 x 7.68TB = 76.8 TB - Options for SAS/vSAS devices - Both MU and RI devices (RI >1.92 TB) WI capacity at 800 GB	Minimum: 4 x 1.6TB = 6.4 TB Maximum: 10 x 7.68TB = 76.8 TB - Both MU and RI devices (RI >1.92 TB)	Minimum: 4 x 2.4 TB = 9.6 TB Maximum: 8 x 2.4 TB = 19.2 TB 4/6/8 x 2.4 TB SAS 10K 2.5" HDDs
Min/Max Raw Storage	3.2 to 76.8 TB	6.4 to 76.8 TB	9.6 to 19.2 TB
Network cards	Integrated LOM: 2 x 1 GbE Base-T Broadcom  Add-in-Card (required) Mellanox Connect-X5 (Dual Port 25 GbE) or Mellanox Connect-X6 DX (Dual Port 100 GbE)  OCP 3.0 Card (optional) Intel X710 Dual Port 10GbE SFP+, OCP NIC 3.0 or Intel X710 Quad Port 10GbE SFP+, OCP NIC 3.0 or Intel X710-T4L Quad Port 10GbE BASE-T, OCP NIC 3.0 or Intel X710-T2L Dual Port 10GbE BASE-T, OCP NIC 3.0 or Broadcom 57414 Dual Port 10/25GbE SFP28, OCP NIC 3.0 or Broadcom 57504 Quad Port 10/25GbE SFP28, OCP NIC 3.0 or Broadcom 57416 Dual Port 10GbE BASE-T Adapter, OCP NIC 3.0 or Broadcom 57412 Dual Port 10GbE SFP+, OCP NIC 3.0		
HCI Software	Microsoft Azure Stack HCI OS (factory preinstalled) Windows Admin Center (WAC)		
Out of Band Management	Integrated Dell Remote Access Controller (iDRAC) 9 Enterprise or Datacenter IPMI 2.0 compliant Quick Sync2 (Optional)		
Integrations	Dell EMC OpenManage Integration with Windows Admin Center		
Services	ProSupport and ProSupport Plus, ProDeploy, ProDeploy Plus with add-on for Azure Stack HCI Call-routing, phone home, and automated case creation supported with Secure Connect Gateway 5.0 Consulting Services for Azure Stack HCI iDRAC Service Module (iSM) 4.1.0.0		
Security	Trusted Platform Module 2.0 v3		
Power Supplies	Dual, Hot-plug, Redundant Power Supply (1+1), 1100/1400 W		
Form Factor	1U Rack		

## AX-7525

Storage Configuration	All Flash (All-NVMe)	All Flash (NVMe + SSD)
Chassis Configurations	24 x 2.5" front bay drives 16 x 2.5" front bay drives	24 x 2.5" front bay drives
Processors	Dual socket, 2nd / 3rd Gen AMD EPYC (Rome/Milan) Processor	
Memory	128 GB to 2 TB (8/16/32/64 GB DDR4; speeds up to 3200 MT/s)	
Storage controller	-	Internal HBA 355i
Internal Boot Storage	BOSS with dual M.2 240GB or 480GB (RAID 1)	BOSS S2 with Dual M.2 240 or 480 GB (RAID 1)
Storage for Cache RI = read intensive WI = write intensive MU = mixed use	-	2, 3, 4 or 8 x PCIe Gen 4 NVMe drives 1.6/3.2/6.4 TB (MU)
Storage for Capacity	4 – 24 x PCIe Gen 4 NVMe drives: 1.6/3.2/6.4 TB (MU) 3.84/7.68 TB (RI)	4 – 16 x SAS/vSAS/SATA SSDs: 960/1.92/3.84/7.68 TB SAS/vSAS/SATA (RI) 800/1600/3200 SAS (MU) 960/1.92/3.84 TB vSAS/SATA (MU)
Min/Max Raw Storage	6.4 to 184.32 TB	3.2 to 122.88 TB
Network cards	Add-in-cards: 1-2 x Mellanox CX5 (Dual Port 10/25 GbE) 1-2 x Mellanox CX6 DX (Dual Port 40/100 GbE)  LOM: On-Board Broadcom 5720 Dual Port 1Gb LOM  Optional OCP: Broadcom 57416 Dual Port 10 GbE Base-T OCP 3.0 or Broadcom 57414 Dual Port 10/25 GbE OCP SFP28 OCP 3.0 or Intel X710 Quad Port 10 GbE SFP+, OCP NIC 3.0 or Intel X710 Dual Port 10 GbE SFP+, OCP NIC 3.0	Add-in-cards: 1-4 x Mellanox CX5 (Dual Port 10/25 GbE) 1-4 x Mellanox CX6 DX (Dual Port 40/100 GbE)  LOM: On-Board Broadcom 5720 Dual Port 1Gb LOM  Optional OCP: Broadcom 57416 Dual Port 10 GbE Base-T OCP 3.0 or Broadcom 57414 Dual Port 10/25 GbE OCP SFP28 OCP 3.0 or Intel X710 Quad Port 10 GbE SFP+, OCP NIC 3.0 or Intel X710 Dual Port 10 GbE SFP+, OCP NIC 3.0
HCI Software	Microsoft Azure Stack HCI OS (factory preinstalled) Microsoft Windows Admin Center (WAC)	
Out of Band Management	Integrated Dell Remote Access Controller (iDRAC) 9 Enterprise or Datacenter IPMI 2.0 compliant Quick Sync2 (Optional)	
Integrations	Dell EMC OpenManage Integration with Windows Admin Center	
Services	ProSupport and ProSupport Plus, ProDeploy, ProDeploy Plus with add-on for Azure Stack HCI Call-routing, phone home, and automated case creation supported with Secure Connect Gateway 5.0 Consulting Services for Azure Stack HCI iDRAC Service Module (iSM) 4.1.0.0	
Security	Trusted Platform Module 2.0 v3	
Power Supplies	Dual, Hot-plug, Redundant Power Supply (1+1), 1400 W Dual, Hot-plug, Redundant Power Supply (1+1), 2400 W	
Form Factor	2U Rack	

## AX-6515


Storage Configuration	All Flash (All-SSD)
Chassis Configurations	8 x 2.5" front bay drives
Processors	Single socket, 2nd / 3rd Gen AMD EPYC (Rome/Milan) Processor
Memory	64 GB to 1 TB (8/16/32/64 GB DDR4; speeds up to 3200 MT/s)
Storage controller	Internal HBA330 12Gbps SAS HBA Controller (NON-RAID)
Internal Boot Storage	BOSS with dual M.2 240GB or 480GB (RAID 1)
Storage for Cache WI = write intensive MU = mixed use	-
Storage for Capacity	4 to 8 x up to 7.68 TB SAS/ vSAS/ SATA SSDs
Min/Max Raw Storage	3.2 to 61.44 TB
Network cards	Add-in-cards: 1 x Mellanox CX5 (Dual Port 10/25 GbE) or 1 x Mellanox CX6 DX (Dual Port 40/100 GbE) or 1 x Qlogic/Marvell QL41262 DP 10/25 GbE  LOM: On-Board Broadcom 5720 Dual Port 1Gb LOM Mezz: Broadcom 57416 Dual Port 10 GbE SFP+/Base-T Network LOM Mezz Card or Broadcom 57414 Dual Port 25 GbE SFP28 LOM Mezz Card
HCI Software	Microsoft Azure Stack HCI OS (factory preinstalled) Windows Admin Center (WAC)
Out of Band Management	Integrated Dell Remote Access Controller (iDRAC) 9 Enterprise or Datacenter IPMI 2.0 compliant Quick Sync2 (Optional)
Integrations	Dell EMC OpenManage Integration with Windows Admin Center
Services	ProSupport and ProSupport Plus, ProDeploy, ProDeploy Plus with add-on for Azure Stack HCI Call-routing, phone home, and automated case creation supported with Secure Connect Gateway 5.0 Consulting Services for Azure Stack HCI iDRAC Service Module (iSM) 4.1.0.0
Security	Trusted Platform Module 2.0
Power Supplies	Dual, Hot-plug, Redundant Power Supply (1+1), 550W
Form Factor	1U Rack

# AX-740xd

Storage Configuration	Hybrid (SSD + HDD)		Hybrid (NVMe + HDD)		Hybrid (NVMe + SSD)	All flash (All-NVMe)	All flash (All-SSD)
Chassis Configurations	18 x 3.5" drives 12 x 3.5" front bay 4 x 3.5" mid bay 2 x 3.5" rear bay		12 x 3.5" front bay drives	24 x 2.5" front bay drives	24 x 2.5" front bay drives	24 x 2.5" front bay drives with up to 12 x NVMe drives	24 x 2.5" front bay drives
Processors	Dual socket Intel Xeon Scalable Processors, Cascade Lake (CL/CL-R), Select Silver/Gold/Platinum options						
Memory	96 GB to 1.5 TB (8/16/32/64 GB DDR4; supports RDIMM; speeds up to 3200MT/s)						
Storage controller	Internal HBA330 12Gbps SAS HBA Controller (NON-RAID)						
Internal Boot Storage	BOSS with dual M.2 240GB or 480GB (RAID 1)						
Storage for Cache WI = write intensive MU = mixed use	Up to 6 x 800 GB to 3.84 TB SAS (WI/MU) / SATA (MU) SSDs	2 or 4 x 800 GB to 3.84 TB SAS (WI/ MU) / SATA (MU) SSDs	2 to 4 x 1600 GB to 6400 GB PCIe NVMe (MU) SSDs	2 to 4 x 1600 GB to 6400 GB PCIe NVMe (MU) SSDs	-	-	-
Storage for Capacity	Up to 12 x 2/4/8/12/16 TB NL-SAS/ SATA HDDs	4 or 8 x 2/4/8/12/16 TB NL-SAS/ SATA HDDs	4 to 20 x 2 TB SATA or 2.4 TB SAS 10K HDDs	4 to 20 x 960 GB to 7.68 TB SAS/vSAS/SATA (MU) SSDs	4 to 12 x 1.6 TB to 6.4 TB PCIe NVMe (MU) SSDs	4 to 24 x 800 GB to 3.84 TB SAS or 960 GB to 3.84 TB SATA or 3.84 TB to 7.68 TB vSAS SSDs (WI or MU highly recommended)	-
Min/Max Raw Storage	24 to 192 TB	8 to 128 TB	8 to 48 TB	3.84 to 153.6 TB	6.4 to 76.8 TB	3.2 to 184.32 TB	-
Network cards	Add-in-Card: 1 or 2 Mellanox Connect-X4 LX (Dual Port 25 GbE) or 1 or 2 x Qlogic QL41262 (Dual Port 25 GbE)	Add-in-Card: 1 or 2 Mellanox Connect-X4 LX (Dual Port 25 GbE) or 1 - 4 x Qlogic QL41262 (Dual Port 25 GbE) or 1 or 2 Mellanox CX5 (Dual Port 100 GbE)	Add-in-Card: 1 or 2 Mellanox Connect-X4 LX (Dual Port 25 GbE) or 1 - 4 x Qlogic QL41262 (Dual Port 25 GbE) or 1 or 2 Mellanox CX5 (Dual Port 100 GbE)	Add-in-Card: 1 or 2 Mellanox Connect-X4 LX (Dual Port 25 GbE) or 1 - 4 x Qlogic QL41262 (Dual Port 25 GbE) or 1 or 2 Mellanox CX5 (Dual Port 100 GbE)	Add-in-Card: 1 or 2 Mellanox Connect-X4 LX (Dual Port 25 GbE) or 1 or 2 x Qlogic QL41262 (Dual Port 25 GbE) or 1 Mellanox CX5 (Dual Port 100 GbE)	Add-in-Card: 1 or 2 Mellanox Connect-X4 LX (Dual Port 25 GbE) or 1 - 4 x Qlogic QL41262 (Dual Port 25 GbE) or 1 Mellanox CX5 (Dual Port 100 GbE)	Add-in-Card: 1 or 2 Mellanox Connect-X4 LX (Dual Port 25 GbE) or 1 - 4 x Qlogic QL41262 (Dual Port 25 GbE) or 1 or 2 Mellanox CX5 (Dual Port 100 GbE)
	<p>NDC*: Dual Port Intel X710 (10 GbE) + Dual Port Intel i350 (1 GbE) or Dual Port Broadcom 57412 (10 GbE) + Dual Port Broadcom 5720 (1 GbE) or QLogic FastLinQ 41164 Quad Port 10GbE SFP+ or QLogic FastLinQ 41164 Quad Port 10GbE BASE-T</p> <p>* more options available</p>						
HCI Software	Microsoft Azure Stack HCI OS (factory preinstalled) Windows Admin Center (WAC)						
Out of Band Management	Integrated Dell Remote Access Controller (iDRAC) 9 Enterprise or Datacenter IPMI 2.0 compliant Quick Sync2 (Optional)						
Integrations	Dell EMC OpenManage Integration with Windows Admin Center						
Services	ProSupport and ProSupport Plus, ProDeploy, ProDeploy Plus with add-on for Azure Stack HCI Call-routing, phone home, and automated case creation supported with Secure Connect Gateway 5.0 Consulting Services for Azure Stack HCI iDRAC Service Module (iSM) 4.1.0.0						
Security	Trusted Platform Module 2.0						
Power Supplies	Dual, Hot-plug, Redundant Power Supply (1+1), 1100W or 1100W - 48VDC only Dual, Hot-plug, Redundant Power Supply (1+1), 1600W Dual, Hot-plug, Redundant Power Supply (1+1), 2000W Dual, Hot-plug, Redundant Power Supply (1+1), 2400W						
Form Factor	2U Rack						

# AX-640

Storage Configuration	Hybrid (SSD + HDD)	Hybrid (NVMe + HDD)	Hybrid (NVMe + SSD)	All flash (All-NVMe)	All flash (All-SSD)
Chassis Configurations	10 x 2.5" front bay drives				
Processors	Dual socket Intel Xeon Scalable Processors, Cascade Lake (CL/CL-R), Select Silver/Gold/Platinum options				
Memory	96 GB to 1.5 TB (8/16/32/64 GB DDR4; supports RDIMM; speeds up to 3200MT/s)				
Storage controller	Internal HBA330 12Gbps SAS HBA Controller (NON-RAID)				
Internal Boot Storage	BOSS with dual M.2 240GB or 480GB (RAID 1)				
Storage for Cache WI = write intensive MU = mixed use	2 x 800 GB (WI) SAS or 960 GB to 3.84 TB (MU) SAS/SATA SSDs	2 x 1.6/3.2/6.4 TB (MU) NVMe SSDs	2 x 1.6/3.2/6.4 TB (MU) NVMe SSDs	-	-
Storage for Capacity RI= read intensive WI = write intensive MU = mixed use	4/6/8 x 2 TB SATA or 2.4 TB SAS 10K HDDs	4/6/8 x 2.4 TB SAS 10K HDDs	4/6/8 x 960 GB/1.92 TB SATA or 800/960 GB to 1.6/1.92/3.84 TB SAS or 3.84/7.68 TB vSAS SSDs (WI or MU highly recommended)	4/6/8/10 x 4 TB (RI) or 1.6/3.2/6.4 TB (MU) NVMe SSDs	4 to 10 x 800 GB to 3.84 TB SAS or 960 GB to 3.84 TB SATA or 3.84 TB to 7.68 TB vSAS SSDs (WI or MU highly recommended)
Min/Max Raw Storage	8 to 19.2 TB	9.6 to 19.2 TB	3.2 to 61.44 TB	16 to 64 TB	3.2 to 76.8 TB
Network cards	Add-in-Card: Mellanox Connect-X4 LX (Dual Port 25 GbE) or QLogic QL41262 (Dual Port 25 GbE)  NDC*: Dual Port Intel X710 (10 GbE) + Dual Port Intel i350 (1 GbE) or Dual Port Broadcom 57412 (10 GbE) + Dual Port Broadcom 5720 (1 GbE) or QLogic FastLinQ 41164 Quad Port 10GbE SFP+ or QLogic FastLinQ 41164 Quad Port 10GbE BASE-T  * more options available	Add-in-Card: Mellanox Connect-X4 LX (Dual Port 25 GbE) or QLogic QL41262 (Dual Port 25 GbE) or Mellanox Connect X5 (Dual Port 100 GbE)  NDC*: Dual Port Intel X710 (10 GbE) + Dual Port Intel i350 (1 GbE) or Dual Port Broadcom 57412 (10 GbE) + Dual Port Broadcom 5720 (1 GbE) or QLogic FastLinQ 41164 Quad Port 10GbE SFP+ or QLogic FastLinQ 41164 Quad Port 10GbE BASE-T  * more options available	Add-in-Card: Mellanox Connect-X4 LX (Dual Port 25 GbE) or QLogic QL41262 (Dual Port 25 GbE) or Mellanox Connect X5 (Dual Port 100 GbE)  NDC*: QLogic FastLinQ 41164 Quad Port 10GbE SFP+ or QLogic FastLinQ 41164 Quad Port 10GbE BASE-T  * more options available	Add-in-Card: Mellanox Connect-X4 LX (Dual Port 25 GbE) or QLogic QL41262 (Dual Port 25 GbE) or Mellanox Connect X5 (Dual Port 100 GbE)  NDC*: QLogic FastLinQ 41262 Dual Port 10/25GbE SFP28 or QLogic FastLinQ 41164 Quad Port 10GbE SFP+ or QLogic FastLinQ 41164 Quad Port 10GbE BASE-T  * more options available	Add-in-Card: Mellanox Connect-X4 LX (Dual Port 25 GbE) or QLogic QL41262 (Dual Port 25 GbE) or Mellanox Connect X5 (Dual Port 100 GbE)  NDC*: Dual Port Intel X710 (10 GbE) + Dual Port Intel i350 (1 GbE) or Dual Port Broadcom 57412 (10 GbE) + Dual Port Broadcom 5720 (1 GbE) or QLogic FastLinQ 41164 Quad Port 10GbE SFP+ or QLogic FastLinQ 41164 Quad Port 10GbE BASE-T  * more options available
HCI Software	Microsoft Azure Stack HCI OS (factory preinstalled) Windows Admin Center (WAC)				
Out of Band Management	Integrated Dell Remote Access Controller (iDRAC) 9 Enterprise or Datacenter IPMI 2.0 compliant Quick Sync2 (Optional)				
Integrations	Dell EMC OpenManage Integration with Windows Admin Center				
Services	ProSupport and ProSupport Plus, ProDeploy, ProDeploy Plus with add-on for Azure Stack HCI Call-routing, phone home, and automated case creation supported with Secure Connect Gateway 5.0 Consulting Services for Azure Stack HCI iDRAC Service Module (iSM) 4.1.0.0				
Security	Trusted Platform Module 2.0				
Power Supplies	Dual, Hot-plug, Redundant Power Supply (1+1), 1100W or 1100W - 48VDC only Dual, Hot-plug, Redundant Power Supply (1+1), 1600W				
Form Factor	1U Rack				



[Learn more](#) about Dell EMC  
Integrated Systems for Microsoft  
Azure Stack HCI



[Contact](#) a Dell EMC Expert  
1-866-438-622

© 2021 Dell Inc. or its subsidiaries. All Rights Reserved. Dell, EMC and other trademarks are trademarks of Dell Inc. or its subsidiaries. Other trademarks may be trademarks of their respective owners.