



DELL POWERSWITCH

S3100 SERIES

High-performance managed Ethernet switches designed for non-blocking access

The S3100 switch series offers a power-efficient and resilient Gigabit Ethernet (GbE) switching solution with integrated 10GbE uplinks for advanced Layer 3 distribution for offices and campus networks. The S3100 switch series has high-performance capabilities and wire-speed performance utilizing a non-blocking architecture to easily handle unexpected traffic loads. Use dual internal hot-swappable 80PLUS-certified power supplies for high availability and power efficiency. The switches offer simple management and scalability via an 84Gbps (full-duplex) high-availability stacking architecture that allows management of up to 12 switches from a single IP address.

Modernize campus network architectures

Modernize campus network architectures with a power-efficient and resilient 1/10GbE switching solution with dense Power over Ethernet Plus (PoE+). Select S3100 models offer 24 or 48 ports of PoE+ to deliver clean power to network devices such as wireless access points (APs), Voice-over-IP (VoIP) handsets, video conferencing systems and security cameras. For greater interoperability in multivendor networks, S3100 series switches offer the latest open-standard protocols and include technology to interface with Cisco protocol PVST+. The S3100 series supports Dell OS9, VLT and network virtualization features such as VRF-lite and support for Dell Embedded Open Automation Framework.

Leverage familiar tools and practices

All S3100 switches include Dell OS9 for easier deployment and greater interoperability. One common command line interface (CLI) using a well-known command language means a faster learning curve for network administrators.

Deploy with confidence at any scale

S3100 series switches help create performance assurance with a data rate up to 260Gbps (full duplex) and a forwarding rate up to 193Mpps. Scale easily with built-in rear stacking ports. Switch stacks of up to 624 ports can be managed from a single screen using the highly-available stacking architecture for high-density aggregation with seamless redundant availability.

Hardware, performance and efficiency

- Up to 48 line-rate GbE ports of copper or 24 line-rate ports of fiber, two combo ports for fiber/copper flexibility, and two integrated 10GbE SFP+ ports
- Up to 48 ports of PoE+ in 1RU without an external power supply
- Hot swappable expansion module supporting dual-port SFP+ or dual-port 10GBaseT
- Integrated stacking ports with support up to 84Gbps
- Up to 624 ports in a 12-unit stack for high-density, high-availability aggregation and distribution in wiring closets/MDFs. Non-stop forwarding and fast failover in stack configurations
- Available with dual 80PLUS-certified hot swappable power supplies. Variable speed fan operation helps decrease cooling and power costs
- Energy-Efficient Ethernet and lower-power PHYs reduce power to inactive ports and idle links, providing energy savings from the power cord to the port
- Dell Fresh Air compliance for operation in environments up to 113°F (45°C) helps reduce cooling costs in temperature constrained deployments

Deploying, configuring and managing

- Tool-less ReadyRails™ significantly reduces rack installation time
- Management via an intuitive and familiar CLI, SNMP-based management console application (including Dell OpenManage Network Manager), Telnet or serial connection
- Private VLAN support
- AAA authorization, TACACS+ accounting and RADIUS support for comprehensive secure access
- Authentication tiering allows network administrators to tier port authentication methods such as 802.1x, MAC Authentication Bypass in priority order so that a single port can provide flexible access and security
- Achieve high availability and full bandwidth utilization with VLT and support firmware upgrades without taking the network offline
- Interfaces with PVST+ protocol for greater flexibility and interoperability in Cisco networks
- Advanced Layer 3 IPv4 and IPv6 functionality
- Flexible routing options with policy-based routing to route packets based on assigned criteria beyond destination address
- Routed Port Monitoring (RPM) covers a Layer 3 domain without costly dedicated network taps
- OpenFlow 1.3 provides the ability to separate the control plane from the forwarding plane for deployment in SDN environments

*Contact your Dell Technologies representative for a full list of validated storage arrays.

Product	Description
S3124	24x RJ45 10/100/1000Mb auto-sensing ports, 2x SFP+ ports, 2x GbE combo media ports, 1x hot swap expansion module bay, 1x 200W PSU included
S3124F	24x 1000-SX (up to 500m distance) or 1000-LX (up to 10km distance) SFP GbE ports, 2x SFP+ ports, 2x GbE combo media ports, 1x hot swap expansion module bay, 1x200W PSU included
S3124P	24x RJ45 10/100/1000Mb PoE+ (up to 30.8W) auto-sensing ports, 2x SFP+ ports, 2x GbE combo media ports, 1x hot swap expansion module bay, 1x 715W PSU included
S3148	48x RJ45 10/100/1000Mb auto-sensing ports, 2x SFP+ ports, 2x GbE combo media ports, 1x hot swap expansion module bay, 1x 200W PSU included
S3148P	48x RJ45 10/100/1000Mb PoE+ (up to 30.8W) auto-sensing ports, 2x SFP+ ports, 2x GbE combo media ports, 1x hot swap expansion module bay, 1x 1100W PSU included**
Power cords	C13 to NEMA 5-15, 3M; C13 to C14, 2M; C15 to NEMA 5-15, 2M (C15 for PoE S-Series only)
Modules (optional)	2-port 10GBASE-T RJ-45 hot swappable uplink module 2-port 10GbE SFP+ hot swappable uplink module
Power supplies (optional)	200W AC hot swappable with V-Lock, adds redundancy to non-PoE switches (S3124, S3124F and S3148 only) 715W AC hot swappable, adds redundancy to S3124P (S3124P only) 1100W AC hot swappable, adds redundancy to S3148P or upgrade S3124P for additional PoE+ power (S3124P and S3148P only)
Optics (optional)	Transceiver, SFP, 100BASE-FX, 1310nm wavelength, up to 2km reach Transceiver, SFP, 1000BASE-T Transceiver, SFP, 1000BASE-SX, 850nm wavelength, up to 550m reach Transceiver, SFP, 1000BASE-LX, 1310nm wavelength, up to 10km reach Transceiver, SFP, 1000BASE-ZX, 1550nm wavelength, up to 80km reach Transceiver, SFP+, 10GbE, LRM, 1310nm wavelength, up to 220m reach Transceiver, SFP+, 10GbE, SR, 850nm wavelength, up to 300m reach Transceiver, SFP+, 10GbE, LR, 1310nm wavelength, up to 10km reach Transceiver, SFP+, 10GbE, ER, 1550nm wavelength, up to 40km reach
Cables (optional)	Stacking cable 0.25m, 1m and 3m Dell Networking cable, SFP+ to SFP+, 10GbE, copper twinax direct attach cable, 0.5m, 1m, 3m, 5m and 7m

**Requires C15 plug

Technical specifications

Physical

2 rear stacking ports (21Gbps) supporting up to 84Gbps (full-duplex)
 2 integrated front 10GbE SFP+ dedicated ports
 Out-of-band management port (10/100/1000BASE-T)
 USB (Type A) port for configuration via USB flash drive
 Auto-negotiation for speed and flow control
 Auto-MDI/MDIX, port mirroring
 Energy-Efficient Ethernet per port settings
 Redundant variable speed fans
 Air flow: I/O to power supply
 RJ45 console/management port with RS232 signaling (RJ-45 to female DB-9 connector cable included)
 Dual firmware images on-board
 Switching engine model: Store and forward

Chassis

Size (1RU): 1.7126in x 17.0866in x 16.0236in (43.5mm x 434.0mm x 407.0mm) (H x W x D)
 Approximate weight: 13.2277lbs/6kg (S3124 and S3124F), 14.5505lbs/6.6kg (S3124P), 15.2119lbs/6.9kg (S3148P)
 ReadyRails rack mounting system, no tools required

Environmental

Power supply: 200W (S3124, S3124F and S3148), 715W or 1,100W (S3124P), 1,100W (S3148P)
 Power supply efficiency: 80% or better in all operating modes
 Max. thermal output (BTU/hr): 182.55 (S3124), 228.96 (S3124F), 4391.42 (S3124P), 221.11 (S3148), 7319.04 (S3148P)
 Power consumption max (watts): 52.8 (S3124), 67.1 (S3124F), 1,287 (S3124P), 74.8 (S3148), 2,145 (S3148P)
 Operating temperature: 32° to 113°F (0° to 45°C)
 Operating relative humidity: 95%
 Storage temperature: -40° to 149°F (-40° to 65°C)
 Storage relative humidity: 85%

Performance

MAC addresses: 56K (80K in L2 scaled mode)
 Static routes: 16K (IPv4)/8K (IPv6)
 Dynamic routes: 16K (IPv4)/8K (IPv6)
 Switch fabric capacity: 212Gbps (S3124, S3124F and S3124P) (full duplex) 260Gbps (S3148 and S3148P)
 Forwarding rate: 158Mpps (S3124, S3124F and S3124P) 193Mpps (S3148 and S3148P)
 Link aggregation: 16 links per group, 128 groups
 Priority queues per port: 8
 Line-rate Layer 2 switching: All (non-blocking)
 Line-rate Layer 3 routing: All (non-blocking)
 Flash memory: 1G
 Packet buffer memory: 4MB
 CPU memory: 2GB DDR3
 Layer 2 VLANs: 4K
 MSTP: 64 instances
 VRF-lite: 511 instances
 Line-rate Layer 2 switching: All protocols, including IPv4 and IPv6
 Line-rate Layer 3 routing: IPv4 and IPv6
 IPv4 host table size: 22K (42K in L3 scaled hosts mode)

IPv6 host table size: 16K (both global + Link Local)
 (32K in L3 scaled hosts mode)
 IPv4 Multicast table size: 8K
 LAG load balancing: Based on Layer 2, IPv4 or IPv6 headers

IEEE compliance

802.1AB LLDP
 802.1D Bridging, STP
 802.1p L2 Prioritization
 802.1Q VLAN Tagging
 802.1Qbb PFC
 802.1Qaz ETS
 802.1s MSTP
 802.1w RSTP
 802.1x Network Access Control
 802.1x-2010 Port Based Network Access Control
 802.3ab Gigabit Ethernet (1000BASE-T)
 802.3ac Frame Extensions for VLAN Tagging
 802.3ad Link Aggregation with LACP
 802.1ax Link Aggregation Revision - 2008 and 2011
 802.3ae 10 Gigabit Ethernet (10GBase-X)
 802.3af PoE (for S3124P and S3148P)
 802.3at PoE+ (for S3124P and S3148P)
 802.3az Energy Efficient Ethernet (EEE)
 802.3u Fast Ethernet (100Base-TX) on mgmt ports
 802.3x Flow Control
 802.3z Gigabit Ethernet (1000Base-X)
 ANSI/TIA-1057 LLDP-MED
 Force10 PVST+
 MTU 12,000 bytes

RFC and I-D compliance

General Internet protocols

768 UDP
 793 TCP
 854 Telnet
 959 FTP

General IPv4 protocols

791 IPv4
 792 ICMP
 826 ARP
 1027 Proxy ARP
 1035 DNS (client)
 1042 Ethernet Transmission
 1305 NTPv3
 1519 CIDR
 1542 BOOTP (relay)
 1812 Requirements for IPv4 Routers
 1918 Address Allocation for Private Internets
 2474 Diffserv Field in IPv4 and Ipv6 Headers
 2596 Assured Forwarding PHB Group
 3164 BSD Syslog
 3195 Reliable Delivery for Syslog

3246 Expedited Assured Forwarding
 4364 VRF-lite (IPv4 VRF with OSPF and BGP)
 5798 VRRP

General IPv6 protocols

1981 Path MTU Discovery Features
 2460 Internet Protocol, Version 6 (IPv6) Specification
 2464 Transmission of IPv6 Packets over Ethernet Networks
 2711 IPv6 Router Alert Option
 4007 IPv6 Scoped Address Architecture
 4213 Basic Transition Mechanisms for IPv6 Hosts and Routers
 4291 IPv6 Addressing Architecture
 4443 ICMP for IPv6
 4861 Neighbor Discovery for IPv6
 4862 IPv6 Stateless Address Autoconfiguration
 5095 Deprecation of Type 0 Routing Headers in IPv6
 IPv6 Management support (telnet, FTP, TACACS, RADIUS, SSH, NTP)

RIP

1058 RIPv1 2453 RIPv2

OSPF (v2/v3)

1587 NSSA 4552 Authentication/
 2154 OSPF Digital Signatures
 2328 OSPFv2 OSPFv3
 2370 Opaque LSA 5340 OSPF for IPv6

IS-IS

5301 Dynamic hostname exchange mechanism for IS-IS
 5302 Domain-wide prefix distribution with two-level IS-IS
 5303 Three way handshake for IS-IS point-to-point adjacencies
 5308 IS-IS for IPv6

BGP

1997 Communities
 2385 MD5
 2545 BGP-4 Multiprotocol Extensions for IPv6 Inter-Domain Routing
 2439 Route Flap Damping
 2796 Route Reflection
 2842 Capabilities
 2858 Multiprotocol Extensions
 2918 Route Refresh
 3065 Confederations
 4360 Extended Communities
 4893 4-byte ASN
 5396 4-byte ASN representations
 draft-ietf-idr-bgp4-20 BGPv4
 draft-michaelson-4byte-as-representation-05 4-byte ASN Representation (partial)
 draft-ietf-idr-add-paths-04.txt ADD PATH

Multicast

1112 IGMPv1
 2236 IGMPv2
 3376 IGMPv3
 MSDP
 draft-ietf-pim-sm-v2-new-05 PIM-SMw

Network management

1155 SMIv1
 1157 SNMPv1
 1212 Concise MIB Definitions
 1215 SNMP Traps
 1493 Bridges MIB
 1850 OSPFv2 MIB
 1901 Community-Based SNMPv2
 2011 IP MIB
 2096 IP Forwarding Table MIB
 2578 SMIv2
 2579 Textual Conventions for SMIv2
 2580 Conformance Statements for SMIv2
 2618 RADIUS Authentication MIB
 2665 Ethernet-Like Interfaces MIB
 2674 Extended Bridge MIB
 2787 VRRP MIB
 2819 RMON MIB (groups 1, 2, 3, 9)
 2863 Interfaces MIB
 3273 RMON High Capacity MIB
 3410 SNMPv3
 3411 SNMPv3 Management Framework
 3412 Message Processing and Dispatching
 for the Simple Network Management
 Protocol (SNMP)
 3413 SNMP Applications
 3414 User-based Security Model (USM) for
 NMPv3
 3415 VACM for SNMP
 3416 SNMPv2
 3417 Transport mappings for SNMP
 3418 SNMP MIB
 3434 RMON High Capacity Alarm MIB
 3584 Coexistence between SNMP v1,
 v2 and v3
 4022 IP MIB
 4087 IP Tunnel MIB
 4113 UDP MIB
 4133 Entity MIB
 4292 MIB for IP
 4293 MIB for IPv6 Textual Conventions
 4502 RMONv2 (groups 1,2,3,9)
 5060 PIM MIB
 ANSI/TIA-1057 LLDP-MED MIB
 Dell_ITA.Rev_1_1 MIB
 draft-grant-tacacs-02 TACACS+
 draft-ietf-idr-bgp4-mib-06 BGP MIBv1
 IEEE 802.1AB LLDP MIB
 IEEE 802.1AB LLDP DOT1 MIB
 IEEE 802.1AB LLDP DOT3 MIB
 sFlow.org sFlowv5
 sFlow.org sFlowv5 MIB (version 1.3)
 FORCE10-BGP4-V2-MIB Force10 BGP MIB
 (draft-ietf-idr-bgp4-mibv2-05)
 FORCE10-IF-EXTENSION-MIB
 FORCE10-LINKAGG-MIB
 FORCE10-COPY-CONFIG-MIB
 FORCE10-PRODUCTS-MIB
 FORCE10-SS-CHASSIS-MIB
 FORCE10-SMI
 FORCE10-TC-MIB
 FORCE10-TRAP-ALARM-MIB
 FORCE10-FORWARDINGPLANE-STATS-MIB

Regulatory compliance

Safety
 UL/CSA 60950-1, Second Edition
 EN 60950-1, Second Edition
 IEC 60950-1, Second Edition Including All
 National Deviations and Group Differences
 EN 60825-1 Safety of Laser Products Part 1:
 Equipment Classification Requirements and
 User's Guide
 EN 60825-2 Safety of Laser Products Part 2:
 Safety of Optical Fibre Communication Systems
 FDA Regulation 21 CFR 1040.10 and 1040.11

Emissions

USA: FCC CFR 47 Part 15, Subpart B:2011,
 Class A

Immunity

EN 300 386 V1.4.1:2008 EMC for Network
 Equipment
 EN 55024: 1998 + A1: 2001 + A2: 2003
 EN 61000-3-2: Harmonic Current Emissions
 EN 61000-3-3: Voltage Fluctuations and Flicker
 EN 61000-4-2: ESD
 EN 61000-4-3: Radiated Immunity
 EN 61000-4-4: EFT
 EN 61000-4-5: Surge
 EN 61000-4-6: Low Frequency Conducted
 Immunity

RoHS

All S Series components are EU RoHS compliant.

Certifications

Available with US Trade Agreements Act (TAA)
 compliance
 USGv6 Host and Router Certified on Dell
 Networking
 OS 9.7 and greater
 IPv6 Ready for both Host and Router
 DoD UC-APL approved switch
 FIPS 140-2 Approved Cryptography

Warranty

Lifetime Limited Hardware Warranty

IT Lifecycle Services for Networking

Experts, insights and ease

Our highly trained experts, with innovative tools and proven processes, help you transform your IT investments into strategic advantages.



Plan & Design

Let us analyze your multivendor environment and deliver a comprehensive report and action plan to build upon the existing network and improve performance.



Deploy & Integrate

Get new wired or wireless network technology installed and configured with ProDeploy. Reduce costs, save time, and get up and running fast.



Educate

Ensure your staff builds the right skills for long-term success. Get certified on Dell Networking technology and learn how to increase performance and optimize infrastructure.



Manage & Support

Gain access to technical experts and quickly resolve multivendor networking challenges with ProSupport. Spend less time resolving network issues and more time innovating.



Optimize


Maximize performance for dynamic IT environments with Dell Optimize. Benefit from in-depth predictive analysis, remote monitoring and a dedicated systems analyst for your network.



Retire

We can help you resell or retire excess hardware while meeting local regulatory guidelines and acting in an environmentally responsible way.

Learn more at DellTechnologies.com/Services



Learn more about Dell Networking solutions



Contact a Dell Technologies Expert



View more resources



Join the conversation with @DellNetworking