



Dell EMC PowerSwitch S5200-ON Series Switches

High-performance, open networking 25GbE top-of-rack and 100GbE spine/leaf switches

The PowerSwitch S5200-ON 25/100GbE fixed switches comprise Dell Technologies' latest disaggregated hardware and software data center networking solutions, providing state-of-the-art, high-density 25/100GbE ports and a broad range of functionality to meet the growing demands of today's data center environment. These innovative, next-generation open networking switches offer optimum flexibility and cost-effectiveness for web 2.0, enterprise and cloud service providers with demanding compute and storage traffic environments.

The S5200-ON is a complete family of switches: 12-port, 24-port, and 48-port 25GbE/100GbE ToR switches, 96-port 25GbE/100GbE Middle of Row (MoR)/End of Row (EoR) switch, and a 32-port 100GbE Multi-Rate Spine/Leaf switch. From the compact half-rack width S5212F-ON providing an ideal form factor for hyper-converged deployments, to the high density S5296F-ON for Middle of Row deployments, the S5200-ON series offers performance and flexibility for a variety of network designs.

In addition to 100GbE Spine/Leaf deployments, the S5232F-ON can also be used in high density deployments using breakout cables to achieve up to 128 10GbE or 128 25GbE ports.

Using industry-leading hardware and a choice of Dell EMC SmartFabric OS10 or select 3rd party network operating systems and tools, the S5200-ON switches incorporate multiple architectural features that optimize data center network flexibility, efficiency and availability, including IO panel to PSU or PSU to IO panel airflow for hot/cold aisle environments, redundant, hot-swappable power supplies and fans and deliver non-blocking performance for workloads sensitive to packet loss.

Priority-based flow control (PFC), data center bridge exchange (DCBX) and enhanced transmission selection (ETS) make the S5200-ON family ideally suited for DCB environments.

Dell EMC PowerSwitch S5200-ON switches support the open source Open Network Install Environment (ONIE) for zero touch installation of Dell EMC SmartFabric OS10 networking operating system, as well as alternative network operating systems.

Key applications

- Organizations looking to enter the software-defined data center era with a choice of networking technologies designed to maximize flexibility
- High-density 10/25GbE ToR server aggregation in high-performance data center environments at the desired fabric speed with the S5248F-ON or S5296F-ON
- Low-density 10/25GbE server and storage aggregation with the S5212F-ON and S5224F-ON
- Small-scale Fabric implementation via the S5232F-ON switch in leaf and spine along with S5248F-ON 1/10/25GbE ToR switches enabling cost-effective aggregation of 10/25/40/50/100 uplinks
- Multi-functional 10/25/40/50/100GbE switching in High Performance Computing Clusters or other business-sensitive deployments requiring the highest bandwidth.
- iSCSI deployments, including DCB converged lossless transactions
- Single-pass VXLAN routing

Key features

- 1 or 2RU high-density ToR switches with up to 48 or 96 ports of 25GbE or 32 ports of 100GbE
- Multi-rate 100GbE ports support 10/25/40/50/100GbE
- Scalable L2 and L3 Ethernet switching with QoS and a full complement of standards-based IPv4 and IPv6 features, including OSPF and BGP routing support
- Line-rate performance via non-blocking switch fabrics: 3.2Tbps (6.4Tbps full-duplex) on S5296F-ON and S5232F-ON, 2.0Tbps (4.0Tbps full-duplex) on S5248F-ON, and 1.08Tbps (2.16Tbps full-duplex) on S5224F-ON and S5212F-ON
- L2 multipath support via Virtual Link Trunking (VLT) and Routed VLT support
- VXLAN gateway functionality support for bridging and routing the non-virtualized and the virtualized overlay networks with line rate performance
- Support for Dell EMC SmartFabric OS10
- Converged network support for DCB, with priority flow control (802.1Qbb), ETS (802.1Qaz), DCBx and iSCSI TLV support
- Routable RoCE to enable convergence of compute and storage on Leaf/Spine Fabric
- IO panel to PSU airflow or PSU to IO panel airflow Redundant, hot-swappable power supplies and fans on most models
- Supports the open source Open Network Install Environment (ONIE) for zero touch installation of alternate network operating systems
- Tool-less enterprise ReadyRails™ mounting kits for most models reducing time and resources for switch rack installation (S5212F-ON will utilize a tandem tray for mounting)
- Power-efficient operation and Dell Fresh Air 2.0 compliant up to 45°C helps reduce cooling costs in temperature constrained deployments

Key features with Dell EMC SmartFabric OS10

- Consistent DevOps framework across compute, storage and networking elements
- Standard networking features, interfaces and scripting functions for legacy network operations integration
- Standards-based switching hardware abstraction via Switch Abstraction Interface (SAI)
- Pervasive, unrestricted developer environment via Control Plane Services (CPS)
- Dell EMC SmartFabric OS10 software enables Dell EMC layer 2 and 3 switching and routing protocols with integrated IP services, quality of service, manageability and automation features
- OS10 supports Precision Time Protocol (PTP, IEEE 1588v2) to synchronize clocks on network devices
- Increase VM Mobility region by stretching L2 VLAN within or across two DCs with unique VLT capabilities
- Scalable L2 and L3 Ethernet Switching with QoS, ACL and a full complement of standards based IPv4 and IPv6 features including OSPF, BGP and PBR
- Enhanced mirroring capabilities including local mirroring, Remote Port Mirroring (RPM), and Encapsulated Remote Port Mirroring (ERPM)
- Converged network support for Data Center Bridging, with priority flow control (802.1Qbb), ETS (802.1Qaz), DCBx and iSCSI TLV
- BGP EVPN with Integrated Routing and Bridging (IRB) in both Asymmetric and Symmetric modes, enabling controller less NVO

Features	S5212F-ON	S5224F-ON	S5248F-ON	S5296F-ON	S5232F-ON
Ports	12xSFP28 3xQSFP28	24xSFP28 4xQSFP28	48xSFP28 2xQSFP28-DD 4xQSFP28	96xSFP28 8xQSFP28	32xQSFP28 2xSFP+
Max 10GbE density	12 (SFP28) 12 (QSFP28 Breakout)	24 (SFP28) 16 (QSFP28 breakout)	48 (SFP28) 16 (QSFP28-DD breakout) 16 (QSFP28 breakout)	96 (SFP28) 32 (QSFP28 breakout)	124 (QSFP28 breakout) 2 (SFP+)
Max 25GbE density	12 (SFP28) 12 (QSFP28 Breakout)	24 (SFP28) 16 (QSFP28 breakout)	48 (SFP28) 16 (QSFP28-DD breakout) 16 (QSFP28 breakout)	96 (SFP28) 32 (QSFP28 breakout)	124 (QSFP28 breakout)
Max 40GbE density	3 (QSFP28)	4 (QSFP28)	6 (QSFP28) 4 (QSFP28-DD breakout)	8 (QSFP28)	32 (QSFP28)
Max 50GbE density	6 (QSFP28 breakout)	8 (QSFP28 breakout)	16 (QSFP28 breakout)	16 (QSFP28 breakout)	64 (QSFP28 breakout)
Max 100GbE density	3 (QSFP28)	4 (QSFP28)	4 (QSFP28) 4 (QSFP28-DD breakout)	8 (QSFP28)	32 (QSFP28)
Switching capacity	1.08 Tbps (2.16 Tbps full duplex)	1.08 Tbps (2.16 Tbps full duplex)	2.0 Tbps (4.0 Tbps full duplex)	3.2 Tbps (6.4 Tbps full duplex)	3.2 Tbps (6.4 Tbps full duplex)
Throughput	440 Mpps (880 Mpps full duplex)	720 Mpps (1.42 Bpps full duplex)	1.5 Bpps (3.0 Bpps full duplex)	2.4 Bpps (4.8 Bpps full duplex)	2.4 Bpps (4.8 Bpps full duplex)
Latency (nano sec)	906	881	847	850	877
1588v2 PTP timing (hardware)		●	●	●	●
CPU Memory	8GB	8GB	16GB	16GB	16GB
SSD	16GB	32GB	64GB	64GB	64GB
Packet Buffer	32MB	32MB	32MB	32MB	32MB
Maximum power	304W	455W	647W	893W	635W
Typical power	140W	200W	310W	457W	360W
Maximum current	2.8A@110VAC / 1.4A@220VAC	4.2A@110VAC / 2.1A@220VAC	5.8A@110VAC / 2.9A@220VAC	8.2A@110VAC / 4.1A@220VAC	5.8A@110VAC / 2.9A@220VAC
Fan modules	Fixed	4	4	4	4
Form Factor	1RU (half-width)	1RU	1RU	2RU	1RU
Dimensions	8.2"Wx19.3"D x1.6"H 20.9Wx49.0D x4.1H (cm)	17.1"Wx18.1"D x1.7"H 43.4Wx46.0D x4.4H (cm)	17.1"Wx18.1"D x1.7"H 43.4Wx46.0D x4.4H (cm)	17.4"Wx20.1"D x3.4"H 44.2Wx51.1D x8.7H (cm)	17.1"Wx18.1"D x1.7"H 43.4Wx46.0D x4.4H (cm)
Weight	4.5kg (10.05lbs)	9.7kg (21.4lbs)	9.7kg (21.4lbs)	15.1kg (33.2lbs)	9.8kg (21.6lbs)
Max thermal output	1037 BTU/h	1552 BTU/h	2208 BTU/h	3047 BTU/h	2167 BTU/h

Features	Description
S5200-ON	<p>S5212F, 12x 25GbE SFP28 + 3x 100GbE QSFP28, 2x AC PSU, I/O Panel to PSU Airflow, Dell EMC SmartFabric OS10</p> <p>S5212F, 12x 25GbE SFP28 + 3x 100GbE QSFP28, 2x AC PSU, PSU to I/O Panel Airflow, Dell EMC SmartFabric OS10</p> <p>S5212F, 12x 25GbE SFP28 + 3x 100GbE QSFP28, 2x DC PSU, I/O Panel to PSU Airflow, Dell EMC SmartFabric OS10</p> <p>S5212F, 12x 25GbE SFP28 + 3x 100GbE QSFP28, 2x DC PSU, PSU to I/O Panel Airflow, Dell EMC SmartFabric OS10</p> <p>S5212F, 12x 25GbE SFP28 + 3x 100GbE QSFP28, 2x AC PSU, I/O Panel to PSU Airflow, NO-OS</p> <p>S5212F, 12x 25GbE SFP28 + 3x 100GbE QSFP28, 2x AC PSU, PSU to I/O Panel Airflow, NO-OS</p> <p>S5212F, 12x 25GbE SFP28 + 3x 100GbE QSFP28, 2x AC PSU, I/O Panel to PSU Airflow, Dell EMC SmartFabric OS10, TAA</p> <p>S5212F, 12x 25GbE SFP28 + 3x 100GbE QSFP28, 2x AC PSU, PSU to I/O Panel Airflow, Dell EMC SmartFabric OS10, TAA</p> <p>S5224F, 24x 25GbE SFP28 + 4x 100GbE QSFP28, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, Dell EMC SmartFabric OS10</p> <p>S5224F, 24x 25GbE SFP28 + 4x 100GbE QSFP28, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, Dell EMC SmartFabric OS10</p> <p>S5224F, 24x 25GbE SFP28 + 4x 100GbE QSFP28, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, NO-OS</p> <p>S5224F, 24x 25GbE SFP28 + 4x 100GbE QSFP28, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, NO-OS</p> <p>S5224F, 24x 25GbE SFP28 + 4x 100GbE QSFP28, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, Dell EMC SmartFabric OS10, TAA</p> <p>S5224F, 24x 25GbE SFP28 + 4x 100GbE QSFP28, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, Dell EMC SmartFabric OS10, TAA</p> <p>S5248F, 48x 25GbE SFP28 + 2x 200GbE QSFP28-DD + 4x 100GbE QSFP28, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, Dell EMC SmartFabric OS10</p> <p>S5248F, 48x 25GbE SFP28 + 2x 200GbE QSFP28-DD + 4x 100GbE QSFP28, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, Dell EMC SmartFabric OS10</p> <p>S5248F, 48x 25GbE SFP28 + 2x 200GbE QSFP28-DD + 4x 100GbE QSFP28, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, NO-OS</p> <p>S5248F, 48x 25GbE SFP28 + 2x 200GbE QSFP28-DD + 4x 100GbE QSFP28, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, NO-OS</p> <p>S5248F, 48x 25GbE SFP28 + 2x 200GbE QSFP28-DD + 4x 100GbE QSFP28, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, Dell EMC SmartFabric OS10, TAA</p> <p>S5248F, 48x 25GbE SFP28 + 2x 200GbE QSFP28-DD + 4x 100GbE QSFP28, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, Dell EMC SmartFabric OS10, TAA</p> <p>S5296F, 96x 25GbE SFP28 + 8x 100GbE QSFP28, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, Dell EMC SmartFabric OS10</p> <p>S5296F, 96x 25GbE SFP28 + 8x 100GbE QSFP28, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, Dell EMC SmartFabric OS10</p> <p>S5296F, 96x 25GbE SFP28 + 8x 100GbE QSFP28, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, NO-OS</p> <p>S5296F, 96x 25GbE SFP28 + 8x 100GbE QSFP28, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, NO-OS</p> <p>S5296F, 96x 25GbE SFP28 + 8x 100GbE QSFP28, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, Dell EMC SmartFabric OS10, TAA</p> <p>S5296F, 96x 25GbE SFP28 + 8x 100GbE QSFP28, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, Dell EMC SmartFabric OS10, TAA</p> <p>S5232F, 32x 100 GbE QSFB28 + 2x 10GbE SFP+, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, Dell EMC SmartFabric OS10</p> <p>S5232F, 32x 100 GbE QSFB28 + 2x 10GbE SFP+, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, Dell EMC SmartFabric OS10</p> <p>S5232F, 32x 100 GbE QSFB28 + 2x 10GbE SFP+, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, NO-OS</p> <p>S5232F, 32x 100 GbE QSFB28 + 2x 10GbE SFP+, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, NO-OS</p> <p>S5232F, 32x 100 GbE QSFB28 + 2x 10GbE SFP+, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, Dell EMC SmartFabric OS10, TAA</p> <p>S5232F, 32x 100 GbE QSFB28 + 2x 10GbE SFP+, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, Dell EMC SmartFabric OS10, TAA</p>
Redundant power supplies	AC Power Supply, IO Panel to PSU Airflow AC Power Supply, PSU to IO Panel Airflow DC Power Supply, IO Panel to PSU Airflow (available as custom kit) DC Power Supply, PSU to IO Panel Airflow (available as custom kit)
Fans	Fan module, IO Panel to PSU Airflow Fan module, PSU to IO Panel Airflow

Features	Description
Optics	Transceiver, 2x100GbE, 2xSR4, QSFP28-DD Transceiver, 2x100GbE, 2xPSM4-IR, QSFP28-DD Transceiver, 2x100GbE, 2xCWDM4, QSFP28-DD Transceiver, 100GbE, SR4 QSFP28 Transceiver, 100GbE, PSM4 (500m) QSFP28 Transceiver, 100GbE, CWDM4 (2Km) QSFP28 Transceiver, 100GbE, LR4 QSFP28 Transceiver, 40GbE, SR4 optic QSFP+ Transceiver, 40GbE, BiDi optic QSFP+ (Duplex) Transceiver, 40GbE, SM4 optic QSFP+ (Duplex) Transceiver, 40GbE, LM4 optic QSFP+ (Duplex) Transceiver, 40GbE, PSM4 10Km, QSFP+ Transceiver, 40GbE, LR4 optic QSFP+ Transceiver, 40GbE, ER4 optics QSFP+ Transceiver, 25GbE, SR, NOF SFP28 Transceiver, 25GbE, LR, SFP28 Transceiver, 10GbE, SR SFP+, short reach Transceiver, 10GbE, LR SFP+, long reach Transceiver, 10GbE, ER SFP+, extended reach Transceiver, 10GbE, ZR SFP+ extra extended reach 10G, Transceiver, 10GBASE-T use with QSA in QSFP+ port, 30m reach on CAT6a/7 Transceiver, 1GbE, SX SFP Transceiver, 1GbE, LX SFP Transceiver, 1GbE, ZX SFP Transceiver, 1GbE, 10km, BiDi SFP Transceiver, 1GbE, 40km, BiDi SFP Transceiver, 1GbE, 80km, BiDi SFP Transceiver, 1GbE, 100BASE-T, Gen2, SFP
Cables	100GbE, 4x25GbE, QSFP28 to 4xSFP28, passive DAC 100GbE, QSFP28 to QSFP28, active optical 100GbE, QSFP28 to QSFP28, passive DAC 100GbE, 2x50GbE, 2xQSFP to 2xQSFP28, passive DAC, breakout 40GbE, QSFP+ to QSFP+, active optical 40GbE, QSFP+ to QSFP+, passive DAC 40GbE, MTP to 4xLC optical breakout 40GbE, 4x10GbE, QSFP+ to 4xSFP+, passive DAC
Cable management	Z9100 Cable Breakout Kit, MTP to LC (1RU 64-port LC over MMF) Z9100 Cable Breakout Kit, MTP to LC (1RU 64-port LC over SMF)

Technical specifications

Physical 1 RJ45 console/management port with RS232 signaling S5212F-ON: 12x25GbE SFP28 + 3x 100GbE QSFP28 S5224F-ON: 24x25GbE SFP28 + 4x 100GbE QSFP28 S5248F-ON: 48x25GbE SFP28 + 4x 100GbE QSFP28 + 2x100GbE QSFP28-DD S5296F-ON: 96x25GbE SFP28 + 8x 100GbE QSFP28 S5232F-ON: 32x100GbE QSFP28 ports + 2xSFP+ 10GbE	Performance* Packet buffer memory: 32MB CPU memory: 16GB MAC Addresses: 32K min, 288K max** IPv4 Hosts: 16K min, 168K max** IPv6 Hosts: 8K min, 100K max** IPv4 Routes: 128K** IPv6 Routes: 64K** Multicast Routes: 16K L2 Ingress ACL: 2K L2 Egress ACL: 256 IPv4 Ingress ACL: 2K IPv4 Egress ACL: 2K IPv6 Ingress ACL: 1K IPv6 Egress ACL: 1K VLANs: 4K MSTP instances: 63 instances PVST instances: 150 instances Total LAG: 128 Total members per LAG: 16 LAG load balancing: Based on layer 2, IPv4 or IPv6 headers	802.3ac Frame Extensions for VLAN Tagging 802.3x Flow Control Jumbo MTU support 9,216 bytes
Environmental Power supply: 100–240 VAC 50/60 Hz Max Operating specifications: AC Max. Operating specifications: Operating temperature: 32° to 113°F (0° to 45°C) Operating humidity: 5 to 90% (RH), non-condensing Max. Non-operating specifications: Storage temperature: –40° to 158°F (–40° to 70°C) Storage humidity: 5 to 90% (RH), non-condensing Fresh air Compliant to 45°C	IEEE Compliance 802.1AB LLDP TIA-1057 LLDP-MED 802.3ad Link Aggregation 802.1D Bridging, STP 802.1p L2 Prioritization 802.1Q VLAN Tagging 802.1Qbb PFC 802.1Qaz ETS 802.1X Network Access Control	Layer2 Protocols 802.1D Compatible 802.1s MSTP 802.1w RSTP 802.1t RPVST+ VLT (Virtual Link Trunking) VRRP Active/Active RSTP & RPVST+ Port Mirroring on VLT ports DCB, iSCSI, FIP Snooping Bridge RPM/ERPM over VLT VLT Minloss upgrade
Redundancy Hot swappable redundant power Hot swappable redundant fans (fixed power supply and fans on S5212F-ON)		RFC Compliance 768 UDP 793 TCP 854 Telnet 959 FTP 1321 MD5 1350 TFTP 2474 Differentiated Services 2698 Two Rate Three Color Marker 3164 Syslog 4254 SSHv2

*Maximum NPU and hardware performance. Please refer to specific Network Operating System scalability numbers for actual, validated values.

**Depends on ALPM mode.

Technical specifications

General IPv4 Protocols

791	IPv4
792	ICMP
826	ARP
1027	Proxy ARP
1035	DNS (client)
1042	Ethernet Transmission
1191	Path MTU Discovery
1305	NTPv4
1519	CIDR
1588v2	PTP support
1812	Routers, Static Routes
1858	IP Fragment Filtering
2131	DHCPv4 (server and relay)
5798	VRRPv3
3021	31-bit Prefixes
1812	Requirements for IPv4 Routers
1918	Address Allocation for Private Internets
2474	Diffserv Field in IPv4 and Ipv6 Headers
2597	Assured Forwarding PHB Group
3195	Reliable Delivery for Syslog
3246	Expedited Forwarding PHB Group VRF(BGP v4/v6)

General IPv6 Protocols

1981	Path MTU for IPv6
2372	IPv6 Addressing
2460	IPv6 Protocol Specification
2461	Neighbor Discovery
2462	Stateless Address AutoConfig
2711	IPv6 Router alert
2463	ICMPv6
2464	Ethernet Transmission
2675	IPv6 Jumbograms
3484	Default Address Selection
3493	Basic Socket Interface
4291	Addressing Architecture
3542	Advanced Sockets API
3587	Global Unicast Address Format
4291	IPv6 Addressing
2464	Transmission of IPv6 Packets over Ethernet Networks
2711	IPv6 Router Alert Option
4007	IPv6 Scoped Address Architecture
4213	Transition Mechanisms for IPv6 Hosts and Routers
3315	DHCPv6 Server & Relay
IPv6	Static Routes

OSPF

1745	OSPF/BGP interaction
1765	OSPF Database overflow
2154	OSPF with DigitalSignatures
2328	OSPFv2
5340	OSPF for IPv6 (OSPFv3)
2370	Opaque LSA
3101	OSPF NSSA
4552	OSPFv3 Authentication

Multicast

4541	IGMPv1/v2/v3 and MLDv1/v2 Snooping
------	------------------------------------

Security

2865	RADIUS
3162	Radius and IPv6
3579	Radius support for EAP
3580	802.1X with RADIUS
3826	AES Cipher in SNMP
1492	TACACS (Authentication, Accounting) Control Plane, VTY & SNMP ACLs

IP Access Control Lists

BGP

1997	Communities
2385	MD5
2439	Route Flap Damping
2796	Route Reflection
2918	Route Refresh
3065	Confederations
4271	BGP-4
2545	BGP-4 Multiprotocol Extensions for IPv6 Inter-Domain Routing
2858	Multiprotocol Extensions
4360	Extended Communities
4893	4-byte ASN
5396	4-byte ASN Representation
5492	Capabilities Advertisement draft-ietf-idr-add-paths-04.txt ADD PATH

Linux Distribution

Debian Linux version 9
Linux Kernel 4.9

Network Management and Monitoring

SNMPv1/2c
IPv4/IPv6 Management support (Telnet, FTP, TACACS, RADIUS, SSH, NTP)
Syslog
Port Mirroring
RPM/ERPM
3176 SFlow
Support Assist (Phone Home)
RestConf APIs (Layer 2 features)
XML Schema
CLI Commit (Scratchpad)
Uplink Failure Detection
Object Tracking
Bidirectional Forwarding Detection (BFD)
Automation
Control Plane Services APIs
Linux Utilities and Scripting Tools
CLI Automation (Multiline Alias)
Zero Touch Deployment (ZTD)
Ansible, Puppet, Chef, SaltStack
8040 RESTCONF APIs (L3)

Quality of Service

Prefix List
Route-Map
Rate Shaping (Egress)
Rate Policing (Ingress)
Scheduling Algorithms
Round Robin
Weighted Round Robin
Deficit Round Robin
Strict Priority
Weighted Random Early Detect

Data center bridging

802.1Qbb	Priority-Based Flow Control
802.1Qaz	Enhanced Transmission Selection (ETS)
Explicit Congestion Notification	
Data Center Bridging eXchange (DCBx)	
DCBx Application TLV (iSCSI, FCoE)	
RoCEv2	
Software Defined Networking	
OpenFlow 1.3 (Native)	

MIBS

IP MIB
IP Forward MIB
Host Resources MIB
IF MIB
LLDP EXT1/3 MIB
Entity MIB

LAG MIB
Dell-Vendor MIB
TCP MIB
UDP MIB
SNMPv2 MIB
ETHERLIKE-MIB
SFLOW-MIB
PFC-MIB

Regulatory compliance

Safety

UL/CSA 60950-1, Second Edition
EN 60950-1, Second Edition
IEC 60950-1, Second Edition Including All National Deviations and Group Differences
EN 60825-1 Safety of Laser Products Part 1: Equipment Classification Requirements and User's Guide
EN 60825-2 Safety of Laser Products Part 2: Safety of Optical Fibre Communication Systems
FDA Regulation 21 CFR 1040.10 and 1040.11 Emissions
Australia/New Zealand: AS/NZS CISPR 22: 2006, Class A
Canada: ICES-003, Issue-4, Class A
Europe: EN 55022: 2006+A1:2007 (CISPR 22: 2006), Class A
Japan: VCCI V3/2009 Class A
USA: FCC CFR 47 Part 15, Subpart B:2011, Class A

Immunity

EN 300 386 V1.4.1:2008 EMC for Network Equipment
EN 55024: 1998 + A1: 2001 + A2: 2003
EN 61000-3-2: Harmonic Current Emissions
EN 61000-3-3: Voltage Fluctuations and Flicker
EN 61000-4-2: ESD
EN 61000-4-3: Radiated Immunity
EN 61000-4-4: EFT
EN 61000-4-5: Surge
EN 61000-4-6: Low Frequency Conducted Immunity

RoHS

All S Series components are EU RoHS compliant.

Certifications

Available with US Trade Agreements Act (TAA) compliance
USGv6 Host and Router Certified on Dell Networking OS 9.5 and greater
IPv6 Ready for both Host and Router
UCR DoD APL (core and distribution ALSAN switch)

Warranty

1 Year Return to Depot

IT Lifecycle Services for Networking

Experts, insights and ease

Our highly trained experts, with innovative tools and proven processes, help you transform your IT investments into strategic advantages.



Plan & Design

Let us analyze your multivendor environment and deliver a comprehensive report and action plan to build upon the existing network and improve performance.



Deploy & Integrate

Get new wired or wireless network technology installed and configured with ProDeploy. Reduce costs, save time, and get up and running fast.



Educate

Ensure your staff builds the right skills for long-term success. Get certified on Dell EMC Networking technology and learn how to increase performance and optimize infrastructure.



Manage & Support

Gain access to technical experts and quickly resolve multivendor networking challenges with ProSupport. Spend less time resolving network issues and more time innovating.



Optimize

Maximize performance for dynamic IT environments with Dell EMC Optimize. Benefit from in-depth predictive analysis, remote monitoring and a dedicated systems analyst for your network.



Retire

We can help you resell or retire excess hardware while meeting local regulatory guidelines and acting in an environmentally responsible way.

Learn more at DellTechnologies.com/Services



[Learn more](#) about Dell EMC Networking solutions



[Contact](#) a Dell Technologies Expert



[View more](#) resources



Join the conversation with [@DellNetworking](#)