

# Dell EMC PowerScale All-Flash Family

PowerScale OneFS is the operating system powering the industry’s leading scale-out NAS platforms that enables you to innovate with your data. The PowerScale family includes Dell EMC PowerScale platforms and the Dell EMC Isilon platforms configured with the PowerScale OneFS operating system. OneFS provides the intelligence behind the highly scalable, high-performance modular storage solution that can grow with your business. A OneFS powered cluster is composed of a flexible choice of storage platforms including all-flash, hybrid and archive nodes. These solutions provide the performance, choice, efficiency, flexibility, scalability, security and protection for you to store massive amounts of unstructured data within a cluster. The PowerScale all-flash platforms co-exist seamlessly in the same cluster with your existing Isilon nodes to drive your traditional and modern applications.



PowerScale F900



PowerScale F600



PowerScale F200



Isilon F800 and F810

The PowerScale all-flash storage platforms - powered by the PowerScale OneFS operating system - provide a powerful yet simple scale-out storage architecture to speed up access to massive amounts of unstructured data while dramatically reducing cost and complexity. The platforms are available in several product lines:

- PowerScale F900:** Provides the maximum performance of all-NVMe drives in a cost-effective configuration to address the storage needs of demanding workloads. Each node is 2U in height and hosts 24 NVMe SSDs. It allows you to scale raw storage capacity from 46 TB to 368 TB per node and up to 93 PB of raw capacity per cluster. The F900 includes in-line compression and deduplication. The minimum number of PowerScale nodes per cluster is three while the maximum cluster size is 252 nodes. The F900 is best suited for Media and Entertainment 8K, genomics, algorithmic trading, artificial intelligence, machine learning and HPC workloads
- PowerScale F600:** With NVMe drives, the F600 provides larger capacity with massive performance in a cost-effective compact form factor to power demanding workloads. Each node allows you to scale raw storage capacity from 15.36 TB to 122.8 TB and up

to 30.96 PB of raw storage per cluster. The F600 includes inline software data compression and deduplication. The minimum number of nodes per cluster is three while the maximum cluster size is 252 nodes. The F600 is best suited for M&E studios, hospitals and financials that need performance and capacity for demanding workloads

- PowerScale F200:** Provides the performance of flash storage in a cost-effective form factor to address the needs of a wide variety of workloads. Each node allows you to scale raw storage capacity from 3.84 TB to 30.72 TB and up to 7.7 PB of raw capacity per cluster. The F200 includes in-line compression and deduplication. The minimum number of PowerScale nodes per cluster is three while the maximum cluster size is 252 nodes. The F200 is best suited for remote offices, small M&E workloads, small hospitals, retail outlets, IoT, factory floor and other similar deployment scenarios.
- Isilon F800:** Provides massive performance and capacity. It delivers up to 250,000 IOPS and up to 15 GB/s aggregate throughput in a single chassis configuration and up to 15.75M IOPS and up to 945 GB/s of aggregate throughput in a 252 node cluster. Each chassis houses 60 SSDs with a capacity choice of 1.6 TB, 3.2 TB, 3.84 TB, 7.68 TB or 15.36 TB per drive. This allows you to scale raw storage capacity from 96 TB to 924 TB in a single 4U chassis and up to 58 PB raw storage in a single cluster.
- Isilon F810:** Provides massive performance and capacity along with inline data compression and deduplication capabilities to deliver extreme efficiency. The F810 delivers up to 250,000 IOPS and up to 15 GB/sec aggregate throughput in a single chassis configuration and up to 15.75M IOPS and up to 945 GB/s of aggregate throughput in a 252 node cluster. Each F810 chassis houses 60 SSDs with a capacity choice of 3.84 TB, 7.68 TB or 15.36 TB per drive. This allows you to scale raw storage capacity from 230 TB to 924 TB in a 4U chassis and up to 58 PB of raw storage in a single cluster.

Embedded, integrated, or attached OEM versions are available for PowerScale all-flash nodes as either de-branded or re-branded solutions.

## PowerScale F900 All-NVMe Specifications

F900 ATTRIBUTES & OPTIONS	1.92 TB NVMe SSD	3.84 TB NVMe SSD	7.68 TB NVMe SSD	15.36 TB NVMe SSD
Raw node capacity	46 TB	92 TB	184.3 TB	368.6 TB
NVMe SSD Non-SED drives (2.5") per node	24			
Operating system	PowerScale OneFS 9.2 or later			
ECC memory (per node)	736 GB			
Front-end networking (per node)	Dual port 25G NIC supporting 10G or 25G connections (SFP+/SFP28) Dual port 100G NIC supporting 40G or 100G connections			
Infrastructure networking (per node)	2 InfiniBand connections with QDR links or Dual port 100G NIC supporting 40G or 100G connections (QSFP+/QSFP28)			
Max Power Consumption @ 200~240V (per node) <sup>1</sup>	859 Watts (@25°C)			
Typical thermal rating	2931 BTU/hr			

<sup>1</sup>Values at <25° C are reflective of more steady state maximum values during normal operation

## PowerScale F600 All-NVMe Specifications

F600 ATTRIBUTES & OPTIONS	1.92 TB SSD	3.84 TB SSD	7.68 TB SSD	15.36 TB SSD
Raw node capacity	15.36 TB	30.72 TB	61.44 TB	122.88 TB
NVMe SSD Non-SED drives (2.5") per node	8			
Operating system	PowerScale OneFS 9.0 or later			

ECC memory (per node)	128, 192 or 384 GB
Front-end networking (per node)	Dual port 25G NIC supporting 10G or 25G connections (SFP+/SFP28) or Dual port 100G NIC supporting 40G or 100G connections (QSFP+/QSFP28)
Infrastructure networking (per node)	2 InfiniBand connections with QDR links or Dual port 100G NIC supporting 40G or 100G connections (QSFP+/QSFP28)
Max Power Consumption @ 200~240V (per node) <sup>1</sup>	467 Watts (@25°C)
Typical thermal rating	1593.5 BTU/hour

<sup>1</sup>Values at <25° C are reflective of more steady state maximum values during normal operation

## PowerScale F200 All-Flash Specifications

F200 ATTRIBUTES & OPTIONS	960 GB SSD	1.92 TB SSD	3.84 TB SSD	7.68 TB SSD
Raw node capacity	3.84 TB	7.68 TB	15.36 TB	30.72 TB
SSD drives (2.5") per node	4			
Self-Encrypting drive (SED SSD) FIPS 140-2 compliant option	Yes			
Operating system	PowerScale OneFS 9.0 or later			
ECC memory (per node)	48 GB or 96 GB			
Front-end networking (per node)	Dual port 25G NIC supporting 10G or 25G connections (SFP+/SFP28)			
Infrastructure networking (per node)	2 InfiniBand connections with QDR links or Dual port 25G NIC supporting 10G or 25G connections (SFP+/SFP28)			
Max Power Consumption @ 200~240V (per node) <sup>1</sup>	239 Watts (@25°C)			
Typical thermal rating	815.5 BTU/hr			

<sup>1</sup>Values at <25° C are reflective of more steady state maximum values during normal operation

CLUSTER ATTRIBUTES	F200	F600	F900
Number of nodes	3 to 252	3 to 252	3 to 252
Raw cluster capacity	11.4TB to 7.7 PB	46TB to 30.96 PB	138 TB to 93 PB
Rack units	3 to 252	3 to 252	6 to 504

## Isilon F800 All-Flash Specifications

F800 ATTRIBUTES & OPTIONS	1.6 TB SSD	3.2 TB SSD	3.84 TB SSD	7.68 TB SSD	15.36 TB SSD
Raw chassis capacity	96 TB	192 TB	230 TB	460 TB	924 TB
SSD drives (2.5") per chassis	60				
Self-Encrypting drive (SED SSD) FIPS 140-2 compliant option	Yes				
Operating system	OneFS 8.1 or later except for self-encrypting drive options which require OneFS 8.1.0.1 or later				
Number of nodes per chassis	4				
ECC memory (per node)	256 GB				
Front-End networking (per node)	2 x 10GbE (SFP+) or 2 x 25GbE (SFP28) or 2 x 40GbE (QSFP+)				
Infrastructure networking (per node)	2 InfiniBand connections supporting QDR links or 2 x 40GbE (QSFP+)				
Max Power Consumption @ 200~240V (per chassis) <sup>1</sup>	1300 Watts (@25°C)				
Typical thermal rating	4,440 BTU/hr				

<sup>1</sup>Values at <25° C are reflective of more steady state maximum values during normal operation

## Isilon F810 All-Flash Specifications

F810 ATTRIBUTES & OPTIONS	3.84 TB SSD	7.68 TB SSD	15.36 TB SSD
Raw chassis capacity	230 TB	460 TB	924 TB
SSD drives (2.5") per chassis	60		
Self-Encrypting drive (SED SSD) FIPS 140-2 compliant option	Yes		
Operating system	OneFS 8.1.3 or later		
Number of nodes per chassis	4		
ECC memory (per node)	256 GB		
Front-End networking (per node)	2 x 10GbE (SFP+) or 2 x 25GbE (SFP28) or 2 x 40GbE (QSFP+)		
Infrastructure networking (per node)	2 X 40GbE (QSFP+)		
Max Power Consumption @ 200~240V (per chassis) <sup>1</sup>	1300 Watts (@25°C)		
Typical thermal rating	4,440 BTU/hour		

<sup>1</sup>Values at <25° C are reflective of more steady state maximum values during normal operation

CLUSTER ATTRIBUTES	F800	F810
Number of chassis	1 to 63	
Number of nodes	4 to 252	
Raw cluster capacity	96 TB to 58 PB	230 TB to 58 PB

# PowerScale Attributes

## PRODUCT ATTRIBUTES

Scale-out architecture	Distributed fully symmetric clustered architecture that combines modular storage with OneFS operating system in a single volume, single namespace and single filesystem
Modular design	Four self-contained Isilon nodes include server, software, HDDs and SSDs in a 4U rack-mountable chassis. 1U or 2U Rack-mountable PowerScale node that integrates into existing PowerScale and Isilon clusters with backend Ethernet or InfiniBand connectivity
Operating system	PowerScale OneFS distributed file system creates a cluster with a single file system and single global namespace. It is fully journaled, fully distributed, and has a globally coherent write/read cache
High availability	No-single-point-of-failure. Self-healing design protects against disk or node failure; includes back-end intra-cluster failover
Scalability	A cluster can scale up to 252 nodes. Minimum number of Isilon nodes per cluster is four. Minimum number of PowerScale all-flash nodes per cluster is three. Add nodes to scale performance and capacity
Data protection	FlexProtect file-level striping with support for N+1 through N+4 and mirroring data protection schemes
2-way NDMP	Supports two ports of Fibre Channel (8G) that allows for two-way NDMP connections and two ports of standard 10GbE connectivity
Data retention	SmartLock policy-based retention and protection against accidental deletion
Security	File system audit capability to improve security and control of your storage infrastructure and address regulatory compliance requirements
Efficiency	SmartDedupe data deduplication option, which can reduce storage requirements by up to 35 percent. Inline data reduction and compression available on F200, F600, F900, F810 and H5600
Automated storage tiering	Policy-based automated tiering options including SmartPools and CloudPools software to optimize storage resources and lower costs
Network protocol support	NFSv3, NFSv4, NFS Kerberized sessions (UDP or TCP), SMB1 (CIFS), SMB2, SMB3, SMB3-CA, Multichannel, HTTP, FTP, NDMP, SNMP, LDAP, HDFS, S3, ADS, NIS reads/writes
Data replication	SyncIQ fast and flexible one-to-many file-based asynchronous replication between clusters

## ENVIRONMENTAL SPECIFICATIONS – POWER

Power factor is a measure of how effectively you are using electricity. The power factor of an AC electrical power system is defined as the ratio of the real power absorbed by the load to the apparent power flowing in the circuit and is a dimensionless number in the closed interval of -1 to 1. A power factor of less than one indicates the voltage and current are not in phase, reducing the instantaneous product of the two.

For max power consumption information during unexpected environmental conditions, please refer to the "Site Preparation and Planning Guide".

POWER SUPPLY: key Specifications and Efficiency for **F200, F600 and F900**

5 | Dell EMC PowerScale All-Flash Family Spec Sheet

© 2021 Dell Inc. or its subsidiaries.

Attribute	F200 and F600	F900
Class	Platinum	Platinum
Heat dissipation (maximum)	2902 BTU/hr	4100 BTU/hr
Frequency	50/60 Hz	50/60 Hz
Voltage	100-240V, 10 A – 5 A	100-240V, 12 A – 6.5 A

**Operating Environment:** 10°C to 35°C (50°F to 95°F) with no direct sunlight on the equipment

For additional information about environmental measurements for specific system configurations, see [Dell.com/environmental\\_datasheets](http://Dell.com/environmental_datasheets)

**POWER SUPPLY: F800 and F810:** Dual-redundant, hot-swappable 1450W power supplies with power factor correction (PFC); rated for input voltage 180 – 265 VAC (optional rack mount step-up transformer for 90-130 VAC input regions)

Power factor and efficiency rate for **F800 and F810** PSU

System Load	Efficiency	PF
10%	89.74%	0.933
20%	94.28%	0.982
30%	95.02%	0.990
40%	95.19%	0.994
50%	95.11%	0.996
60%	94.77%	0.997
70%	94.50%	0.998
80%	94.13%	0.998
90%	93.66%	0.998
100%	92.93%	0.998

CFM – Volume of airflow; cubic feet/minute  
 F800 and F810: each node 70CFM, total chassis 280CFM (max)

**OPERATING ENVIRONMENT**

Compliant with ASHRAE A3 data center environment guidelines

**DIMENSIONS / WEIGHT:**

The following specifications apply to **F900**:

- Height: 86.8mm (3.42")
- Width: 434mm (17.08")
- Depth: 737.5mm (29.04") (end of the power supply latches)

The following specifications apply to **F200 and F600**

- Height: 42.8mm (1.68")
- Width: 434mm (17.08")
- Depth: 808.5mm (31.83") (end of the power supply latches)

The following specifications apply to **F800 and F810**:

- Height: 7" (17.8 cm)
- Width: 17.6" (44.8 cm);
- Depth (front NEMA rail to rear 2.5" SSD cover ejector): 35.8" (91.0 cm);
- Depth (front of bezel to rear 2.5" SSD cover ejector): 37.6" (95.5 cm)

The following max weights per Chassis/node:

- F900: 61.95 lbs. (28.1 kg)
- F200, F600: 48.28 lbs (21.9 kg)
- F800, F810: 170 lbs. (77.1 kgs)

## Safety and EMI Compliance

### Statement of Compliance

This Information Technology Equipment is compliant with the electromagnetic compatibility (EMC) and product safety regulations/standards required by the countries in which the product is sold. EMC compliance is based on FCC part 15, CISPR22/CISPR24 and EN55022/EN55024 standards, including applicable international variations. EMC compliant Class A products are marketed for use in business, industrial, and commercial environments. Product Safety compliance is based on IEC 60950-1 and EN 60951-1 standards, including applicable national deviations.

This Information Technology Equipment is in compliance with EU RoHS Directive 2011/65/EU.

The individual devices used in this product are approved under a unique regulatory model identifier that is affixed to each individual device rating label, which may differ from any marketing or product family name in this datasheet.

For additional information see <http://support.dell EMC.com> under the Safety & EMI Compliance Information tab.

### Take the next step

Contact your Dell EMC sales representative or authorized reseller to learn more about how Isilon scale-out NAS storage can benefit your organization.



[Learn more](#) about Dell Technologies Storage



[Contact](#) a Dell EMC Expert



[View more](#) resources



[Join](#) the conversation with #DellEMCStorage