



CONNECTRIX B-SERIES DS-7730B, DS-7720B & DS-7710B

64Gb/s Fibre Channel Data Center Switches

Overview

The Connectrix B-Series 64Gb/s DS-7700B family of Fibre Channel SAN switches support data growth, demanding workloads and data-center consolidation. The Connectrix DS-7730B and DS-7720B platforms are built for maximum flexibility, scalability and ease of use.

DS-7730B The Connectrix DS-7730B 64G switch is a high-density building block that enables dense rackmount environments to connect more devices and build larger fabrics. With 128 64G ports in a 2U design, organizations can create high-scale fabrics in less space. The DS-7730B utilizes 96 64G SFP+ ports and 16 2x64G double-density optical transceiver (SFP-DD) ports. Each of the 16 SFP-DD transceivers provides 2 ports, making 32 ports available for device or ISL connectivity. The addition of SFP-DD ports allows the DS-7730B to connect more servers, storage, and switches in a small footprint. Built to support maximum flexibility and dense Fibre Channel fabrics, the DS-7730B offers cost-effective, pay-as-you-grow scalability, expanding from 48 ports to 128 ports with Ports on Demand (PoD). The DS-7730B base configuration comes with 48 ports enabled. To scale from 48 ports to 128 ports, additional 24-port SFP+ PODs and a 32-port SFP-DD POD can be installed in any order and combination. In addition, with a 50% latency reduction compared to the previous generation and no oversubscription, the DS-7730B enables maximum performance of NVMe storage and high-transaction workloads. The DS-7730B includes optional features such as Fabric Vision, Extended Fabric, ISL Trunking and Integrated Routing at no additional charge.

DS-7720B The Connectrix DS-7720B Switch is a 64-port, ultra-dense 1U switch designed to build high-performance fabrics that maximize flash and NVMe storage to meet demanding workloads. Delivering unmatched 64G performance and 50% lower latency compared to the previous generation, this switch delivers a fixed-port building block designed to maximize the performance of flash and NVMe environments to meet demanding workloads. This enterprise-class switch offers pay-as-you-grow scalability with Ports on Demand (PoD). Organizations can quickly, easily, and cost-effectively scale from 24 to 64 ports. The DS-7720B provides up to 56 64G SFP+ ports and 8 2x64G double-density SFP-DD ports, all in an efficient 1U package. Each SFP-DD transceiver provides 2 ports, making 16 ports available for device or ISL connectivity. The Connectrix DS-7720B base configuration comes with 24 ports enabled and can scale to 56 ports with SFP+ transceivers only or 64 ports by installing SFP+ and SFP-DD POD licenses in any order and any combination. Each SFP-DD port can accommodate SFP+ or SFP-DD transceivers, providing the flexibility to use either type of transceiver in those ports when needed. The DS-7720B switch is fully licensed, meaning software features such as Fabric Vision, Extended Fabric, ISL Trunking, Integrated Routing and FICON CUP are included at no additional charge. The DS-7720B is certified for mainframe environments.

DS-7710B The Connectrix DS-7710B 24-port entry level Switch comes in a 1U form factor. It is capable of supporting 8,16,32 and 64 Gbps Fibre Channel speed. The base switch is offered in two rear-to-front airflow SKUs, one with 32G SFPs and the other with 64G SFPs. DS-7710B base configuration comes with 8 ports enabled and can scale to 24 ports with Ports on Demand kits that comes with 8 ports of 32G or 64G SFPs.

The DS-7710B switch is fully licensed, meaning software features such as Fabric Vision, Extended Fabric, ISL Trunking and Integrated Routing. A single integrated Fan/ Power supply unit and rack mount kit are included at no additional charge.

Management and the Autonomous SAN

The DS-7700B family of switches simplifies deployment, configuration and management of SAN resources with a collection of easy-to-use tools. The simplified user interface of Web Tools makes the SAN easier to manage. To further simplify operations and increase visibility, the switches include Fabric Vision technology to monitor and analyze the SAN. This technology provides visibility and insight to quickly identify problems and achieve critical service-level agreements (SLAs). Fabric Vision technology is a suite of features that leverage comprehensive data collection capabilities with powerful analytics to quickly understand the health and performance of the environment and identify any potential impacts or trending problems.

The Connectrix B-Series 64G switches utilize built-in analytics to optimize performance and eliminate disruptions. In addition, these switches collect comprehensive telemetry data across the fabric to enable advanced analytics. To visualize the data, SANnav Management Portal enables organizations to easily understand the health and performance of the SAN. Organizations can leverage SANnav Management Portal to streamline management workflows, thereby accelerating the deployment of new applications, switches, servers, and storage. Furthermore, SANnav's modernized graphical user interface (GUI) improves operational efficiencies with visual dashboards for instant visibility and faster troubleshooting. By leveraging automation, SAN admins gain the ability to automate repetitive tasks to save time and mitigate disruptions with limited expertise.

With self-optimizing capabilities, Connectrix B-Series technology utilizes actionable intelligence to maximize performance. Real-time monitoring of health and performance characteristics enables the network to make smarter decisions on traffic prioritization, congestion management and notification to ensure optimal network performance for applications and storage. The DS-7700B switches also deliver a traffic optimizer that guarantees critical application performance by automatically prioritizing traffic. This advanced capability classifies and separates traffic with similar characteristics.

The combination of SAN analytics and automation technologies unlocks the capabilities to deliver a self-learning, self-optimizing and self-healing SAN. Click here for video on [Connectrix B-Series Autonomous SAN](#).

DS-7700B

System Architecture	Technical Specification
Fibre Channel ports	<p>DS-7730B: Switch mode (default): Minimum of 48 ports and maximum of 128 ports. Ports are enabled in increments of 24 ports up to 128 ports via Ports on Demand (PoD) licenses; E_Ports, F_Ports, D_Ports, EX_Ports.</p> <p>Switch mode (default): Minimum of 24 ports and maximum of 64 ports. Ports are enabled in increments of 8 ports up to 56 ports using SFP+ PODs, and up to 64 ports using a combination of SFP+ and SFP-DD PODs; E_Ports, F_Ports, D_Ports, EX_Ports. Access Gateway default port mapping: 56 F_Ports, 8 N_Ports</p> <p>DS-7720B: 64 ports (48 64G SFP+ ports, plus 8 2x64G SFP-DD ports), each supporting E_Ports, F_Ports, M_Ports, D_Ports, and EX_Ports.</p> <p>24-port base configuration; additional ports are enabled with three 8-port SFP+ PODs (Ports on Demand), plus a 16-port SFP-DD POD (8 2x64G SFP-DD transceivers), scaling the switch from 24 ports to 64 ports.</p> <p>Access Gateway default port mapping: 48 F_Ports, 8 N_Ports.</p> <p>DS-7710B: a minimum of 8 ports, can go up to maximum of 24 ports (with 32G or 64G SWL SFP), Each port supports E/F/Ex/D_Port.</p>
Scalability	Full-fabric architecture with a maximum of 239 switches
Certified maximum	4K active nodes; 56 switches, 19 hops in Fabric OS (FOS) fabrics
Performance	Fibre Channel: 8.5Gb/s line speed, full duplex; 10.53Gb/s line speed, full duplex; 14.025Gb/s line speed, full duplex; 28.05Gb/s line speed, full duplex; 57.8Gb/s line speed, full duplex; auto-sensing of 8, 10, 16, 32, and 64G port speeds. 10G optionally programmable to fixed-port speed.
ISL Trunking	Frame-based trunking with up to eight SFP+ ports per ISL trunk; up to 512Gb/s per ISL trunk. Exchange-based load balancing across ISLs with Dynamic Path Selection (DPS) included in FOS
Aggregate bandwidth	<p>DS-7730B: 8.192 Tb/s</p> <p>DS-7720B: 4.096 Tb/s</p> <p>DS-7710B: 3.072 Tb/s</p>
Maximum fabric latency	Latency for locally switched ports is 460 ns (including FEC)
Maximum frame size	2112-byte payload
Frame buffers	24K per switching ASIC
Classes of service	Class 2, Class 3, Class F (inter-switch frames)
Port types	<p>DS-7730B: D_Port (ClearLink® Diagnostic Port), E_Port, EX_Port, F_Port, M_Port; optional port-type control</p> <p>DS-7720B: D_Port (ClearLink® Diagnostic Port), E_Port, EX_Port, F_Port, M_Port; optional port-type control</p> <p>Access Gateway mode: F_Port and NPIV-enabled N_Port</p> <p>DS-7710B: F_Port, E_Port, D_Port on 128 ports.</p>
Data traffic types	Fabric switches supporting unicast
Media types	<p>DS-7730B:</p> <p>64Gb/s: hot-pluggable SFP+, LC connector; 64Gb/s SWL</p> <p>32Gb/s: hot-pluggable SFP+, LC connector; 32Gb/s SWL, LWL 10 km, ELWL 25 km</p> <p>10Gb/s: hot-pluggable SFP+, LC connector; 10Gb/s SWL, LWL 10 km</p> <p>2x64G FC SFP-DD SN connectors: SWL</p> <p>DS-7720B</p> <p>64Gb/s: hot-pluggable SFP+, LC connector; 64Gb/s SWL</p> <p>32Gb/s: hot-pluggable SFP+, LC connector; 32Gb/s SWL, LWL 10 km, ELWL 25 km</p> <p>10Gb/s: hot-pluggable SFP+, LC connector; 10Gb/s SWL, LWL 10 km</p> <p>2x64G FC SFP-DD SN connectors: SWL</p> <p>DS-7710B</p> <p>64Gb/s: hot-pluggable SFP+, LC connector; 64Gb/s SWL</p> <p>32Gb/s: hot-pluggable SFP+, LC connector; 32Gb/s SWL, LWL 10 km, ELWL 25 km</p> <p>Note: Fibre Channel distance is subject to fiber-optic cable and port speed</p>
USB	One standard USB port for firmware download, SupportSave, and configuration upload or download

Fabric services	BB Credit Recovery; Advanced Zoning (Default Zoning, Port/WWN Zoning, Peer Zoning); Congestion Signaling; Dynamic Path Selection (DPS); Extended Fabrics; Fabric Performance Impact Notification (FPIN); Fabric Vision; FDMI; FICON CUP; Flow Vision; F_Port Trunking; FSPF; Integrated Routing; ISL Trunking; Management Server; Name Server; NPIV; NTP v3; Port Decommission/Fencing; QoS; Registered State Change Notification (RSCN); Slow Drain Device Quarantine (SDDQ); Target-Driven Zoning; Traffic Optimizer; Virtual Fabrics (Logical Switch, Logical Fabric); VMID+ and AppServer
SAN Extension	<p>DS-7730B: Integrated optional 10G Fibre Channel for DWDM MAN connectivity. Note: Fibre Channel in-flight compression and encryption are not supported on this switch; Supported distances are limited and dependent on FC speed. See Fabric OS Admin Guide for more details; Integrated optional 10G Fibre Channel for DWDM MAN connectivity is supported.</p> <p>DS-7720B: Fibre Channel, in-flight compression (Brocade LZO) and encryption (AES-GCM-256 encryption on FC ISLs [E_Port]); Integrated optional 10G Fibre Channel for DWDM MAN connectivity</p> <p>DS-7710B: N/A</p>

DS-7700B	
Management	Technical Specification
Supported management software	Advanced Web Tools; Brocade SANnav Management Portal and SANnav Global View; Command Line Interface (CLI); EZSwitchSetup; HTTP/HTTPS; RESTful API; SNMP v1/v3 (FE MIB, FC Management MIB); SSH.
Security	<p>DS-7730B: DH-CHAP (between switches and end devices); FCAP switch authentication; HTTPS; IP filtering; LDAP with IPv6; OpenLDAP; Port Binding; RADIUS; TACACS+; user-defined Role-Based Access Control (RBAC); Secure Boot; Secure Copy (SCP); Secure Syslog; SFTP; SSH v2; SSL; Switch Binding; Trusted Switch; Trusted FOS Certificates (TruFOS); root access removed.</p> <p>DS-7720B: DH-CHAP (between switches and end devices); FCAP switch authentication; HTTPS; IP filtering; LDAP with IPv6; OpenLDAP; Port Binding; RADIUS; TACACS+; user-defined Role-Based Access Control (RBAC); Secure Boot; Secure Copy (SCP); Secure Syslog; SFTP; SSH v2; SSL; Switch Binding; Trusted Switch</p> <p>DS-7710B: DH-CHAP (between switches and end devices); FCAP switch authentication; HTTPS; IP filtering; LDAP with IPv6; OpenLDAP; Port Binding; RADIUS; TACACS+; user-defined Role-Based Access Control (RBAC); Secure Boot; Secure Copy (SCP); Secure Syslog; SFTP; SSH v2; SSL; Switch Binding; Trusted Switch.</p>
Management access	<p>DS-7730B: 10/100/1000Mb/s Ethernet (RJ-45) port, serial console port, and USB port</p> <p>DS-7720B: 10/100/1000Mb/s Ethernet (RJ-45), port and serial console port (mini-USB)</p> <p>DS-7710B: 1000 Mbps Ethernet (RJ-45), in-band over Fibre Channel, RJ45 serial console port, and one USB port</p>
Diagnostics	<p>DS-7730B: Active Support Connectivity (ASC) and Brocade Support Link (BSL); built-in flow generator; ClearLink optics and cable diagnostics, including electrical/optical loopback, link traffic/latency/distance; Fabric Performance Impact Monitoring (FPI); flow mirroring; Forward Error Correction (FEC); frame viewer; Global Quiet Time (GQT); IO Insight for SCSI and NVMe monitoring; Monitoring and Alerting Policy Suite (MAPS); nondisruptive daemon restart; optics health monitoring; POST and embedded online/offline diagnostics, including environmental monitoring, FCping, and Pathinfo (FC traceroute); power monitoring; RAStracE logging; Rolling Reboot Detection (RRD); Syslog/Audit Log; VM Insight.</p> <p>DS-7720B: Active Support Connectivity (ASC) and Brocade Support Link (BSL); built-in flow generator; ClearLink optics and cable diagnostics, including electrical/optical loopback, link traffic/latency/distance; Fabric Performance Impact Monitoring (FPI); flow mirroring; Forward Error Correction (FEC); frame viewer; IO Insight for SCSI and NVMe monitoring; Monitoring and Alerting Policy Suite (MAPS); nondisruptive daemon restart; optics health monitoring; POST and embedded online/offline diagnostics, including environmental monitoring, FCping, and Pathinfo (FC traceroute); power monitoring; RAStracE logging; Rolling Reboot Detection (RRD); Syslog/Audit Log; VM Insight</p> <p>DS-7710B: ClearLink optics and cable diagnostics, including electrical/optical loopback, link traffic/latency/distance; flow mirroring; built-in flow generator; POST and embedded online/offline diagnostics, including environmental monitoring, FCping and Pathinfo (FC traceroute), frame viewer, non-disruptive daemon restart, optics health monitoring, power monitoring, RAStracE logging, and Rolling Reboot Detection (RRD).</p>

DS-7700B

Mechanical	Technical Specification
Enclosure	Front-to-rear airflow; non-port-side exhaust; power from back Rear-to-front airflow; non-port-side intake; power from back
Size	<p>DS-7730B Width: 440.00 mm (17.32 in.) Height: 86.70 mm (3.41 in.) Depth: 609.60 mm (24.00 in.)</p> <p>DS-7720B Width: 440.00 mm (17.32 in.) Height: 43.90 mm (1.73 in.) Depth: 355.60 mm (14.00 in.)</p> <p>DS-7710B Width: 428.8 mm (16.88 in.) Height: 42.9 mm (1.69 in.) Depth: 306.6 mm (12.07 in.)</p>
System weight	<p>DS-7730B: 18.92 kg (41.71 lbs) with two power supply FRUs and three fan FRUs, without transceivers DS-7720B: 7.17 kg (15.8 lb) with two power supply FRUs, without transceivers DS-7710B: 4.24 kg (9.35 lbs.) (estimated) with one power supply and four fans, without transceivers</p>

DS-7700B

Environment	Technical Specification
Operating environment	Temperature: 0°C to 40°C (32°F to 104°F) Humidity: 8% to 90% (non-condensing)
Non-operating environment	Temperature: -25°C to 70°C (-13°F to 158°F) Humidity: 8% to 90% (non-condensing)
Operating altitude	Up to 3000 m (9842 ft)
Storage altitude	Up to 12 km (39,370 ft)
Shock	Operating: Up to 20G, 6 ms half-sine Non-operating: Half-sine, 33G, 11 ms, 3/G axis
Vibration	<p>DS-7730B: Operating: 0.5 Grms sine, 0.4 Grms random, 5 Hz to 500 Hz Nonoperating: 2.0 Grms sine, 1.1 Grms random, 5 Hz to 500 Hz</p> <p>DS-7720B: Operating: 0.25 Grms sine, 0.40 Grms random, 5 Hz to 500 Hz Non-operating: 5 Hz at 0.5 Grms; 10–500 Hz at 1.0 Grms (sine vibration); 3–500 Hz at 1.12 Grms (random vibration)</p> <p>DS-7710B: Operating: 0.5 g sine, 0.4 grms random, 5 to 500 Hz Non-operating: 2.0 g sine, 1.1 grms random, 5 to 500 Hz</p>
Heat dissipation	<p>DS-7730B: 128 ports at 3195 Btu/hr DS-7720B: 64 ports at 1192 Btu/hr DS-7710B: 24 ports at 351.55 BTU/hr</p>
Carbon Footprint Reports	DS-7720B and DS-7730B (These documents are created and maintained by Broadcom, Inc.)

DS-7700B

Power	Technical Specification
Power supply	<p>DS-7730B: Dual, hot-swappable, redundant power supplies with integral cooling fans and status LEDs. 80 Plus Gold.</p> <p>DS-7720B: Dual, hot-swappable redundant power supplies with integrated system cooling fans. 80 Plus Gold.</p> <p>DS-7710B: Base switch includes a single, fixed power supply with four integrated system cooling fans.</p>
AC input	<p>DS-7730B: 100 to 240 VAC nominal, 90 to 264 VAC range, maximum input current 12A @ 100V or 5A @ 240V</p> <p>DS-7720B: 90V to 264V, 4.5A</p> <p>DS-7710B: 100V to 240V nominal, 85V to 264V range, max 1.23A</p>
AC input line frequency	50 Hz to 60 Hz nominal, 47 Hz to 63 Hz range
AC power consumption	<p>DS-7730B: 969W with all 128 ports operating at 64G (96 ports populated with 64G SWL transceivers, 16 ports populated SFP-DD SWL transceivers, each providing two ports of 64G connectivity). 364W for an empty chassis with no transceivers.</p> <p>DS-7720B: 349W with all 64 ports operating at 64G (48 ports populated with 64G SWL transceivers and 8 ports populated with 2x64G SFP-DD SWL transceivers). 57W for an empty chassis with no transceivers.</p> <p>DS-7710B: Max 105W with all 24 ports running with 100% traffic rate. Fans at max speed, 45 Watts for empty chassis with no optical transceivers.</p>

Dell Ordering SKUs

DS-7710B SKUs:	DS-7720B SKUs:	DS-7730B SKUs:
210-BNXX (RTF airflow) Populated with eight 32G SFPs, includes ENT Bundle, INTEG. FAN/PSU, with rackmount kit	210-AZLV (FTR airflow), populated with twenty-four 64G SFPs, with rackmount kit	210-BELU (FTR airflow), populated with forty-eight 64G SFPs, includes rack mount kit
210- BNXY (RTF airflow) Populated with eight 64G SFPs, includes ENT Bundle, INTEG. FAN/PSU, with rackmount kit	210-AZLW (RTF airflow), populated with twenty-four 64G SFPs, with rackmount kit	210-BELT (RTF airflow), populated with forty-eight 64G SFPs, includes rack mount kit
	210-AZLT (FTR airflow), populated with twenty-four 32G SFPs, with rackmount kit	
	210-AZLU (RTF airflow), populated with twenty-four 32G SFPs, with rackmount kit	



Dell Technologies Services

Plan, deploy, manage and support
IT transformation with our top-rated
services

Consulting

Dell Technologies Consulting Services provides industry professionals with a wide range of tools and the experience you need to design and execute plans to transform your business.

Deployment

Accelerate technology adoption with ProDeploy Enterprise Suite. Trust our experts to lead deployments through planning, configuration and complex integrations.

Management

Regain control of operations with flexible IT management options. Our Residency Services help you adopt and optimize new technologies and our Managed Services allow you to outsource portions of your environment to us.

Support

Increase productivity and reduce downtime with ProSupport Enterprise Suite. Expert support backed by proactive and predictive artificial intelligence tools.

Education

Dell Technologies Education Services help you develop the IT skills required to lead and execute transformational strategies. Get certified today.

Learn more at DellTechnologies.com/Services

Connectrix B-Series 64Gb/s Switch Specification Sheet

2025 Dell Inc. or its subsidiaries. Rev July 2025.