

# DELL VPLEX HARDWARE FAMILY

**VPLEX™ delivers continuous data availability, transparent data mobility and non-disruptive data migration for mission-critical applications**

VPLEX's unique implementation of distributed cache coherency allows the exact same data to be read/write accessible across two storage systems at the same time. This ensures uptime for mission-critical applications scenarios and enables seamless data mobility across arrays without host disruption and thereby eliminating a variety of planned downtime instances like tech refresh, load balancing, and infrastructure maintenance. The storage systems connected to VPLEX can be in a single datacenter (VPLEX Local) or separated by distance (VPLEX Metro).

VPLEX engine is the core building block of a VPLEX cluster that can be configured as single, dual or quad engine in a single rack. VS6 is the current generation of VPLEX engine. A VPLEX cluster is configured with all VS6 engines single, dual or quad options.

VPLEX for All-Flash is an all-inclusive solution with a software license for any capacity on one or multiple Dell all-flash arrays.

All VPLEX systems ship with Storage Monitoring and Reporting (M&R) for VPLEX.

Note: VPLEX VS2 is no longer available for sale. VPLEX VS2 is included in this Specification Sheet for historical reference.



## Specifications Management

HTML5-based graphical user interface (GUI) ; REST API v2

Command line interface (CLI)

10/100/1,000 Ethernet port/LAN connectivity

VS2 Platform: In rack 1RU server external to VPLEX engine

VS6 Platform: Embedded two Management Module & Control Station (MMCS) in VS6 base engine with internal storage

All VPLEX systems ship with Storage M&R for VPLEX

## Systems Capacities

	VS2		VS6	
	Local	Metro	Local	Metro
Max. Virtual Volumes	8,000	16,000	12,000	24,000
Max. Storage Elements	8,000	16,000	12,000	24,000
Number of Initiators	1,600	3,200	1,600	3,200

## VPLEX Engine Cluster Configuration

	VS2			VS6			
	Single	Dual	Quad		Single	Dual	Quad
Number of engines per cluster	1	2	4	Number of engines per cluster	1	2	4
Front end 8Gb/s Fibre Channel ports	8	16	32	Front end 16Gb/s Fibre Channel ports	8	16	32
Back end 8Gb/s Fibre Channel ports	8	16	32	Back end 16Gb/s Fibre Channel ports	8	16	32
WAN communication	MetroIP 10GigE or MetroFC 8Gb FC			WAN communication	MetroIP 10GigE or MetroFC 16Gb FC		
Intra-engine communication	8Gb/s FC			Intra-engine communication	Infiniband, 40Gb/s		
Intra-engine communication switch	8-port 8Gb/s FC switch			Intra-engine communication switch	12-port 40Gb/s Infiniband switch		

## Power Cabling

### VS2

Connector	Operating Voltage and Frequency	Service Type	Region
NEMA L6-30P	200-240 VAC and 50-60 Hz	30-amp, single-phase	North America, Japan
IEC 309 332P6	200-240 VAC and 50-60 Hz	32-amp, single-phase	International (except Australia)
CLIPSAL P/N 56PA332	200-240 VAC and 50-60 Hz	32-amp, single-phase	Australia
Russellstoll 3750DP	200-240 VAC and 50-60 Hz	30-amp, single-phase	North American, Japan

### VS6

Connector	Operating Voltage and Frequency	Service Type	Region
NEMA L6-30P	200-240 VAC and 50-60 Hz	30-amp, single-phase	North America, Japan
IEC 309 332P6	200-240 VAC and 50-60 Hz	32-amp, single-phase	International (except Australia)
CLIPSAL P/N 56PA332	200-240 VAC and 50-60 Hz	32-amp, single-phase	Australia
Russellstoll 3750DP	200-240 VAC and 50-60 Hz	30-amp, single-phase	North America, Japan
NEMA L7-30P	200-240 VAC and 50-60 Hz	30-amp, single-phase	North America, Japan

Note: Each AC circuit requires a source connection that can support a minimum of 4800 VA of single-phase, 200-240 VAC input power. For high availability, the left and right sides of the cabinet must receive power from separate branch feed circuits.

## Interoperability

Please see the Dell Technologies [E-Lab Simplified Support Matrix](#) for details or download the E-Lab Navigator App for iPhone or Android.

## Environmental Specifications

### Dimensions

VS2				VS6		
	Height	Width	Depth	Height	Width	Depth
VPLEX Cabinet	75 in (190cm)	24in (60cm)	39.37in (100 cm) overall; 41.5in (105.4 cm) including front door	75in (190cm)	24in (60cm)	39.37in (100 cm) overall; 41.5in (105.4 cm) including front door
VPLEX Engine				6.97in (17.7cm)	18.87in (47.92cm)	30.62in (77.77cm)

\* The VS6 engine requires a front and rear EIA RS310-compliant 19-in. NEMA rack with 38- in. minimum rack depth and cannot be installed in a Dell provided VS2 rack. Please refer the VS6 hardware setup guide for more information.

### Weight

	VS2	VS6
Single Engine Cluster	754 lb (342 kg)	667 lb (302.5 kg)
Dual Engine Cluster	1,017 lb (462 kg)	852 lb (386.5 kg)
Quad Engine Cluster	1,418 lb (644 kg)	1086 lb (492.6 kg)

## Operating Specifications

### Power and Heat

VS2			VS6	
	Total Power Consumption (kVA)	Heat Dissipation (Btu/Hr)	Total Power Consumption (kVA)	Heat Dissipation (Btu/Hr)
Single Engine	0.6	1,900	1.83	6,244
Dual Engine	1.29	4,000	4.03	13,750
Quad Engine	2.32	7,200	7.63	26,034


The power consumption and heat dissipation totals are steady-state maximum operation at 25°C for VS2 and at 35°C for VS6

### Non-Operating Temperature, Humidity and Altitude

VS2			VS6		
Temperature	Humidity	Altitude	Temperature	Humidity	Altitude
-40 – 149°F (-40 – 65°C)	10 – 90% Non-condensing	25,000 ft (7.62 km) max.	-40 – 149°F (-40 – 65°C)	10 – 90% Non-condensing	25,000 ft (7.62 km) max.

## Operating Temperature, Humidity, and Altitude

VS2			VS6		
Temperature	Humidity	Altitude	Temperature	Humidity	Altitude
50 – 90°F (10 – 32°C)	20 – 80%, Non-condensing	10,000 ft (3 km) max.	50 – 95°F (10 – 35°C)	20 – 80%, Non-condensing	10,000 ft (3 km) max.



[Learn More](#) about  
VPLEX solutions



[Contact](#) a Dell Expert