

# CONNECTRIX B-SERIES ED-DCX7 ENTERPRISE DIRECTORS

64 Gigabits per second (Gb/s) Fibre Channel Enterprise Directors

## Overview

The Dell Connectrix ED-DCX7 Directors provide a modular building block, purpose-built for scalability to accommodate growth and power large-scale storage environments. With a 50% latency reduction compared to the previous generation, the ED-DCX7 Directors maximize the performance of NVMe storage and high-transaction workloads, eliminating I/O bottlenecks and unleashing the full performance of next-generation storage. In addition, the ED-DCX7 Directors lay the foundation for the Connectrix B-Series autonomous SAN. With autonomous SAN technology, the director harnesses the power of analytics and the simplicity of automation to optimize performance, ensure reliability and simplify management. Leveraging these capabilities enables organizations to realize a self-learning, self-optimizing and self-healing SAN.

The ED-DCX7 directors provide up to 384 64Gb ports or up to 512 32Gb/s ports, enabling organizations to scale more devices, applications and workloads. With diverse deployment options, multiprotocol flexibility and mixed blade capability, organizations can adapt and optimize their businesses to meet next-generation storage and server requirements. Connectrix Directors support the concurrent use of both traditional Fibre Channel and NVMe storage traffic, allowing organizations to seamlessly integrate Fibre Channel networks with next-generation NVMe-based storage, without a disruptive rip-and-replace.

## Connectrix ED-DCX7 Chassis Models

There are two Connectrix ED-DCX7 models to address all your storage networking requirements. To accommodate the requirements of today's data centers, the ED-DCX7 director models provide two airflow options for each chassis. Having two airflow options extends the flexibility for hot/cold aisle network designs. Non-port-side intake to port-side exhaust or port-side intake to non-port-side exhaust options are available.

**Note:** Content within parenthesis below are ordering SKUs. For example, "210-AWYK" is the SKU for the legacy "ED-DCX7-8B" model number. SKUs are referenced in this document only in the first iteration.

- **ED-DCX7-8B (210-AWYK):** This 14U chassis has eight vertical blade slots to provide up to 384 64Gb/s line rate ports, or up to 512 32Gb/s line rate ports for device connectivity. An additional 32 Inter-Chassis Link (ICL) connections provide 128 ports for chassis-to-chassis interconnect.
- **ED-DCX7-4B (210-AWYJ):** This 8U chassis has four horizontal blade slots to provide up to 192 64Gb/s line rate ports, or up to 256 32Gb/s line rate ports for device connectivity. An additional 16 ICL connections provide 64 ports for chassis-to-chassis interconnect.

ED-DCX7 directors build upon years of innovation and leverage the core technology of Connectrix B-Series systems to consistently deliver five-nines availability in the world's most demanding data centers. Delivering non-disruptive software upgrades, hot-pluggable components, and a no-single-point-of-failure design, the Connectrix ED-DCX7 offers a highly resilient solution for today's enterprise-class storage environments.

Please review the SKUs in the table below for descriptions of the port blades available for the ED-DCX7 directors.

## Analyze the SAN to Optimize Performance and Reliability

IT organizations are responsible for delivering non-stop performance and reliability to ensure that service-level agreements (SLAs) are met. They need analytics to help extract actionable intelligence from their environment and simplified management tools to easily understand the state of their environment. This requires an infrastructure that can automatically learn its performance and health characteristics, identify potential risks, and provide recommended actions to resolve issues.

With ED-DCX7 Directors, a self-learning SAN is enabled that gathers and transforms millions of data points into actionable intelligence to make fast, informed decisions to optimize performance and ensure reliability. Connectrix products proactively monitor I/O performance and behavior data points through integrated network sensors to gain deep insight into the environment. The information captured is displayed in Connectrix SANnav™ Management Portal to quickly identify and isolate problems before they impact application availability. With built-in best practice recommendations, organizations can simplify troubleshooting by identifying and isolating issues to resolve them as fast as possible. Combining these tools with automation, Connectrix technology can detect abnormal traffic behaviors and degraded performance to automatically take corrective action, eliminating the potential impact of this issue. These new autonomous SAN technologies greatly simplify SAN management and enable unparalleled network performance and reliability.

Click here for video on [Connectrix B-Series Autonomous SAN](#).

## Connectrix B-Series Unified Storage Fabric (USF)

Included in Connectrix B-Series Fabric Operating System (FOS) version 9.2.1+ is a technology named Unified Storage Fabric (USF). Through the concept of logical switches, USF enables IP storage protocols such as iSCSI, NVMe/TCP and File to exist in parallel with Fibre Channel on a Connectrix B-Series SAN fabric. This technology may appeal to customers who want to leverage their existing investment in Connectrix B-Series Fibre Channel to also carry storage traffic for iSCSI, NVMe/TCP and File.

# Connectrix ED-DCX7 Directors

## System Architecture

## Technical Specification

|                                 |  |
|---------------------------------|--|
| Chassis                         | <p>Single chassis</p> <ul style="list-style-type: none"> <li>• <b>ED-DCX7-8B:</b> Non-blocking architecture <ul style="list-style-type: none"> <li>○ ED-DCX7-8B Director with 48 64Gb/s port blades, 31Tb/s of aggregate chassis bandwidth (384 device ports with a 64Gb/s data rate plus 32 Inter-Chassis Links (ICLs))</li> <li>○ ED-DCX7-8B Director with 64 32Gb/s port blades: 22.8Tb/s of aggregate chassis bandwidth (512 device ports with a 32Gb/s data rate plus 32 Inter-Chassis Links (ICLs))</li> </ul> </li> <li>• <b>ED-DCX7-4B:</b> Non-blocking architecture <ul style="list-style-type: none"> <li>○ ED-DCX7-4B Director with 48 64Gb/s port blades, 15.5Tb/s of aggregate chassis bandwidth (192 device ports with a 64Gb/s data rate plus 16 Inter-Chassis Links (ICLs))</li> <li>○ ED-DCX7-4B Director with 64 32Gb/s port blades: 11.4Tb/s of aggregate chassis bandwidth (256 device ports with a 32Gb/s data rate plus 16 Inter-Chassis Links (ICLs))</li> </ul> </li> </ul> <p>Each provides support for (E, F, D, M, SIM, and EX) Fibre Channel ports using 48-port 64Gb/s Fibre Channel blades.</p>   |
| Control processor               | Redundant (active/standby) control processor modules   |
| Scalability                     | Full-fabric architecture of 239 switches   |
| Certified maximum               | 6000 active devices per switch; 56 switches, 19 hops in FOS fabrics; larger fabrics certified as required  |
| Fibre Channel Blade Models/SKUs | <p><b>64Gb/s Capable Switching Blades</b></p> <p><b>210-BJPM:</b> 32 x 64Gb/s double density SFPs for 64-ports of Fibre Channel connectivity. Supports 64/32/16/8 Gb/s Fibre Channel which is configurable at the port level</p> <p><b>PB-DCX7-FC6464GSW (210-BBHK):</b> 48 x 64/32/16/10/8 Gb/s 64 Gb/s port blade fully populated with 64 Gb/s short wave SFP+ optics. 4 Gb/s Fibre Channel is not supported with this blade</p> <p><b>PB-DCX7-FC6432GSW (210-AWYL):</b> 48 x 64/32/16/10/8 Gb/s 64 Gb/s port blade fully populated with 32 Gb/s short wave SFP+ optics. 4 Gb/s Fibre Channel is not supported with this blade</p> <p><b>PB-DCX7-FC6432GLW (210-AWYM):</b> 48 x 64/32/16/10/8 Gb/s 64 Gb/s port blade fully populated with 32 Gb/s long wave SFP+ optics. 4 Gb/s Fibre Channel is not supported with this blade</p> <p><b>32Gb/s Switching Blades</b></p> <p><b>PB-DCX7-FC32-SW (210-AWYN):</b> 48 x 32/16/10/8/4 Gb/s port blade fully populated with 32 Gb/s short wave SFP+ optics</p> <p><b>PB-DCX7-FC32-LW (210-AWYO):</b> 48 x 32/16/10/8/4 Gb/s port blade fully populated with 32 Gb/s long wave SFP+ optics</p> <p><b>PB-DCX6-64P32G (210-AWUO):</b> 64 x 32/16/10/8/4 Gb/s port blade half populated with 8 4x32 Gb/s short wave QSFP optics</p> <p><b>(210-AWUN):</b> DCX6 32Gb/S 48 port blade populated with 48 short wave 32Gb/s optics</p> <p><b>(210-AWUL):</b> DCX6 32Gb/s 48 port blade with no optics</p> |
| Extension Blade                 | <p><b>PB-DCX6-SX6-SW (210-AWUP):</b> Extension blade provides Fibre Channel extension (16x32Gb/s Fibre Channel ports) and IP extension over IP networks (16x1GbE/10GbE and 2x40GbE ports). This blade can be used in ED-DCX6 directors as well.</p>  |

|                          |   |
|--------------------------|---|
| Performance              | <p><b>PB-DCX7-FC64 Port Blade:</b><br/>Fibre Channel: 8.5Gb/s line speed, full duplex; 10.53Gb/s line speed, full duplex; 14.025Gb/s line speed, full duplex; 28.05Gb/s line speed, full duplex; 57.8Gb/s line speed, full duplex. Autosensing of 8, 16, 32, and 64G port speeds depending on SFPs used. 10G port speeds with dedicated SFPs.</p> <p><b>PB-DCX7-FC32 Port Blade:</b><br/>Fibre Channel: 4.25Gb/s line speed, full duplex; 8.5Gb/s line speed, full duplex; 10.53Gb/s line speed, full duplex; 14.025Gb/s line speed, full duplex; 28.05Gb/s line speed, full duplex. Autosensing of 4, 8, 16, and 32G port speeds depending on SFPs used. 10G port speeds with dedicated SFPs.</p> <p><b>PB-DCX6-48P32G Port Blade:</b><br/>Fibre Channel: 4.25Gb/s line speed, full duplex; 8.5Gb/s line speed, full duplex; 10.53Gb/s line speed, full duplex; 14.025Gb/s line speed, full duplex; 28.05Gb/s line speed, full duplex. Autosensing of 4, 8, 16, and 32G port speeds depending on SFPs used. 10G port speeds with dedicated SFPs.</p> <p><b>PB-DCX6-64P32G Port Blade:</b><br/>Fibre Channel: 4.25Gb/s line speed, full duplex; 8.5Gb/s line speed, full duplex; 14.025Gb/s line speed, full duplex; 28.05Gb/s line speed, full duplex. Autosensing of 4, 8, 16, and 32G port speeds depending on QSFPs used.</p> |
| ISL trunking             | Frame-based trunking with up to eight 64Gb/s ports per ISL trunk; up to 512Gb/s per ISL trunk; exchange-based load balancing across ISLs with DPS included in FOS   |
| ICL trunking             | <p>Chassis-to-chassis linkage through connectors on the Core Routing (CR) blade. Can configure the following maximum number of QSFPs per trunk depending on blade type, connecting:</p> <ul style="list-style-type: none"> <li>Up to four QSFP ports in a trunk group between two CR64-4 blades. For trunks that contain four or fewer QSFP ports, ports in a trunk must be located in the same port group on each blade.</li> <li>Up to four QSFP ports in a trunk group between a CR64-4 blade and a CR64-8 blade. For trunks that contain four or fewer QSFP ports, ports in a trunk must be located in the same port group on each blade.</li> </ul> <p>A minimum of two QSFP connections are required for a trunk, and up to four QSFP trunks between pairs of CR64-8 (CR64-4) and CR32-8 (CR32-4).</p>  |
| Multi-chassis ICL ports  | Up to 4608 Fibre Channel ports; ICL ports (32 for 8-slot or 16 per 4-slot chassis, optical QSFP) connect up to 9 chassis in a full-mesh topology or up to 12 chassis in a core-edge topology  |
| Chassis bandwidth        | ED-DCX7-8B: 31Tb/s per chassis with 384 device ports + 32 ICL connections supporting 128 ports<br>ED-DCX7-4B: 15.5Tb/s per chassis with 192 device ports + 16 ICL connections supporting 64 ports   |
| Slot bandwidth           | 3072 Gb/s provides line-rate performance for the PB-DCX6-64P32G blade   |
| Maximum frame size       | 2112-byte payload   |
| Frame buffers            | 24,000 per switching ASIC   |
| Classes of service       | Class 2, Class 3, Class F (inter-switch frames)   |
| Fibre Channel port types | <p><b>CR64-8 and CR64-4 CR blades:</b> E_Port, EX_Port, and D_Port.</p> <p><b>PB-DCX7-FC64, PB-DCX7-FC32, PB-DCX6-48P32G, PB-DCX6-64P32G port blades:</b> F_Port, E_Port, EX_Port, M_Port, SIM, and D_Port. (FC32-X7-48 at 4G speed supports only F_Port connectivity.)</p> <p><b>SX6 extension blade:</b> F_Port, FL_Port, E_Port, SIM, and EX_Port on FC and VE_Port on GbE.</p> <p>Self-discovery is based on switch type (U_Port) with an optional port type control.</p>   |
| Data traffic types       | Fabric switches supporting unicast  |

|                 |   |
|-----------------|---|
| Media types     | <p><b>210-BJPM 64-port port blade:</b><br/>Hot-pluggable, industry-standard Small Form Factor Pluggable Double-Density (SFP-DD) and Small Form Factor Pluggable (SFP+) Media Types</p> <p>PB-DCX7-FC64 port blade<br/>64G FC SFP+ LC connector: SWL, LWL, ELWL<br/>32G FC SFP+ LC connector: SWL, LWL, ELWL<br/>10G FC SFP+ LC connector: SWL, LWL</p> <p>PB-DCX7-FC32 port blade<br/>32G FC SFP+ LC connector: SWL, LWL, ELWL<br/>16G FC SFP+ LC connector: SWL, LWL, ELWL<br/>10G FC SFP+ LC connector: SWL, LWL</p> <p>PB-DCX6-48P32G port blade<br/>32G FC SFP+ LC connector: SWL, LWL, ELWL<br/>16G FC SFP+ LC connector: SWL, LWL, ELWL<br/>10G FC SFP+ LC connector: SWL, LWL</p> <p>PB-DCX6-64P32G port blade<br/>4x32G FC QSFP+ MPO connector: SWL<br/>4x32G FC QSFP+ SMF LC connector: 2 km (fixed at 4x32G only)<br/>4x16G FC QSFP+ MPO connector: SWL</p> <p>FCoE QSFP+ MPO connector: 100GBASE-SR4, 4x25GbE<br/>FCoE QSFP+ MPO connector: 40GBASE-SR4, 4x10GbE<br/>FCoE QSFP+ LC connector: 40GbE BiDi</p> <p>SX6 Extension Blade<br/>32G FC SFP+ LC connector: SWL, LWL, ELWL<br/>16G FC SFP+ LC connector: SWL, LWL, ELWL<br/>10G FC SFP+ LC connector: SWL, LWL</p> <p>Ethernet QSFP+ MPO connector: 40GBASE-SR4, 40GBASE-LR4, 40GBASE-ER4<br/>Ethernet QSFP+ LC connector: 40GbE BiDi<br/>10GbE SFP+ LC connector: SR, LR, USR<br/>1GbE SFP+ LC connector: SR, LR<br/>1GbE SFP+ copper connector</p> <p>Core Routing (CR) blades, CR64-4 and CR64-8<br/>FC QSFP+ MPO connector: SWL, 2 km*<br/>4x32G FC QSFP+ SMF LC connector: SWL, 2 km</p> <p>Note: MPO connectors require 1x12 ribbon cable up to 66m over OM3 or 100m over OM4.</p> <p>*Use of the 2KM2-km ICL QSFP is subject to the following environmental ratings for maximum intake air temperature: 0—40°C at sea level; 0—35°C up to 1500m (4921 ft) elevation; and 0—30°C from 1500m- to 3000m (9843 ft) elevation.</p> |
| USB             | One USB port per control processor for firmware download, SupportSave, and configuration upload or download   |
| Fabric services | BB Credit Recovery; Advanced Zoning (Default Zoning, Port/WWN Zoning, Peer Zoning); Congestion Signaling; Dynamic Path Selection (DPS); Extended Fabrics; Fabric Performance Impact Notification; Fabric Vision; FDMI; FICON CUP; Flow Vision; F_Port Trunking; FSPF; Integrated Routing; ISL Trunking; Management Server; Name Server; NPIV; NTP v3; Port Decommission/Fencing; QoS Registered State Change Notification (RSCN); ; Target-Driven Zoning; Traffic Optimizer; Virtual Fabrics (Logical Switch, Logical Fabric); VMID+ and AppServer.   |
| Extension       | Supports DWDM, CWDM, and FC-SONET Devices; Fibre Channel; In-flight Compression (LZO) and Encryption (AES-GCM-256); BB Credit Recovery; FCIP; IP Extension; Adaptive Rate Limiting (ARL); Data Compression; Fast Write; Read/Write Tape Pipelining; QoS   |
| FICON           | FICON cascading; support for lossless DLS; FICON CUP; Advanced Accelerator for FICON (IBM z/OS Global Mirror and read/write Tape Pipelining. FICON connectivity is not supported on the PB-DCX6-64P32G blade)   |

## Connectrix ED-DCX7 Directors

| System Components           | Technical Specification  |
|-----------------------------|--|
| Fibre Channel ports         | ED-DCX7-8B: Up to 384 64Gb/s ports or up to 512 32Gb/s ports, universal (E_Port, F_Port, EX_Port, M_Port, D_Port, SIM Port, FICON)<br>ED-DCX7-4B: Up to 192 64Gb/s ports or up to 256 32Gb/s ports, universal (F_Port, E_Port, EX_Port, M_Port, D_Port, SIM Port, FICON) |
| Classes of service          | Class 2, Class 3, Class F (inter-switch frames)  |
| ANSI Fibre Channel protocol | FC-PH (Fibre Channel Physical and Signaling Interface standard)  |
| Port-to-port latency        | Local switching: 460 ns at 64Gb/s (including FEC as part of the FC standard).<br>Blade to blade: 1.4 µs  |

## Connectrix ED-DCX7 Directors

| High Availability     | Technical Specification  |
|-----------------------|--|
| Architecture          | Non-blocking shared memory; passive backplane; redundant active/passive control processor; redundant active/active core switching blades; redundant WWN cards  |
| Chassis power         | <p><b>ED-DCX7-8B</b></p> <ul style="list-style-type: none"> <li>Four power supplies required for AC low-line (100 VAC to 120 VAC).</li> <li>Two power supplies required for AC high-line (200 VAC to 240 VAC).</li> <li>Two power supplies required for high voltage AC (200 VAC to 277 VAC) or high voltage DC (240 VDC to 380 VDC).</li> <li>Chassis ships empty only. PSU and fans must be ordered separately. Three PSUs are required for 2+1 redundancy. Two PSUs provide system power, but four PSUs must be installed to provide power efficiency and 2+2 redundancy.</li> </ul> <p><b>ED-DCX7-4B</b></p> <ul style="list-style-type: none"> <li>Two power supplies required for AC low-line (100 VAC to 120 VAC).</li> <li>One power supply required for AC high-line (200 VAC to 240 VAC).</li> <li>One power supply required for high voltage AC (200 VAC to 277 VAC) or high voltage DC (240 VDC to 380 VDC).</li> <li>Chassis ships empty only. PSU and fans must be ordered separately. One PSU provides system power, but both PSUs must be installed to provide power efficiency and 1+1 redundancy.</li> </ul> |
| Cooling               | <p><b>ED-DCX7-8B</b></p> <ul style="list-style-type: none"> <li>Requires three fan tray assemblies. A failure condition is one failed fan from any fan tray.</li> <li>Each assembly contains two fans for a total of six fans. The system requires five of six functioning fans for the system requires five of six functioning fans for operation in the DCX7-8. One fan tray assembly can be hot-swapped and should be replaced immediately in the event of a failure.</li> </ul> <p><b>ED-DCX7-4B</b></p> <ul style="list-style-type: none"> <li>Requires two fan tray assemblies. A failure condition is one failed fan from any fan tray.</li> <li>Each assembly contains two fans for a total of four fans. The system requires three of four functioning fans for operation in the DCX7-4. One fan assembly can be hot-swapped and should be replaced immediately in the event of a failure.</li> </ul>   |
| Airflow               | Non-port-side intake (NPI) to port-side exhaust and port-side intake to non-port-side exhaust (NPE) options are available  |
| Solution availability | Designed to provide 99.999% uptime capabilities; hot-pluggable redundant power supplies, fans, WWN cards, processors, core switching, port blades, and optics; online diagnostics; non-disruptive firmware download and activation   |

## Connectrix ED-DCX7 Directors

| Management        | Technical Specification   |
|-------------------|---|
| Management        | Advanced Web Tools; Brocade SANnav Management Portal and SANnav Global View; Command Line Interface (CLI); HTTP/HTTPS; RESTful API; SSH; SNMP v1/v3 (FE MIB, FC Management MIB); trial licenses for add-on capabilities.  |
| Security          | AES-GCM-256 encryption on FC ISLs (E_Port); Device Connection Control (DCC); DH-CHAP (between switches and end devices); Fabric Configuration Server (FCS); FCAP switch authentication; FIPS 140-2 compliant; HTTPS; IP filtering; LDAP with IPv6; OpenLDAP; RADIUS; user-defined Role-Based Access Control (RBAC); Secure Boot; Secure Copy (SCP); SFTP; SSH v2; Switch Binding; TACACS+; TLS v1.2/v1.3; USGv6 compliant.  |
| Management access | 10/100/1000Mb/s Ethernet (RJ-45) per control processor; serial console port (RJ-45) and one USB per control processor module; DHCP/DHCPv6; call-home integration enabled through SANnav Management Portal   |
| Diagnostics       | Active Support Connectivity (ASC) and Brocade Support Link (BSL); built-in flow generator; ClearLink® optics and cable diagnostics, including electrical/optical loopback, link traffic/latency/distance; Fabric Performance Impact Monitoring (FPI); flow mirroring; Forward Error Correction; frame viewer; IO Insight for SCSI and NVMe monitoring; Monitoring and Alerting Policy Suite (MAPS); nondisruptive daemon restart; optics health monitoring; POST and embedded online/offline diagnostics, including environmental monitoring, FCping, and Pathinfo (FC traceroute); power monitoring; RAstrace logging; Rolling Reboot Detection (RRD); Syslog/Audit Log; VM Insight. |

## Connectrix ED-DCX7 Directors

| Mechanical    | Technical Specification   |
|---------------|---|
| Enclosure     | <p><b>ED-DCX7-8B:</b> 14U rack-mountable chassis; 27 in. to 31 in. and 22 in. rail kits for the four-post rack; mid-mount kit for the two-post rack.</p> <p><b>ED-DCX7-4B:</b> 8U rack-mountable chassis; 27 in. to 31 in. rail, 18 in. to 24 in. rail, and airflow diversion rack-mount kits for the four-post rack; mid-mount kit for the two-post rack.</p>  |
| Mounting      | Rack-mountable in a standard 19-inch EIA cabinet.   |
| Size          | <p><b>ED-DCX7-8B</b><br/>Height: 61.23 cm (24.11 in., 14U)<br/>Width: 43.74 cm (17.23 in.)<br/>Depth: 61.04 cm (24.04 in.)</p> <p><b>ED-DCX7-4B:</b><br/>Height: 34.45 cm (13.56 in., 8U)<br/>Width: 43.74 cm (17.23 in.)<br/>Depth: 61.04 cm (24.04 in.)</p> <p><b>ED-DCX7-4B with airflow diversion rack-mount kit</b><br/>Height: 40.00 cm (15.75 in., 9U)<br/>Width: 43.74 cm (17.23 in.)<br/>Depth: 61.29 cm (24.09 in.)</p> |
| System weight | <p><b>ED-DCX7-8B</b><br/>35.61 kg (78.5 lb) for chassis<br/>145.8 kg (321.5 lb) maximum fully populated configuration</p> <p><b>ED-DCX7-4B</b><br/>24.5 kg (54 lb) for chassis<br/>68.95 kg (152.0 lb) maximum fully populated configuration</p>  |

## Connectrix ED-DCX7 Directors

| Environment                    | Technical Specification   |
|--------------------------------|---|
| Temperature                    | Operating: 0°C to 40°C (32°F to 104°F)<br>Non-operating: -25°C to 70°C (-13°F to 158°F)   |
| Humidity                       | Operating humidity: 5% to 93% RH non-condensing at 40°C (104°F) with a maximum gradient of 10% per hour<br>Non-operating humidity: 10% to 93% RH non-condensing at 70°C (158°F)   |
| Altitude                       | Up to 3000 meters (9842 feet)   |
| Shock                          | Operating: 10g, 11 ms, half sine wave<br>Non-operating: 20g, 11 ms, half sine wave  |
| Vibration                      | Operating: 5 Hz to 10 Hz at +5 dB/oct; 10 Hz to 200 Hz at 0.0005 G <sup>2</sup> /Hz; 200 Hz to 500 Hz at -5 dB/oct; scale 0.5 grms<br><br>Non-operating: 3 Hz to 10 Hz at +5 dB/oct; 10 Hz to 200 Hz at 0.0065G <sup>2</sup> /Hz; 200 Hz to 500 Hz at -5 dB/oct; scale 1.12 grms  |
| Heat dissipation               | <b>ED-DCX7-8B</b><br>64 Gb/s 384-port configuration, including ICLs: Typical: 10,953 Btu/hr; Max: 158,530 Btu/hr.<br>Power consumed: Typical: 3210W; Max: 4550W.<br>Note: Input power is at 200 VAC with full PSU redundancy.<br><br><b>ED-DCX7-4B</b><br>64 Gb/s 192-port configuration, including ICLs: Typical: 5596 Btu/hr; Max: 7523 Btu/hr.<br>Power consumed: Typical: 1640W; Max: 2204W.<br>Note: Input power is at 200 VAC with full PSU redundancy. |
| Carbon Footprint Reports Links | <a href="#">ED-DCX7-8B</a> <a href="#">ED-DCX7-4B</a> (Documents provided and maintained by Broadcom. Inc.)   |

## Connectrix ED-DCX7

| Power                 | Technical Specification  |   |
|-----------------------|--|---|
| Supported power range | <p><b>Standard AC Power Supplies</b></p> <p><i>Input Voltage</i></p> <p>Standard AC input:<br/>Range: 90 VAC to 264 VAC auto-volt<br/>Nominal: 100 VAC to 240 VAC</p> <p><i>Power</i></p> <p>85 VAC to 132 VAC: 1450W<br/>180 VAC to 264 VAC: 2870W</p> <p><i>80 PLUS Platinum certified</i></p> | <p><b>High Voltage (HV) Power Supplies</b></p> <p><i>Input Voltage</i></p> <p>Range: 90 VAC to 132 VAC<br/>Nominal: 100 VAC to 120 VAC</p> <p>Range: 180 VAC to 305 VAC<br/>Nominal: 200 VAC to 277 VAC</p> <p>Range: 192 VDC to 400 VDC<br/>Nominal: 240 VDC to 380 VDC</p> <p><i>Power</i></p> <p>90 VAC to 132 VAC: 1450W<br/>180 VAC to 305 VAC: 2870W</p> <p>192 VDC to 400 VDC: 2870W</p> |
|                       | In-rush current  | 35A maximum, peak   |
| Frequency             | 50 Hz to 60 Hz (Nominal: 50 Hz to 60 Hz)   |   |





# Dell Technologies Services

Plan, deploy, manage and support  
IT transformation with our top-rated  
services

## Consulting

Dell Technologies Consulting Services provides industry professionals with a wide range of tools and the experience you need to design and execute plans to transform your business.

## Deployment

Accelerate technology adoption with ProDeploy Enterprise Suite. Trust our experts to lead deployments through planning, configuration and complex integrations.

## Management

Regain control of operations with flexible IT management options. Our Residency Services help you adopt and optimize new technologies and our Managed Services allow you to outsource portions of your environment to us.


## Support

Increase productivity and reduce downtime with ProSupport Enterprise Suite. Expert support backed by proactive and predictive artificial intelligence tools.

## Education

Dell Technologies Education Services help you develop the IT skills required to lead and execute transformational strategies. Get certified today.

Learn more at [DellTechnologies.com/Services](https://DellTechnologies.com/Services)



[Learn More](#) about  
Connectrix solutions



[Contact](#) a Dell Technologies Expert