

Dell EMC VxRail

Designed for VMware, with VMware, to enhance VMware

Dell EMC VxRail™, the jointly engineered hyperconverged infrastructure from Dell EMC and VMware, is the easiest and fastest way to extend a VMware environment. Powered by VMware vSAN™ and managed through the VMware vCenter interface, the VxRail provides existing VMware customers a consistent operating experience. As the foundation for Dell Technologies Cloud, VxRail is the first hyperconverged system fully integrated with VMware Cloud Foundation SDDC Manager delivering one, complete, automated platform.

VxRail is a distributed system consisting of common modular building blocks powered by the best in class VxRail HCI System Software that allows customers to start small and grow, scaling capacity and performance easily and non-disruptively from 3 to 64 nodes in a cluster. For edge deployments, users can choose a fixed two-node cluster or a three-node cluster if they desire future node expandability. Single-node scaling and storage capacity expansion provide a simple, predictable, cost effective “pay-as-you-grow” approach for future growth as needed.

VxRail HCI System Software ensures workloads are always up and running with intelligent lifecycle management (LCM) that automates non-disruptive upgrades, patches, node additions or retirement to ensure the VxRail infrastructure is in a continuously validated state. Coupled with detailed health reporting using infrastructure machine learning from SaaS multi-cluster management, it has never been easier to keep infrastructure smoothly running.

Built on PowerEdge servers. With a choice of 2nd Generation Intel® Xeon® Scalable or 2nd Generation AMD EPYC™ processors, VxRail is designed for today’s mission-critical workloads in mind, and also delivers multiple compute, memory, storage, network and graphics options to cover a wide variety of applications and workloads. VxRail continuously delivers new technologies such as Intel Optane persistent memory, NVMe cache and capacity drives, 100 Gb/s networking, and NVIDIA Quadro GPUs. With redundancy built in at every opportunity; from the SATA M.2 RAID 1 “BOSS”, high-efficiency redundant power supplies and multiple networking ports.

VxRail comes stacked with mission-critical data services at no additional charge. Data protection technology such as a starter set of licenses for Dell EMC RecoverPoint for VMs is included, with the option of adding Data Protection Suite for VMware and Data Domain Virtual Edition (DD VE) for larger environments that require more comprehensive data protection.

VxRail is also backed by Dell EMC’s world-class support with a single point of contact for both hardware and software and includes Dell EMC SRS for call-home and proactive two-way remote connection for remote monitoring, diagnosis, and repair to ensure maximum availability.

The VxRail portfolio includes:

E Series: Go Everywhere 1U/1Node with an all NVMe option and T4 GPUs for a wide range of use cases including artificial intelligence and machine learning. Also available in a single socket server powered by 2nd Generation AMD EPYC™ processor with up to 64 cores.

P Series: Performance intensive 2U/1Node platform with an all NVMe option, configurable with 1,2 or 4 Intel Xeon Scalable processors, or a single 2nd Gen AMD EPYC processor with up to 64 cores.

V Series: VDI-optimized 2U/1Node platform with GPU hardware for graphics-intensive desktops and workloads

D Series: Durable, ruggedized, short depth. Designed to withstand extreme conditions such as intense heat and cold, shock, vibration, dust, humidity, and EMI. Available in MIL-STD and DNV-GL Maritime certified configurations.

S Series: Storage dense 2U/1Node platform for demanding applications such as virtualized Microsoft SharePoint, Microsoft Exchange, big data, analytics, and video surveillance.

G Series: Compute dense 2U/4Node platforms for general purpose workloads.

Compute and memory					
	Processors	Cores	Frequency	Memory	Optane PMem
E Series	Single or dual Intel® Xeon® Scalable Gen 2	4–56	1.9 GHz–3.8 GHz	64 GB–3072 GB	128 GB–3072 GB
P Series	Single, dual, or quad Intel® Xeon® Scalable Gen 2	4–112	1.9 GHz–3.8 GHz	64 GB–6144 GB	128 GB–12288 GB
V Series	Dual Intel® Xeon® Scalable Gen 2	8–56	2.1 GHz–3.8 GHz	192 GB–3072 GB	N/A
D Series	Single or dual Intel® Xeon® Scalable Gen 2	4–48	1.9 GHz–3.8 GHz	64 GB–1024 GB	N/A
G Series	Single or dual Intel® Xeon® Scalable Gen 2	4–56	1.9 GHz–3.8 GHz	64 GB–2048 GB	N/A
S Series	Single or dual Intel® Xeon® Scalable Gen 2	4–56	1.9 GHz–3.8 GHz	64 GB–3072 GB	N/A
E Series (AMD)	Single 2nd Generation AMD EPYC™	8–64	2.0–3.2 GHz	64 GB–1024 GB	N/A
P Series (AMD)	Single 2nd Generation AMD EPYC™	8–64	2.0–3.7 GHz	64 GB–2048 GB	N/A

Storage						
	Cache	Flash	Hybrid	NVMe	Drive bays	Disk groups
E Series	Up to 1600 GB SAS 375 or 750 GB Optane 1600 GB NVMe	Up to 61.44 TB SAS <i>or</i> Up to 30.72 TB SATA	Up to 19.2 TB SAS	Up to 61.44 TB	10 x 2.5"	2
P Series	Up to 1600 GB SAS 375 or 750 GB Optane 1600 GB NVMe	Up to 153.6 TB SAS <i>or</i> Up to 76.8 TB SATA	Up to 48 TB SAS	Up to 153.6 TB	24 x 2.5"	4
V Series	Up to 1600 GB SAS	Up to 153.6 TB SAS <i>or</i> Up to 76.8 TB SATA	Up to 48 TB SAS	N/A	24 x 2.5"	4
D Series	Up to 1600 GB SAS	Up to 46.1 TB SAS <i>or</i> Up to 23.0 TB SATA	Up to 14.4 TB SAS	N/A	8 x 2.5"	2
G Series	Up to 1600 GB SAS 375 or 750 GB Optane 1600 GB NVMe	Up to 38.4 TB SAS <i>or</i> Up to 19.2 TB SATA	Up to 12 TB SAS	N/A	6 x 2.5"	1
S Series	Up to 1600 GB SAS	N/A	Up to 96 TB NL SAS	N/A	12 x 3.5" plus 2 x 2.5"	2
E Series (AMD)	Up to 1600 GB SAS 375 or 750 GB Optane 1600 GB NVMe	Up to 46.1 TB SAS <i>or</i> Up to 23.0 TB SATA	Up to 14.4 TB SAS	Up to 61.44 TB	8 x 2.5" (All flash/hybrid) <i>or</i> 10 x 2.5" (All NVMe)	2
P Series (AMD)	800 or 1600 GB SAS 375 GB Optane 1600 GB NVMe	Up to 153.6 TB SAS <i>or</i> Up to 76.8 TB SATA	N/A	Up to 153.6 TB	24 x 2.5"	4

Environmental and certifications					
	Ambient operating temperature	Storage temperature range	Operating relative humidity	Operating attitude with no deratings	Heat dissipation
E Series	10°C to 30°C 50°F to 86°F	-40°C to +65°C -40°F to +149°F	10% to 80% (non-condensing)	3048m approx. 10,000 ft	4100 BTU/h
P Series	10°C to 30°C 50°F to 86°F	-40°C to +65°C -40°F to +149°F	10% to 80% (non-condensing)	3048m approx. 10,000 ft	6000 BTU/h
V Series	10°C to 30°C 50°F to 86°F	-40°C to +65°C -40°F to +149°F	10% to 80% (non-condensing)	3048m approx. 10,000 ft	7500 BTU/h
D Series*	5°C to 45°C 41°F to 113°F	-40°C to +70°C -40°F to +158°F	5% to 85% (non-condensing)	15,000 ft for 1 hour after stabilization	2891 BTU/h
G Series	10°C to 30°C 50°F to 86°F	-40°C to +65°C -40°F to +149°F	10% to 80% (non-condensing)	3048m approx. 10,000 ft	9000 BTU/h (4-node chassis)
S Series	10°C to 25°C 50°F to 77°F	-40°C to +65°C -40°F to +149°F	10% to 80% (non-condensing)	3048m approx. 10,000 ft	4416 BTU/h
E Series (AMD)	10°C to 35°C 50°F to 95°F	-40°C to +65°C -40°F to +149°F	8% to 80% (non-condensing)	3048m approx. 10,000 ft	2107 BTU/h
P Series (AMD)	10°C to 35°C 50°F to 95°F	-40°C to +65°C -40°F to +149°F	8% to 85% (non-condensing)	3048m approx. 10,000 ft	6000 BTU/h

Networking, fibre channel, and GPU					
	Base network connectivity*	Max additional networking ports	Remote Management	Fibre Channel	GPU
E Series	2x25 GbE SFP28 or 4x10 GbE RJ45 or 4x10 GbE SFP+ or 4x1 GbE RJ45**	2x100GbE SFP28 or Up to 8x10 GbE RJ45 or Up to 4x10 GbE SFP+ or Up to 4x25 GbE SFP28	iDRAC9 Enterprise	Up to 4x 16/32Gb	1x-2x NVIDIA Tesla T4
P Series	2x25 GbE SFP28 or 2x10, 4x10 GbE RJ45 or 4x10 GbE SFP+ or 4x1 GbE RJ45**	2x100GbE SFP28 or Up to 16x10 GbE RJ45 or Up to 16x10 GbE SFP+ or Up to 8x25 GbE SFP28	iDRAC9 Enterprise	Up to 8x 16/32Gb	1x-2x NVIDIA Tesla M10****
V Series	2x25 GbE SFP28 or 4x10 GbE RJ45 or 4x10 GbE SFP+	2x100GbE SFP28 or Up to 16x10 GbE RJ45 or Up to 16x10 GbE SFP+ or Up to 8x25 GbE SFP28	iDRAC9 Enterprise	Up to 8x 16/32Gb	1x-6x NVIDIA Tesla T4 or 1x-3x Quadro RTX8000 or 1x-3x Quadro RTX6000 or 1x-3x NVIDIA A40 or 1x-3x NVIDIA Tesla V100S or 1x-2x NVIDIA Tesla M10***
D Series	2x25GbE SFP28 or 2x10GbE RJ45	2x25GbE SFP28 2x10GbE SFP+ 2x10GbE RJ45 4x10GbE RJ45	iDRAC9 Enterprise	N/A	1x NVIDIA Tesla T4
G Series	2x25GbE SFP28 or 2x10 GbE SFP+	2x100GbE SFP28 or Up to 4x10 GbE RJ45 or Up to 2x10 GbE SFP+ or 2x25 GbE SFP28	iDRAC9 Enterprise	N/A	N/A
S Series	2x25 GbE SFP28 or 2x10, 4x10 GbE RJ45 or 4x10 GbE SFP+ or 4x1 GbE RJ45**	2x100GbE SFP28 or Up to 12x10 GbE RJ45 or Up to 12x10 GbE SFP+ or Up to 6x25 GbE SFP28	iDRAC9 Enterprise	Up to 6x 16/32Gb	N/A
E Series (AMD)	2x10/25GbE SFP28 2x10 GbE RJ45	2x10/25GbE SFP28 2x10GbE SFP+ 4x10GbE RJ45	iDRAC9 Enterprise	Up to 2x 16/32Gb	N/A
P Series (AMD)	2x10/25GbE SFP28 2x10 GbE RJ45	2x10/25GbE SFP28 2x10GbE SFP+ 4x10GbE RJ45 2x 100GbE QSFP28	iDRAC9 Enterprise	Up to 2x 16/32Gb	1x-2x NVIDIA Tesla T4 or 1x NVIDIA Tesla V100s

*Base network connectivity must match for all nodes within a cluster (e.g. all nodes must use 10 GbE)
**1 GbE connectivity limited to single socket CPU and hybrid storage only
***M10 GPU can only address up to 1TB of memory
****Only available on the P580N

Power, dimensions, and weight					
	High-efficiency dual redundant AC PSU	High-efficiency dual redundant DC PSU	Redundant cooling fans	Physical dimensions	Weight
E Series	1100W 100V – 240V AC 1600W 200V – 240V AC	1100W 48V DC	8	42.8mm/1.68in H 434.0mm/17.09in W 733.82mm/29.61in D	21.9kg/48.28lb
P Series	1100W 100V – 240V AC 1600W 200V – 240V AC 2000W 200V – 240V AC 2400W 200V – 240V AC	1100W 48V DC	4-6	86.8mm/3.42in H 434mm/17.09in W 678.8mm/26.72in D	28.1kg/61.95lb
V Series	2000W 200V – 240V AC	N/A	6	86.8mm/3.42in H 434mm/17.09in W 678.8mm/26.72in D	28.1kg/61.95lb
D Series	550W 100 – 240V AC	600W - 48V DC	6	42.8 mm/1.68 in H 434 mm/17.09 in W 514.35 mm/20.06 in D	13.00kg/28lb
G Series	2000W 220V – 240V AC 2400W 220V – 240V AC	N/A	4	86.8mm/3.42in H 448.0mm/17.64in W 790mm/31.10in D	41.46kg/91.40lb
S Series	1100W 100V – 240V AC	1100W - 48V DC	6	86.8mm/3.42in H 434mm/17.09in W 678.8mm/26.72in D	33.1kg/72.91lb
E Series (AMD)	550W 110V – 240VAC	N/A	6	42.8mm/1.68in H 434.0mm/17.09in W 657.25mm/25.88in D	15.8kg/34.83lb

P Series (AMD)	1100W 100V – 240V AC 1600W 100V – 240V AC	1100W - 48V DC	6	86.8mm/3.42in H 434mm/17.09in W 647.01mm/25.47in D	23.72kg/52.29lb
Services and Support					
Services	ProDeploy: Including pre-deployment planning, project management and 24x7 onsite installation				
	ProDeploy Plus: Additional value including post-deployment assistance and training credits				
Support	ProSupport: Keep your hardware and software running smoothly with 24x7 access to technology engineers as well as proactive and preventive technologies to help you get ahead of issues.				
	ProSupport Plus: Optimize your critical systems and free up staff to innovate the business. ProSupport Plus provides an assigned Technology Service Manager and access to specialized support engineers that quickly diagnose issues and provide personalized guidance to avoid problems before they ever impact your business.				



[Learn more](#) about Dell EMC VxRail



[Contact](#) a Dell EMC Expert



[View more](#) resources



Join the conversation with #VxRail