



# DELL EMC POWERSWITCH N1500 SERIES SWITCHES

## Extending enterprise features to small and mid-sized businesses

The N1500 switch series offers a power-efficient Gigabit Ethernet (GbE) network-access switching solution with integrated 10GbE uplinks. With high-performance capabilities and wire-speed performance, utilizing a non-blocking architecture to easily handle unexpected traffic loads, the switches offer simple management and scalability via an 40Gbps (full-duplex) high availability stacking architecture that allows management of up to four switches from a single IP address. An integrated 80PLUS-certified power supply and features such as Energy-Efficient Ethernet and short cable detection provide energy efficiency to help decrease power and cooling costs.

### Modernize campus network architectures

Modernize campus network architectures with a power-efficient and resilient 1/10GbE switching solution with Power over Ethernet Plus (PoE+). Select N1500 models offer 24 or 48 ports of PoE+ to deliver clean power to network devices such as wireless access points (APs), Voice-over-IP (VoIP) handsets, video conferencing systems and security cameras.

### Leverage familiar tools and practices

All N-Series switches include Dell EMC Networking OS6, designed for easier deployment, greater interoperability and a lower learning curve for network administrators. OS6 common command line interface (CLI) and graphic user interface (GUI) using a well-known command language gets skilled network administrators productive quickly. With USB auto-configuration, network administrators can rapidly deploy mirrored configurations to numerous devices by simply inserting a USB key.

### Deploy with confidence at any scale

N1500 series switches help create performance assurance with a data rate up to 176Gbps (full duplex) and a forwarding rate up to 164Mpps. Scale easily by stacking with 10GbE ports. Switch stacks of up to 200 1GbE ports can be managed from a single screen using the highly available stacking architecture for high-density aggregation with seamless redundant availability. N-Series switches help provide certainty with a lifetime warranty that covers software upgrades, hardware repair or replacement, and optics and cables purchased with the switch.\*

\*Select Networking products carry a Lifetime Limited Warranty with Basic Hardware Service (repair or replacement) for life. Repair or replacement does not include troubleshooting, configuration, or other advanced service provided by Dell EMC ProSupport. For details, visit <https://www.dell.com/en-us/work/shop/networkingwarranty/cp/networkingwarranty>.

### Hardware, performance and efficiency

- Up to 48 line-rate GbE RJ-45 ports and four integrated 10GbE SFP+ ports.
- Up to 48 ports of PoE+ with an optional external power supply.
- Up to 200 1GbE ports in a 4-unit stack for high-density, high-availability in IDFs, MDFs and wiring closets.
- Non-stop forwarding and fast failover in stack configurations.
- Energy-Efficient Ethernet and lower power PHYs reduce power to inactive ports and idle links, providing energy savings from the power cord to the port.
- Fresh Air compliance for operation in environments up to 113°F (45°C) helps reduce cooling costs in temperature-constrained deployments.

### Deploying, configuring and managing

- USB auto-configuration rapidly deploys the switch without setting up complex TFTP configurations or sending technical staff to remote offices.
- Management via an intuitive and familiar CLI, embedded web server (GUI), SNMP-based management console application (including Dell EMC OpenManage Network Manager), Telnet or serial connection.
- Private VLAN extensions and Private VLAN Edge support.

Product	Description
<b>N1500 series</b>	N1524: 24x RJ45 10/100/1000Mb auto-sensing ports, 4x SFP+ ports, 1 integrated 40W PSU N1524P: 24x RJ45 10/100/1000Mb PoE+ (up to 30.8w) auto-sensing ports, 4x SFP+ ports, 1 integrated 600W PSU (requires C15 plug) N1548: 48x RJ45 10/100/1000Mb auto-sensing ports, 4x SFP+ ports, 1 integrated 100W PSU N1548P: 48x RJ45 10/100/1000Mb PoE+ (up to 30.8w) auto-sensing ports, 4x SFP+ ports, 1 integrated 600W PSU (requires C15 plug)
<b>Power cords</b>	C13 to NEMA 5-15, 3M C13 to C14, 2M C15 to NEMA 5-15, 2M (C15 for POE N-Series only)
<b>Power supplies (optional)</b>	RPS720 external power supply for N1500 non-POE (720 watts): N1524 and N1548 (sold separately) MPS1000 external power supply for N1500 PoE+ switches (1000 watts): N1524P and N1548P (sold separately)
<b>Optics (optional)</b>	Transceiver, SFP, 1000BASE-T Transceiver, SFP, 1000BASE-SX, 850nm wavelength, up to 550m reach Transceiver, SFP, 1000BASE-LX, 1310nm wavelength, up to 10km reach Transceiver, SFP, 1000BASE-ZX, 1550nm wavelength, up to 80km reach Transceiver, SFP+, 10GbE, SR, 850nm wavelength, up to 300m reach Transceiver, SFP+, 10GbE, LR, 1310nm wavelength, up to 10km reach Transceiver, SFP+, 10GbE, ER, 1550nm wavelength, up to 40km reach
<b>Cables (optional)</b>	Dell Technologies Networking cable, SFP+ to SFP+, 10GbE, copper twinax direct

## Technical specifications

### Physical

4 integrated front 10GbE SFP+ dedicated ports,  
2 10GbE can be used as stacking ports  
USB (Type A) port for configuration via USB flash drive  
Auto-negotiation for speed and flow control  
Auto MDI/MDIX, port mirroring  
Flow-based port mirroring  
Broadcast storm control  
Energy-Efficient Ethernet per port settings  
Redundant variable speed fans  
Air flow: I/O to power supply  
Integrated power supply: 40W AC (N1524),  
100W AC (N1548), 600W AC (N1524P,  
N1548P)  
RJ45 console port with RS232 signaling (RJ-45 to  
female DB-9 connector cable included)  
Dual firmware images on-board  
Switching engine model: Store and forward

### Chassis

Size (1RU, H x W x D):  
N1524 and N1548: 1.7 in x 17.3 in x 10.1 in  
(43.2 mm x 440.0 mm x 257.0 mm)  
N1524P and N1548P: 1.7 in x 17.3 in x 15.2 in  
(43.2 mm x 440.0 mm x 387.0 mm)  
Approximate weight: 6.6lbs/3kg (N1524),  
12.8lbs/5.8kg (N1524P), 8.8lbs/4kg (N1548),  
15.4lbs/7kg (N1548P)  
Rack mounting kit with 2 mounting brackets, bolts  
and cage nuts

### Environmental

Power supply efficiency: 80% or better in all  
operating modes  
Max. thermal output (BTU/hr): 103.1 (N1524),  
2972 (N1524P), 152.2 (N1548),  
5824.3 (N1548P)  
Power consumption max (watts): 30.2 (N1524),  
871 (N1524P), 44.6 (N1548), 1704 (N1548P)  
Operating temperature: 32° to 113°F (0° to 45°C)  
Operating humidity: 95%  
Storage temperature: -40° to 149°F  
(-40° to 65°C)  
Storage relative humidity: 85%

### Performance

MAC addresses: 16K  
Static routes: 256 (IPv4)/128 (IPv6)  
Dynamic routes: 256 (IPv4)  
Switch fabric capacity: 128Gbps (N1524 and  
N1524P) (full duplex); 176Gbps (N1548 and  
N1548P)  
Forwarding rate: 128Mpps (86 Gbps) N1524 and  
N1524P  
164Mpps (110 Gbps) N1548 and N1548P  
Link aggregation: 64 LAG groups, 144 dynamic  
ports per stack, 8 member ports per LAG  
Priority queues per port: 8  
Line-rate Layer 2 switching: All (non-blocking)  
Line-rate Layer 3 routing: All (non-blocking)  
Flash memory: 256MB  
Packet buffer memory: 1.5MB  
CPU memory: 1GB  
RIP routing interfaces: 128  
VLAN routing interfaces: 128  
VLANs supported: 512  
Protocol-based VLANs: Supported  
ARP entries: 2,048 (IPv4)/512 (IPv6)  
NDP entries: 400  
Access control lists (ACL): Supported  
MAC and IP-based ACLs: Supported  
Time-controlled ACLs: Supported  
Max number of ACLs: 100  
Max ACL rules system-wide: 2,048  
Max rules per ACL: 1,023  
Max ACL rules per interface (IPv4): 1,023  
(ingress), 1,023 (egress)  
Max ACL rules per interface (IPv6): 512 (ingress),  
509 (egress)  
Max VLAN interfaces with ACLs applied: 24

### IEEE compliance

802.1AB LLDP  
Dell Voice VLAN  
Dell ISDP (inter-operates with devices running CDP)  
802.1D Bridging, Spanning Tree  
802.1p Ethernet Priority (User Provisioning  
and Mapping)  
Dell Adjustable WRR and Strict Queue Scheduling

802.1Q VLAN Tagging, Double VLAN Tagging,  
GVRP  
802.1S Multiple Spanning Tree (MSTP)  
802.1v Protocol-based VLANs  
802.1W Rapid Spanning Tree (RSTP)  
Dell RSTP-Per VLAN (compatible with Cisco's  
RPVST+)  
Dell Spanning tree optional features: STP root  
guard, BPDU guard, BPDU filtering  
Network Access Control, Auto VLAN  
802.1X Logical Link Control  
802.2 10BASE-T  
802.3 Gigabit Ethernet (1000BASE-T)  
802.3ab Frame Extensions for VLAN Tagging  
802.3ac Link Aggregation with LACP  
802.3ad 10 Gigabit Ethernet (10GBASE-X)  
802.3at PoE+ (N1524P and N1548P)  
802.3AX LAG Load Balancing  
802.3az Energy Efficient Ethernet (EEE)  
802.3u Fast Ethernet (100BASE-TX) on  
Management Ports  
802.3x Flow Control  
802.3z Gigabit Ethernet (1000BASE-X)  
ANSI LLDP-MED (TIA-1057)  
MTU 9,216 bytes

### RFC compliance and additional features

#### General Internet protocols

General Internet protocols are supported. For a  
detailed list, please contact your Dell Technologies  
representative.

#### General IPv4 protocols

General IPv4 protocols are supported. For a  
detailed list, please contact your Dell Technologies  
representative.

#### General IPv6 protocols

General IPv6 protocols are supported. For a  
detailed list, please contact your Dell Technologies  
representative.

#### Layer 3 functionality

1058 RIPv1  
2082 RIP-2 MD5 Auth  
1724 RIPv2 MIB Extension 2453  
RIPv2

## Multicast

2932 IPv4 MIB  
4541 IGMP v1/v2/v3 Snooping and Querier  
IEEE 802.1ag draft 8.1-Connectivity Fault Management

## Quality of service

2474 DiffServ Field  
Dell Flow Based QoS  
2475 DiffServ Architecture Services Mode  
2597 Assured Fwd PHB (IPv4/IPv6)  
Dell L4 Trusted Mode  
Dell Port Based QoS (TCP/UDP) Services Mode  
Dell UDLD

## Network management and security

1155 SMIv1  
1157 SNMPv1  
1212 Concise MIB Definitions  
1213 MIB-II  
1215 SNMP Traps  
1286 Bridge MIB  
1442 SMIv2  
1451 Manager-to-Manager MIB  
1492 TACACS+  
1493 Managed Objects for Bridges MIB  
1573 Evolution of Interfaces  
1612 DNS Resolver MIB Extensions  
1643 Ethernet-like MIB  
1757 RMON MIB  
1867 HTML/2.0 Forms with File Upload Extensions  
1901 Community-based SNMPv2  
1907 SNMPv2 MIB  
1908 Coexistence Between SNMPv1/v2  
2011 IP MIB  
2012 TCP MIB  
2013 UDP MIB  
2068 HTTP/1.1  
2096 IP Forwarding Table MIB  
2233 Interfaces Group using SMIv2  
2246 TLS v1  
2271 SNMP Framework MIB  
2295 Transport Content Negotiation  
2296 Remote Variant Selection  
2576 Coexistence Between SNMPv1/v2/v3  
2578 SMIv2  
2579 Textual Conventions for SMIv2  
2580 Conformance Statements for SMIv2  
2613 RMON MIB  
2618 RADIUS Authentication MIB  
2620 RADIUS Accounting MIB  
2665 Ethernet-like Interfaces MIB  
2674 Extended Bridge MIB  
2737 ENTITY MIB  
2818 HTTP over TLS  
2819 RMON MIB (groups 1, 2, 3, 9)  
2863 Interfaces MIB  
2865 RADIUS  
2866 RADIUS Accounting  
2868 RADIUS Attributes for Tunnel Prot.  
2869 RADIUS Extensions  
3410 Internet Standard Mgmt. Framework  
3411 SNMP Management Framework  
3412 Message Processing and Dispatching  
3413 SNMP Applications  
3414 User-based security model

3415 View-based control model  
3416 SNMPv2  
3418 SNMP MIB  
3577 RMON MIB  
3580 802.1X with RADIUS  
3737 Registry of RMOM MIB  
4086 Randomness Requirements  
4113 UDP MIB  
4251 SSHv2 Protocol  
4252 SSHv2 Authentication  
4253 SSHv2 Transport  
4254 SSHv2 Connection Protocol  
4419 SSHv2 Transport Layer Protocol  
4521 LDAP Extensions  
4716 SECSH Public Key File Format  
5246 TLS v1.2  
6101 SSL  
Dell Enterprise MIB supporting routing features draft-ietf-hubmib-etherif-mib-v3-00.txt (Obsoletes RFC 2665)

## Regulatory, environment and other compliance

**Safety and emissions**  
Australia/New Zealand: ACMA RCM Class A  
Canada: ICES Class A; cUL  
China: CCC Class A; NAL  
Europe: CE Class A  
Japan: VCCI Class A  
USA: FCC Class A; NRTL UL; FDA 21 CFR 1040.10 and 1040.11  
Eurasia Customs Union: EAC  
Germany: GS mark  
Product meets EMC and safety standards in many countries inclusive of USA, Canada, EU, Japan, China. For more country-specific regulatory information and approvals, please see your Dell Technologies representative.

## RoHS

Product meets RoHS compliance standards in many countries inclusive of USA, EU, China, and India. For more country-specific RoHS compliance information, please see your Dell Technologies representative.  
EU WEEE  
EU Battery Directive  
REACH

## Energy

Japan: JEL  
Certifications (available or coming soon)  
Available with US Trade Agreements Act (TAA) compliance.  
N-Series products have the necessary features to support a PCI-compliant network topology.

Dell LAG MIB  
Support for 802.3ad  
Functionality  
Dell sflow version 1.3 draft 5  
Dell 802.1x Monitor Mode  
Dell Custom Login Banners  
Dell Dynamic ARP Inspection  
Dell IP Address Filtering  
Dell Tiered Authentication  
Dell RSPAN  
Dell OpenFlow 1.3  
Dell Python Scripting  
Dell Support Assist  
HiveManager NG



**Dell Technologies Services**

Plan, deploy, manage and support your IT transformation with our top-rated services

## Consulting

Dell Technologies Consulting Services provides industry professionals with a wide range of tools and the experience you need to design and execute plans to transform your business.

## Deployment

Accelerate technology adoption with ProDeploy Enterprise Suite. Trust our experts to lead deployments through planning, configuration and complex integrations.

## Management

Regain control of operations with flexible IT management options. Our Residency Services help you adopt and optimize new technologies and our Managed Services allow you to outsource portions of your environment to us.

## Support

Increase productivity and reduce downtime with ProSupport Enterprise Suite. Expert support backed by proactive and predictive artificial intelligence tools.

## Education

Dell Technologies Education Services help you develop the IT skills required to lead and execute transformational strategies. Get certified today.

Learn more at [DellTechnologies.com/Services](https://DellTechnologies.com/Services)

Learn more at [DellTechnologies.com/Networking](https://DellTechnologies.com/Networking)